

















Group 050 Holesaws  Page 230 - 231	Group 055 Rotary Masonry Drills  Page 227 - 228	Group 057 SDS Masonry Drills  Page 229	Group 259 Air Products  Page 200
Group 268 Magnetic Drilling Machines  Page 218	Group 270 Air Tools  Page 202 - 217	Group 271 Machine Tools  Page 217, 219	Group 273 Pressure Washers  Page 221
Group 279 Water Pumps  Page 220	Group 279 Industrial Power Tools  Page 224 - 225	Group 280 Sanding Pads & Polishing Foams  Page 226 - 234	Group 280 Polishing Pads & Circular Saw Blades  Page 234
Group 288 Multi-Tooth Drilling Cutters  Page 218	Group 289 Power Tool Chisels  Page 235	Group 291 Push-Fit Pneumatic Fittings  Page 236 - 237	Group 295 Wire Wheels & Brushes  Page 240
Group 904 Torches  Page 243 - 247			

Air & Power Tools

Product Groups

200 - 904


Contents

Description	Group	Page
AIR POWER TOOLS		
Airline Fittings	259	194 - 197 & 238 - 239
Air Preparation	259	198 - 199
Blow Guns	259	202
Balancers	280	201
Die Grinders	270	207 - 209
Drills	270	204 - 205
Grinders	270	206
Hammers	270	210 - 211
Hoses	258	201
Micro Die Grinders	270	209
Needle Scalars	269	210 - 211
Nibblers, Saws & Shears	270	210
Ratchets	270	215
Riveters	270	212 - 217
Sanders	270	212 - 214
Screwdrivers	270	214 - 215
Spray Guns	259	203
Tyre Inflators & Gauges	259	200
Wrenches	270	216 - 217
CORDLESS POWER TOOLS		
18V	279	223
12V	279	222
Batteries & Chargers	280	222
CORDED POWER TOOLS		
115mm Angle Grinders	266	224
Engraver	279	225
Heat Guns	279	224

Description	Group	Page
OTHER POWER TOOLS & ACCESSORIES		
Bench Grinders	261	224
Circular Saw Blades	280	234
Holesaws	050	230 - 231
Jigsaw Blades	240	232 - 233
Machine Tools - Milling/Drilling	271	217
Machine Tools - Sanders	271	219
- Saws	271	219
Magnetic Drilling Machines	268	218
Masonry Drills	055	227 - 229
Multi-Tools	279	225
Multi-Tooth Drilling Cutters	288	218
Polishing Pads	280	234
Power Tool Chisels	289	235
Pressure Washers	279	221
Sanding Pads	280	226
Vacuum Cleaners	273	220
Water Pumps	279	220
Wire Wheels & Brushes	295	240
MISCELLANEOUS ITEMS		
Batteries	904	247
Portable Site Lights	282	242
Torches	904	243 - 247

KOBE 'Standard' Couplings

Compatible with the range of standard Kobe adaptors. Steel construction. Ideal for use in engineering/workshop environment.



Female Threaded




Male Threaded

Thread Size	Thread Type	Order Code KBE-259
1/4 BSPT	Female	-6940Y
3/8 BSPT	Female	-6946F
1/4 BSPT	Male	-6944D

Slim Profile Coupling

Designed for use with Kobe airline couplings. 'Third level' zinc plated for protection against corrosion.




Male Threaded


Thread Size	Thread Type	Order Code KBE-259
1/4 BSPT	Male	-6983A

Coupling Adaptors

Designed for use with Kobe airline couplings. 'Third level' zinc plated for protection against corrosion.



Female Threaded



Male Threaded



Integral Tailpiece

Thread Size	Thread Type	Order Code KBE-259
1/4 BSPT	Female	-6992X
3/8 BSPT	Male	-6996D
1/4 Bore	Tailpiece	-6983P
3/8 Bore	Tailpiece	-6984T

PCL Non-Corrosible Couplings

For specialist applications such as breathing air, non-spark, damp or high condensation environments. Brass body & valves.

Nominal Bore: 4.8mm.
Flow rate @ 6 bar - 43cfm @ 100psi.
Maximum working pressure: 14 bar/200psi.
Adaptor series: Standard.
Interchangeable: Cejn 295, Rectus 19.



Male Thread

Product Number	Thread Size	Order Code PCL-259
Male Thread		
AC32CM	R _{1/4}	-1985H
Female Thread		
AC32CF	Rp _{3/8}	-1985L

PCL Airflow Couplings

Airflow is the original quick-release coupling with over 50 years of design enhancements and manufactured in the UK to the highest standard.

Nominal Bore: 4.8mm.
Flow rate @ 6 bar - 43cfm @ 100psi.
Maximum working pressure: 14bar/200psi.
Adaptor series: Standard.
Interchangeable: Cejn 295, Rectus 19.



Male Thread



Hose Tailpiece

Product Number	Thread Size	Order Code PCL-259
Male Thread		
AC21CM	R _{1/4}	-1944D
AC21EM	R _{3/8}	-1946K
AC21JM	R _{1/2}	-1946W
Female Thread		
AC21CF	Rp _{1/4}	-1940Y
AC21EF	Rp _{3/8}	-1946F
AC21JF	Rp _{1/2}	-1946R
Hose Tailpiece		
AC21R	7mm/ _{1/4}	-1947F
AC21S	8mm/ _{5/16}	-1947P
AC21T	10mm/ _{3/8}	-1948D
Twin Coupling		
AC6103	Hosetail	-1981A

Vertex Couplings

Designed and made in the UK, these couplings have a double action feature. Ideal for trailing hoses such as air tools.

Nominal Bore: 4.8mm.
Flow rate @ 6 bar - 43 cfm @ 100psi.
Maximum working pressure: 14 bar/200psi.
Adaptor series: Standard.
Interchangeable: Cejn 295, Rectus 19.



Male Thread



Female Thread

Product Number	Thread Size	Order Code PCL-259
Male Thread		
AC91CM	R _{1/4}	-1983D
AC91EM	R _{3/8}	-1983J
AC91JM	R _{1/2}	-1983K
Female Thread		
AC91CF	Rp _{1/4}	-1983A
AC91EF	Rp _{3/8}	-1983M
AC91JF	Rp _{1/2}	-1983Q
Hose Tailpiece		
AC91R	7mm/ _{1/4}	-1983R
AC91S	8mm/ _{5/16}	-1983S
AC91T	10mm/ _{3/8}	-1983T
Twin Coupling		
AC6503	Hosetail	-1981L




Group 291


Standard Adaptors

The Standard Air Line Adaptor is suitable for most compressed air applications, this range of adaptors has become the benchmark for quality and reliability.

Nominal Bore: 4.8mm.
Flow rate @ 6 bar - 43cfm @ 100psi.
Maximum working pressure: 14 bar/200psi.
Interchangeable: Cejn 295, Rectus 19.



Male Thread



Female Thread



Hose Tailpiece

Product Number	Thread Size	Order Code PCL-259
Male Thread		
ACA2593	R _{1/4}	-1985R
ACA6909	R _{3/8}	-1996D
ACA6584	R _{1/2}	-1996H
Female Thread		
ACA2746	Rp _{1/4}	-1992X
ACA6582	Rp _{3/8}	-1996B
ACA6583	Rp _{1/2}	-1996L
Hose Tailpiece		
ACA2486	4.78mm/ _{3/16}	-1996P
ACA1793	6.35mm/ _{1/4}	-1983P
ACA2487	7.9mm/ _{5/16}	-1984Q
ACA2488	9.5mm/ _{3/8}	-1984T
ACA9438	13mm/ _{1/2}	-1996T

Safeflow Couplings

Quick release coupling and offers a two-stage self venting release - totally eliminating the dangers of hose whip.

Nominal Bore: 4.8mm.
Flow rate @ 6 bar - 43cfm @ 100psi.
Adaptor series: Standard.
Interchangeable: Cejn 295, Rectus 19.



Male Thread



Female Thread



Hose Tailpiece

Product Number	Thread Size	Order Code PCL-259
Male Thread		
SC21CM	R _{1/4}	-4520A
SC21EM	R _{3/8}	-4522C
SC21JM	R _{1/2}	-4524E
Female Thread		
SC21CF	Rp _{1/4}	-4518T
SC21EF	Rp _{3/8}	-4521B
SC21JF	Rp _{1/2}	-4523D
Hose Tailpiece		
SC21R	7mm/ _{1/4}	-4528M
SC21S	8mm/ _{5/16}	-4528Q
SC21T	10mm/ _{3/8}	-4532R



Group 294

XF Couplings

Offers excellent flow character providing the workshop with increase airflow when required and enhance tool efficiency.

Nominal Bore: 7.4mm.

Flow rate @ 6 bar -

43cfm @ 100psi 2,200 l/min.

Adaptor series: XF Series.

Interchangeable:

Cein 320, Legris 25/26, Norgren 234/238, Rectus 25/26, Schrader Intercheck 35.



Male Thread



Female Thread

Product Number	Thread Size	Order Code PCL-259
Male Thread		
AC71CM	R $\frac{1}{4}$	-1981K
AC71EM	R $\frac{3}{8}$	-1981P
AC71JM	R $\frac{1}{2}$	-1981W
Female Thread		
AC71CF	Rp $\frac{1}{4}$	-1981H
AC71EF	Rp $\frac{3}{8}$	-1981M
AC71JF	Rp $\frac{1}{2}$	-1981T

XF Adaptors

Case hardened and corrosive resistant finish for longer life.

Nominal Bore: 7.4mm.

Flow rate @ 6 bar -

43 cfm @ 100 psi 2,200 l/min.


Adaptor series: XF Series.

Interchangeable:

Cein 320, Legris 25/26, Norgren 234/238, Rectus 25/26, Schrader Intercheck 35.



Male Thread



Female Thread



Hose Tailpiece

Product Number	Thread Size	Order Code PCL-259
Male Thread		
AA7101	R $\frac{1}{8}$	-1101Z
AA7102	R $\frac{1}{4}$	-1102A
AA7103	R $\frac{3}{8}$	-1103C
AA7104	R $\frac{1}{2}$	-1104E
Female Thread		
AA7105	Rp $\frac{1}{8}$	-1105J
AA7106	Rp $\frac{1}{4}$	-1106K
AA7107	Rp $\frac{3}{8}$	-1107M
AA7108	Rp $\frac{1}{2}$	-1108P
Hose Tailpiece		
AA7109	4mm	-1110E
AA7110	6mm	-1110R
AA7111	8mm	-1111S
AA7112	9mm	-1111X
AA7112	10mm	-1112B
AA7113	13mm	-1113C

60 Series Couplings

Quick release coupling and offers greater airflow characteristics for the larger air tool application. Hardened sholder helps prevent accidental disconnection.

Nominal Bore: 7.1mm.

Flow rate @ 6 bar - 60cfm @ 100psi.

Maximum working pressure: 14 bar/200psi.

Adaptor series: 60 Series.



Female Thread

Product Number	Thread Size	Order Code PCL-259
Male Thread		
AC4CM	R $\frac{1}{4}$	-1953K
AC4EM	R $\frac{3}{8}$	-1959V
AC4JM	R $\frac{1}{2}$	-1960B
Female Thread		
AC4CF	Rp $\frac{1}{4}$	-1980L
AC4EF	Rp $\frac{3}{8}$	-1958T
AC4JF	Rp $\frac{1}{2}$	-1959X

60 Series Adaptors

Case hardened for longer life and corrosive resistant finish.

Nominal Bore: 7.1mm.

Flow rate @ 6 bar - 500 l/min.

Maximum working pressure: 14 bar/200psi.

Coupling: 60 Series.



Male Thread

Product Number	Thread Size	Order Code PCL-259
Male Thread		
ACA2657	R $\frac{1}{4}$	-1986M
ACA2661	R $\frac{3}{8}$	-1988T
Female Thread		
ACA2653	Rp $\frac{1}{4}$	-1986D
ACA2660	Rp $\frac{3}{8}$	-1987S
Hose Tailpiece		
ACA2654	8mm	-1986N
ACA2658	10mm	-1986P
ACA2659	13mm	-1986R

KOBE XF Series Adaptor

EURO 130

Corrosive resistant finish.

For use with Kobe airline couplings.



Male Threaded

Thread Size	Thread Type	Order Code KBE-259
$\frac{1}{4}$ BSPT	Male	-6102A

100 Series Couplings

Designed and made in the UK, these couplings offers greater airflow characteristics for larger air tool applications.

Nominal Bore: 10.3mm.

Flow rate @ 6 bar - 117cfm @ 100psi.

Maximum working pressure: 14 bar/200.

Adaptors: 100 Series Adaptors.



Male Thread



Female Thread

Product Number	Thread Size	Order Code PCL-259
Male Thread		
AC5EM	R3/8	-1980Q
AC5JM	R1/2	-1980X
Female Thread		
AC5EF	Rp3/8	-1980N
AC5JF	Rp1/2	-1980T

100 Series Adaptors

Designed and made in the UK, these couplings offers greater airflow characteristics for larger air tool applications.

Nominal Bore: 10.3mm.

Flow rate @ 6 bar - 117cfm @ 100psi.

Maximum working pressure: 14 bar/200.

Adaptors: 100 Series Adaptors.



Male Thread



Female Thread



Hose Tailpiece

Product Number	Thread Size	Order Code PCL-259
Male Thread		
ACA2999	R $\frac{1}{4}$	-1994W
ACA3035	R $\frac{3}{8}$	-1995G
Female Thread		
ACA2994	Rp $\frac{3}{8}$	-1994M
Hose Tailpiece		
ACA3037	9.5mm/ $\frac{3}{8}$	-1995L
ACA3036	12.7mm/ $\frac{1}{2}$	-1995J

Emergency Coupling Kit

Includes couplings, adaptors, hose tails, hose connectors, hose clips and PTFE tape to convert or repair an airline connection. Ideal to keep in workshop or van.



Product Number	Order Code PCL-259
ACKIT01	-5020K



Standard Schrader Couplings

Schrader couplings and adaptors, generally suitable for most fixed compressed air applications. Twist locking feature

Nominal Bore: 5mm.
Flow rate @ 6 bar - 900 l/min.
Maximum working pressure: 17 bar/250psi.
Adaptor series: Standard.
Interchangeable: Cejn 317, Rectus 17.



Product Number	Thread Size	Order Code PCL-259
Male Thread		
ACS102	R $\frac{1}{4}$	-2002C
ACS103	R $\frac{3}{8}$	-2002E
Female Thread		
ACS101	G $\frac{1}{4}$	-2002A

Standard Schrader Adaptors

When connected to the coupling, the adaptor can swivel, thereby eliminating hose kinks.

Nominal Bore: 5mm.
Flow rate @ 6 bar - 900 l/min.
Maximum working pressure: 17 bar/250psi.
Coupling series: Standard.
Interchangeable: Cejn 317, Rectus 17.



Product Number	Thread Size	Order Code PCL-259
Male Thread		
ACAS104	R $\frac{1}{4}$	-1998G
Female Thread		
ACAS105	Rp $\frac{1}{4}$	-1998J
Hose Tailpiece		
ACAS101	6mm	-1998A
ACAS103	8mm	-1998E
ACAS102	10mm	-1998C


KOBE Genuine 'Schrader' Couplings

Designed for use with KOBE airline couplings. 'Third level' zinc plated for protection against corrosion.



Thread Size	Thread Type	Order Code KBE-259	NA
$\frac{1}{4}$ " BSPT	Female	-7002A	NA

Genuine 'Schrader' Coupling Adaptors
 Corrosive resistant finish. For use with Kobe airline couplings.



Thread Size	Thread Type	Order Code KBE-259
$\frac{1}{4}$ BSPT	Male	-6998G
$\frac{1}{4}$ BSPT	Female	-6998J
$\frac{1}{4}$ Bore	Tailpiece	-6998A

Heavy Duty Schrader Couplings

Schrader heavy duty couplings and adaptors, generally suitable for most fixed compressed air applications. Twist locking feature.

Nominal Bore: 8.5mm.
Flow rate @ 6 bar - 500 l/min.
Maximum working pressure: 17 bar/250psi.
Adaptor series: Heavy Duty Adaptors.
Interchangeable: Cejn 499, Rectus 68.



Product Number	Thread Size	Order Code PCL-259
Male Thread		
ACS202	G $\frac{1}{4}$	-2003G
ASC203	G $\frac{3}{8}$	-2003K
ACS201	G $\frac{1}{2}$	-2003F

Heavy Duty Schrader Adaptors

When connected to the coupling, the adaptor can swivel, thereby eliminating hose kinks.

Nominal Bore: 8.5mm.
Flow rate @ 6 bar - 500 l/min.
Maximum working pressure: 17 bar/250psi.
Coupling series: Heavy Duty.
Interchangeable: Cejn 499, Rectus 68.



Product Number	Thread Size	Order Code PCL-259
Male Thread		
ACAS204	R $\frac{1}{4}$	-1999X
ACAS205	R $\frac{3}{8}$	-1999Y
ACAS203	R $\frac{1}{2}$	-1999W
Female Thread		
ACAS206	G $\frac{1}{4}$	-1999Z
ACAS207	G $\frac{3}{8}$	-2000A
Hose Tailpiece		
ACAS201	10mm/ $\frac{3}{8}$	-1999R
ACAS202	12mm/ $\frac{1}{2}$	-1999T

PF Adaptors

Broomwade InstantAir was acquired by PCL in 2001 and still made in the UK. Bayonet style and are zinc plated steel.

Nominal Bore: 5mm.
Flow rate @ 6 bar - 2,200 l/min.
Maximum working pressure: 35 bar/508psi.
Couplings: PF Series.



Product Number	Thread Size	Order Code PCL-259
Male Thread		
AA7702	R $\frac{1}{4}$	-1702B
AA7703	R $\frac{3}{8}$	-1703C
Female Thread		
AA7706	Rp $\frac{1}{4}$	-1706F
AA7707	Rp $\frac{3}{8}$	-1707G
Hose Tailpiece		
AA7710	6mm	-1710K
AA7711	8mm	-1711L
AA7712	10mm	-1712M

Euro Couplings

Suitable for most general compressed air applications where this adaptor profile is required.

Nominal Bore: 5.5mm.
Flow rate @ 6 bar - 650 l/min
Maximum working pressure: 14 bar/200psi.
Adaptor series: Euro.
Interchangeable:
 Aro 210, Cejn 300,
 JWL 522/532,
 Schrader Euro,
 Rectus 14/22.



Product Number	Thread Size	Order Code PCL-259
Male Thread		
AC61CM	R $\frac{1}{4}$	-1980A
AC61EM	R $\frac{3}{8}$	-1980B
AC61JM	R $\frac{1}{2}$	-1980C
Female Thread		
AC61CF	Rp $\frac{1}{4}$	-1981D
AC61EF	Rp $\frac{3}{8}$	-1981E
AC61JF	Rp $\frac{1}{2}$	-1981F
Hose Tailpiece		
AC61R	7mm	-1979D
AC61S	8mm	-1979E
AC61T	10mm	-1979F

Euro Adaptors

Steel construction with corrosive resistant finish.

Nominal Bore: 5.5mm.
Flow rate @ 6 bar - 650 l/min
Maximum working pressure: 14 bar/200psi.
Coupling Series: Euro.
Interchangeable:
 Aro 210, Cejn 300,
 JWL 522/532,
 Schrader Euro,
 Rectus 14/22.




Product Number	Thread Size	Order Code PCL-259
Male Thread		
ACA6912	6.35mm/ $\frac{1}{4}$	-1989P
Female Thread		
ACA6924	R $\frac{1}{2}$	-1989Q
Hose Tailpiece		
ACA6912	6.35mm/ $\frac{1}{4}$	-1989M
ACA6922	7.9mm/ $\frac{9}{16}$	-1989N
ACA6930	9.5mm/ $\frac{3}{8}$	-1989R

KENNEDY Ball Valves

Available in Male to Female and Female to Female fitting.

Pressure range: 0 to +10bar.

Temperature range: -25 to +90°C.



Product Number	Size (mm)	Order Code
Male to Female		
VAB1FM	G $\frac{1}{8}$ - G $\frac{1}{8}$	-7200K
VAB2FM	G $\frac{1}{4}$ - G $\frac{1}{4}$	-7210K
VAB3FM	G $\frac{3}{8}$ - G $\frac{3}{8}$	-7220K
VAB4FM	G $\frac{1}{2}$ - G $\frac{1}{2}$	-7230K
Female to Female		
VB2FF	G $\frac{1}{4}$ - G $\frac{1}{4}$	-7310K
VB3FF	G $\frac{3}{8}$ - G $\frac{3}{8}$	-7320K
VB6FF	G $\frac{3}{4}$ - G $\frac{3}{4}$	-7340K

 $\frac{1}{4}$ " NPT/BSP Convertors

Specially designed to allow British Standard airline couplings and adaptors to be fitted to $\frac{1}{4}$ " NPT threaded air tools. Also suitable for use in hydraulic lines and coolant flow systems. Passivated zinc finish for double protection against corrosion.

Type	BSP x NPT	Order Code
Swivel		
Fixed	$\frac{1}{4}$ x $\frac{1}{4}$	-4900K
Swivel	$\frac{1}{4}$ x $\frac{1}{4}$	-4950K

PCL Instant Air Couplings

Bayonet type range, positive seal, quick release couplings designed for maximum efficiency and to prevent accidental uncoupling.

Nominal Bore: 5.6mm.

Flow rate @ 6 bar - 54cfm @ 100psi.

Maximum working pressure: 17 bar/250psi.

Adaptor series: InstantAir.

Product Number	Thread Size	Order Code
Female Thread		
AC51CF	Rp $\frac{1}{4}$	-1980Z

Instant Air Adaptors

Broomwade InstantAir was acquired by PCL in 2001 and still made in the UK. Bayonet style and are zinc plated steel.

Nominal Bore: 5.6mm.

Flow rate @ 6 bar - 54 cfm @ 100psi.

Maximum working pressure: 17 bar/250psi.

Coupling series:

InstantAir.

Product Number	Thread Size	Order Code
Male Thread		
AA5102	G $\frac{1}{4}$	-1002H
AA5103	G $\frac{3}{8}$	-1003J
Female Thread		
AA5106	Rp $\frac{1}{4}$	-1006M
AA5107	Rp $\frac{3}{8}$	-1006N

PCL Tailpieces & Connectors

Case hardened with zinc finish.

Male Threaded Tailpieces

For connecting a hose to a female threaded fitting.

Product Number	Thread Size	Bore Size	Order Code
PCL-259			
HC5656	$\frac{1}{4}$ "	$\frac{1}{4}$ "	-3368N
HC1206	G $\frac{1}{4}$ "	$\frac{5}{16}$ "	-3355T
HC1217	$\frac{1}{2}$ "	$\frac{3}{8}$ "	-3360M
HC2479	$\frac{1}{2}$ "	$\frac{1}{2}$ "	-3362A
HC6904	G $\frac{3}{8}$ "	$\frac{1}{4}$ "	-3371T
HC2951	G $\frac{3}{8}$ "	$\frac{3}{8}$ "	-3365D
HC2808	G $\frac{1}{2}$ "	$\frac{1}{2}$ "	-3364C
HC2954	G $\frac{1}{2}$ "	$\frac{1}{2}$ "	-3365H

Hose Connector

For joining two lengths of hose or repairing a hose.

Product Number	Bore Diameter	Order Code
PCL-259		
HC2983	$\frac{1}{4}$ x $\frac{1}{4}$	-3365P
HC2985	$\frac{3}{8}$ x $\frac{3}{8}$	-3365T
HC2986	$\frac{1}{2}$ x $\frac{1}{2}$	-3365W

Coned Tailpieces

For use in conjunction with union nuts to connect hose to male threaded fittings.

Product Number	Bore Diameter	Order Code
PCL-259		
HC5275	$\frac{1}{4}$	-3367W
HC1225	$\frac{3}{8}$	-3360W

Double Unions Nuts

For connecting female threaded fittings of the same size.

Product Number	Thread Size	Order Code
PCL-259		
HC6560	$\frac{1}{4}$ x $\frac{1}{4}$	-3368X
HC4281	$\frac{3}{8}$ x $\frac{3}{8}$	-3366R
HC6898	$\frac{1}{2}$ x $\frac{1}{2}$	-3370G

Reducing Unions

For connecting female threaded fittings of different sizes.

Product Number	Bore Diameter	Order Code
PCL-259		
HC6899	$\frac{3}{8}$ x $\frac{1}{4}$	-3370K
HC6900	$\frac{1}{2}$ x $\frac{1}{4}$	-3370M
HC6901	$\frac{1}{2}$ x $\frac{3}{8}$	-3370S

Reducing Bush - Male to Female

For connecting female threaded fittings to male threaded fittings of a smaller size.

Product Number	Thread Size	Order Code
PCL-259		
HC6895	R $\frac{3}{8}$ x R $\frac{1}{4}$	-3370A
HC6896	R $\frac{1}{2}$ x R $\frac{1}{4}$	-3370C
HC6897	R $\frac{1}{2}$ x R $\frac{3}{8}$	-3370E

Union Nuts

For use in conjunction with coned tailpieces to connect hose to male threaded fittings.

Product Number	Bore Diameter	Order Code
PCL-259		
HC5194	$\frac{1}{4}$	-3367H
HC1226	$\frac{3}{8}$	-3360Y

KOBE Male Threaded Tailpieces

Designed for use with KOBE airline couplings. 'Third Level' Zinc plated for protection against corrosion.

Thread Size	Bore Size	Order Code
KBE-259		
G $\frac{1}{4}$	$\frac{1}{4}$	-8368N
	$\frac{3}{8}$	-8360M
	$\frac{1}{2}$	-8362A
G $\frac{3}{8}$	$\frac{3}{8}$	-8365D

Coupling Adaptors

Designed for use with Kobe airline couplings. 'Third level' zinc plated for protection against corrosion.

Double-Ended Tailpiece
Designed for use with KOBE Airline Couplings. 'Third Level' Zinc Plated for protection against corrosion.

Bore Size	Order Code
KBE-259	
$\frac{3}{8}$ x $\frac{3}{8}$	-8365T

Male Threaded Union

For connecting female threaded fittings of the same size.

Bore Size (BSPT)	Order Code
KBE-259	
$\frac{1}{4}$ x $\frac{1}{4}$	-8368X

PCL Tailpieces & Connectors

Case hardened with zinc finish.

Parallel Socket

Female to Female.

Product Number	Thread Size	Order Code
PCL-259		
HC6889	Rp $\frac{1}{4}$	-3369R

Y-Piece Connector - Female

For providing two airlines from a single supply.

Product Number	Thread Size	Order Code
PCL-259		
SPR4279	$\frac{1}{4}$	-4420D

Flexible Elbow

Flexible elbow (female to male). A flexible connection used to eliminate hose kinks.

Product Number	Thread Size	Order Code
PCL-259		
FE101	$\frac{1}{4}$ " BSPT	-3131B

KENNEDY QUALITY INDUSTRIAL TOOLING

Air Filter Regulator Lubricator

Manual/semi-auto drain as standard. Rolling membrane regulator with secondary bleed and adjustable knob. 20µm element as standard. Constant oil flow. Fully assembled units comprise a combined filter - regulator - lubricator in modular configuration.

Body: technopolymer.
Bowl: polycarbonate with protector.
Filtration size: 20µm.



Pressure Gauge - supplied separately.
See page 199.

Port Size	Flow Rate	Order Code KEN-259
G ¹ / ₄	260ltr/min	-5830K
G ³ / ₈	1100ltr/min	-5840K
G ¹ / ₂	2500ltr/min	-5850K

Air Filter Regulator Combi

Manual/semi-auto drain as standard. Rolling membrane regulator with secondary bleed and adjustable knob. 20µm element as standard. Simply unscrew bowl for servicing. Use individually or as part of a combination unit.

Pressure range:
0 - 8bar.
Max inlet: 15bar.
Body: Technopolymer.
Bowl: Polycarbonate with protector.
Filtration size: 20µm.



Port Size	Flow Rate	Order Code KEN-259
G ¹ / ₄	800ltr/min	-5800K
G ³ / ₈	1650ltr/min	-5810K
G ¹ / ₂	3000ltr/min	-5820K

Air Lubricator Units

Adjustable, constant oil flow. Integral mounting provision. Use individually or as part of a combination unit.

Temperature range: -10°C to 60°C.
Max input pressure: 10bar.
Body: Technopolymer.
Bowl: Polycarbonate with protector.
Recommended oil: ISO VG32 (Servo System 32).
Filtration size: 20µm.



Port Size	Bowl Capacity	Order Code KEN-259
G ¹ / ₄	28.0cc	-5900K
G ³ / ₈	46.0cc	-5910K
G ¹ / ₂	89.0cc	-5920K

Air Regulator Units

Rolling membrane regulator with secondary bleed and adjustable knob. Press to lock.

Pressure range: 0 - 8bar standard, 2bar, 4bar and 12bar options.
Temperature range: -10°C to 60°C.
Gauge ports: G¹/₈ (two).
Body: technopolymer.



Port Size	Flow Rate	Order Code KEN-259
G ¹ / ₄	600ltr/min	-6100K
G ³ / ₈	2050ltr/min	-6110K
G ¹ / ₂	3200ltr/min	-6120K

Portable Air Preparation Cradle

Housed in a rugged stove enamelled steel cage. Manual filter drain. Push to lock non-rising regulator control knob. Constant lubricator oil flow and very low pick-up pressure. Rugged metal bowl guards. Filters out condensate build-up from compressor through mains close to point of use. High flow rate allows multiple air tool use. Adjustable pressure range 0.5 to 10bar. For use in garages (very high automotive use), machine shops, joinery industry, sheet metal industry and any industry where air tools or spray guns are used.



Port Size	Delivery (@7bar)	Order Code KEN-294
1/2"	3000l/min(106cfm)	-3001B

Air Filter Units

Manual/Semi-Auto drain as standard, 20µm element, simply unscrew bowl for servicing. Integral mounting provision. Use individually or as part of a combination unit.

Pressure range: 0 - 8bar max Inlet: 15bar.
Temperature range: -10°C to 60°C.
Filtration standard: 25mu.
Body: Technopolymer
Bowl: Polycarbonate with protector.
Filtration size: 20µm.



Port Size	Flow Rate	Order Code KEN-259
G ¹ / ₄	800ltr/min	-5500K
G ³ / ₈	1900ltr/min	-5510K
G ¹ / ₂	3750ltr/min	-5520K

KOBE Mini Oiler

Feeds oil directly into the airline ensuring your air tool is well lubricated at all times preventing corrosion. The clear body reservoir allows immediate inspection of the oil level. All brass construction.



Thread (BSP)	Weight each (g)	Order Code
1/4	130	KBE-280-1400K

Water Separator

Continuously removes moisture from the air supply helping to prevent corrosion to the internal components of the air tool. The spring valve allows immediate draining of reservoir without any down time.



Thread (BSP)	Weight each	Order Code
1/4	110g	KBE-280-1900K

AVON Anti-Corrosion Tape

Grease impregnated petrolatum tape. Self-adhesive and waterproof. Flexible. Protects against corrosion. Effective for long term sealing & protection. Works above and below ground and under water. Conforms to British Gas Standard BG/PS/CW2.



Width x Length	Order Code
50mm x 10m	AVN-981-7100K
75mm x 10m	AVN-981-7110K
100mm x 10m	AVN-981-7120K
150mm x 10m	AVN-981-7130K

Air Preparation

KENNEDY Pressure Gauges

Fitted with a G $\frac{1}{8}$ brass thread, can be used to measure psi and bar readings and can be fitted directly onto any filter regulator - lubricators. Available in two face sizes (40mm and 50mm), made from tough ABS plastic. Back entry fittings.



Face Dia. (mm)	Pressure Bar	Weight each (g)	Order Code
40	0 - 12	55	KEN-259-8240K
	0 - 4	50	KEN-259-8280K
50	0 - 12	70	KEN-259-8320K
	0 - 4	70	KEN-259-8360K

S.O.S. Repair Tape

Self fusing tape creates an air and water tight seal. Resists fuels, oils, acids, solvents, salt water, road salt and UV rays. Seals leaky hoses, pipes, and fittings.



Colour	Width x Length	Order Code
Black	25mm x 3m	AVN-981-4010K
Clear		AVN-981-4020K
White		AVN-981-4030K

KENNEDY
QUALITY INDUSTRIAL TOOLING

Heavy Duty Tyre Inflator with Gauge


This heavy duty push-on inflator is of rugged construction and has a clear-view integral pressure gauge reading from 10 - 120psi. Heavy duty corrosion resistant body with brass fittings. 300psi rated fibre reinforced rubber hose.

Conforms to EC Directive 86/217/EEC.

Accuracy:

Reading scale: 2psi/50kPa (0.5bar).

Inflation range: 120psi/800kPa (8bar).



Product Number	Weight each	Order Code
ALG120	635g	KEN-503 -8520K

Heavy Duty Dial Type Tyre Inflator

This push-on type tyre inflator is robust and has a dial type pressure gauge reading up to a maximum of 170psi. The pressure gauge is protected from accidental damage by a rubber shock guard. Heavy duty corrosion-resistant body with steel operating lever, brass fittings and anti-shock rubber guard. 300psi rated fibre reinforced rubber hose.

Conforms to EC Directive 86/217/EEC.

Accuracy:

Reading scale: 2psi/10kPa (0.1bar).

Inflation range: 170psi/1200kPa (12bar).



Product Number	Weight each	Order Code
TPG170	720g	KEN-503 -8480K

PCL

Tyre Inflation Equipment


Airforce Tyre Inflator

Clear dial display, modern, lightweight and shock resistant construction. Direct valve design increasing inflation and deflation rates. Built-in swivel and hanging device.

Conforms to BSEN 12645:1999.

Calibration type: 0 - 170lbf/in² and 0 - 12bar.

Air inlet: 1/4" BSP.



Product Number	Connector Type	Hose Length	Order Code
AFG1HO3	Twin Hold-on	21"	PCL-259 -2004A
AFG1HO6	Twin Clip-on	9'	-2004K
AFG1HO8	Euro Connect on	6'	-2004T

Accura 1 Tyre Inflator

Direct valve design increasing inflation and deflation rates with an over-pressure warning if pressure exceeds 12bar/174lbf/in²/1200kPa. Individually tested and certified, **Exceeds EC Directive 86/217/EEC.**

Reading accuracy:

0.01bar/0.2lbf/in²/1kPa.

Maximum inflation pressure:

15bar/218lbf/in²/1,500kPa.

Inflation range: 12bar/174lbf/in²/1,200kPa.

Operating temperature:

-20°C to 60°C.



Product Number	Connector Type	Hose Length	Order Code
DAC1AO3	Twin Hold-on	21"	PCL-259 -3023A
DAC1AO6	Twin Clip-on	9"	-3026D

Tyre Valve Inflator Connector

Twin hold on connector for standard bore tyre valves. Access both inner and outer valves of twin wheel assemblies on commercial vehicles. Open connection for use with tyre inflation gauges. Black rubber handle. 1/4" female air inlet thread.

Overall length: 250mm.




Product Number	Connector Type	Weight each	Order Code
C01A03	Hold-on	100g	PCL-259 -3001A

KOBE Retracting Airline Hoses

With brass 360° swivel couplings, ideal for use in awkward access areas. Recoils to a fraction of its working length leaving the work place clear of entanglement hazards.

Extended length: 7.5m.

Pressure rating: 6.0mm diameter - 250psi
9.5mm diameter - 150psi.



Thread (BSPT)	Bore Dia.	Weight each	Order Code KBE-280
Hi-flex Polyurethane			
1/4"	6.0mm	850g	-1160K NA
Heavy Duty Nylon Air Hose			
1/4"	6.0mm	850g	-1140K
3/8"	9.5mm	850g	-1300K

Retractable Air Hose Balancer

With adjustable tension return, it retracts when the air tool is released, leaving the work place clear of unwanted lengths of air hose. Ideally suited for in-line production. With spring loaded safety clip for overhead fixing.

Hose length: 1.5m.
Hose I.D.: 5mm.
Hose O.D.: 8mm.
Maximum pressure: 200psi.
Hoist range: 0 - 1.5kg.



Weight each	Order Code KBE-280
850g	-1000K

Whip Hose Adaptor

Supplies air between supply point and air tool. Prevents vibration damage to couplings and the tool user. Quick release coupling.

Overall length: 650mm.



Thread (BSPT)	Bore Dia.	Weight each	Order Code KBE-280
1/4"	6.0mm	145g	-1360K

PU Air & Water Hose Reels

Auto layering mechanism to prevent jamming. Working pressure 8 bar (120 PSI). Suitable for water up to 45°C. 180° pivoting wall bracket included - can be fixed to walls or ceilings. 1/4 BSPT. Conforms to **BS EN ISO 12100: 2010**.



Hose Size Bore x Length	Order Code KBE-258
6mm x 12m	-1050K
8mm x 12m	-1060K
10mm x 10m	-1070K

Rubber Air & Water Hose Reels

Designed for professional garages/workshops. Controlled slow rewind with auto layering mechanism to prevent jamming. Suitable for water up to 45°C. Working pressure 18 bar (260 PSI). 180° pivoting wall bracket included - can be fixed to walls or ceilings. 1/4 BSPT Conforms to **BS EN ISO 12100: 2010**.



Hose Size Bore x Length	Order Code KBE-258
10mm x 15m	-1110K
10mm x 20m	-1120K
10mm x 30m	-1130K

KENNEDY QUALITY INDUSTRIAL TOOLING**Through Flow Air Hose**

Easy wind reel mechanism. With high impact resistant drum and guide walls. 1/2" air hose fitted with two ear hose clips and standard PCL couplings for 1/2" hose. 15bar working pressure. The axial supply allows the hose to be wound and unwound during operation. Supplied with 1.5m supply connection hose and wall mounting hooks.



Size	Weight each	Order Code KEN-258
20m	4.5kg	-5100K

Industrial PVC Airline Hose

Reinforced with a polyester fibre braid. Used in pneumatic airline systems, crop spraying, transportation of gases and liquids, decanting of acids, salts and many other chemicals. Fully approved for food contact applications. Operating temperature range of -20°C to +60°C.

Maximum pressure ratings:

6.35mm - 250psi,
9.50mm - 150psi,
12.7mm - 130psi,
19.0mm - 100psi.



Supplied in 30m (100ft) reels.

Bore Size (mm)	Weight each	Order Code KEN-258
6.35 (1/4")	3.6kg	-1010K
9.50 (3/8")	4.5kg	-1030K
12.70 (1/2")	5.9kg	-1050K
19.00 (3/4")	9.0kg	-1070K

YORK ABRASIVES Silicon Carbide Valve Grinding Compound

For cutting brass, hardened steel and cast iron. Ideally used within the automotive and engineering industry. For heavy and light stock removal applications, from the removal of pits in exhaust pipes to the finishing of inlet valves.

*Contains 1x fine 85g and 1x coarse 85g

Size	Type	Weight each	Order Code YRK-257
85g*	Fine/Coarse	290g	-2100K
200g	Fine	250g	-2010K
	Coarse	235g	-2050K
500g	Fine	560g	-2020K
	Coarse	560g	-2060K



BEST SELLER



KENNEDY
QUALITY INDUSTRIAL TOOLING**Mini Metal Blow Gun**

Manufactured from bright nickel chrome plated die cast alloy for a long trouble free life. Complete with safety nozzle as standard. 1/4" NPT air inlet.

Safe Working Pressure:
with safety nozzle: 90psi
without safety nozzle: 30psi



Overall Length	Weight each	Order Code
100mm	140g	KEN-259 -5050K

Flexible Extension

Can be bent into any position to allow you to direct the air flow to exactly the area you require it in. Suitable for use with metal and plastic blow guns.



Overall Length	Weight each	Order Code
250mm	10g	KEN-259 -5100K

PCL**Plastic Blow Gun**

Anti-slip body made from a special acetalic resin to resist damage, staining and contamination with a 100% brass inner valve. The blow gun adjusts the airflow gradually for delicate working. With 110mm long safety nozzle for access into awkward areas. Suitable for use with both air and water.

Safe Working Pressure: 2bar/30psi.




Nozzle Length	Weight each	Order Code
110mm	105g	PCL-259 -2404H

PCL**Mini Metal Blow Gun**

Made from die cast alloy for long trouble-free life. Inlet thread 1/4" BSPT. With a safety nozzle.

Safe Working Pressure: 28psi



Product Number	Weight each	Order Code
BG106	200g	PCL-259 -2106A

Rigid Extension Nozzle

For use with both metal or plastic guns.



Overall Length	Weight each	Order Code
230mm	30g	PCL-259 -2466K

Plastic Blow Gun

Special acetalic resin moulded body to resist damage, staining and contamination with a 100% brass inner valve. Adjusts the airflow gradually for delicate working. The 230mm extension nozzle version can be cut and bent to suit user applications. Suitable for use with air or water.

Safe Working Pressure: 2bar/30psi.



Product Number	Nozzle Length	Order Code
BG5002	110mm	PCL-259 -2402G
BG5007	230mm	-2407M

KOBE**Pistol Grip Blow Gun**

Ideal for general air dusting jobs. Supplied with safety nozzle and interchangeable coupling. Ergonomically designed and impact resistant body with integral air control valve and trigger style operation.

Minimum working pressure: 3bar/43psi.
Safe working pressure: 10bar/150psi.



Temperature Range	Order Code
-17 to 37°C	KBE-259 -2550K

Blow Gun

Ideal for awkward and general air dusting jobs with 110mm long angled nozzle allowing projection of airflow directly to required area. Supplied with interchangeable coupling. Trigger style operation.

Minimum working pressure: 3bar/43psi.
Safe working pressure: 10bar/150psi.



Temperature Range	Order Code
-10 to 50°C	KBE-259 -2500K

KOBE Air Spray Guns

For Industrial and automotive use. Large responsive trigger, adjustable width of spray and flow control adjustment. Quick release bayonet fitting canisters.

Max operating pressure:
Suction/gravity: 2 - 3.5bar.
Air consumption:
Suction/gravity feed:
180 - 280ltr/min.
Pot capacities:
680cc.

Gravity Feed
KGSG15



Suction Feed
KGSG20



Type	Nozzle (mm)	Order Code
Suction	2.0	-2150K
Gravity	1.5	-2055K

KOBE STAR Spare Pots

Only suitable with Kobe Star spray guns.



Feed Type	Weight each	Order Code
Gravity (600cc)	100g	-1500A
Suction (1000cc)	50g	-1510B
Set of No. 4 Baffles & No. 7 Cup Gaskets	10g	-2500A

KOBE STAR

Suction Feed Spray Guns


Standard/Professional
Well balanced with large, responsive triggers, and adjustable width of spray. For horizontal or vertical use with cellulose enamel or acrylic paints etc. Both with 1/4" NPT male fittings. 30 - 70psi, 7 - 12cfm. Standard model is suitable for applying base coats. Professional is suitable for applying finishing coats.

Weight: 1.3kg.



Nozzle (mm)	Max. Spray Pattern	Order Code
1.4	240mm	-1000A
1.8	280mm	-1010B
1.5	255mm	-1200D
2.0	265mm	-1210E

Spare Needles



Feed Type	Size (mm)	Weight each	Order Code
Gravity	1.4	10g	-2120M
Suction	1.4	15g	-2100K
Suction	1.8	16g	-2110L
Suction	1.5	15g	-2130N
Suction	2.0	15g	-2140P

Spare Air Caps



Feed Type	Size (mm)	Weight each	Order Code
Gravity	1.5	50g	-2020H
Suction	1.4 & 1.8	100g	-2000F
Suction	1.4	50g	-2010G
Suction	2.0	50g	-2030J

Gravity Feed Spray Gun

Professional

Well balanced with large, responsive trigger and adjustable width of spray. For horizontal or vertical use with cellulose enamel or acrylic paints etc. With 1/4" NPT male fittings. 40 - 60psi, 6 - 12cfm. Screw top.

Weight: 1.10kg.



Nozzle (mm)	Max. Spray Pattern	Order Code
1.4	195mm	-1100C
Spare Filter for STA259-1100C		-2060S

Spray Gun Accessories

Spare Nozzles



Feed Type	Size (mm)	Weight each	Order Code
Gravity	1.4	35g	-2220S
Suction	1.4	30g	-2200Q
Suction	1.8	30g	-2210R
Suction	1.5	25g	-2230N
Suction	2.0	25g	-2240P

Repair Kit

Includes replacement air valve, valve spring, needle spring and O-rings.



Feed Type	Size (mm)	Weight each	Order Code
Gravity	1.5	14g	-2310V
Suction	1.4 & 1.8	11g	-2300T
Suction	1.5 & 2.0	15g	-2320W

KOBE 10mm Straight Drill

DS4510L

10mm Jacobs chuck, stall-resistant, safety lever throttle, high performance, planetary gearing.

Air inlet thread: 1/4" NPT.**Min. air hose size (ID):** 3/8" (10mm).**Air consumption:** 4cfm* (144ltr/min).**Sound power level:** 95dBA.**Overall length:** 206mm.**Spindle thread:** 3/8" - 24.**Air pressure:** 90psi/6.3bar.**Sound pressure level:** 88dBA.**Vibration level:** 2.5m/s².

Free Speed (rpm)	Weight each	Order Code KBE-270
4,500	0.90kg	-1450N

*Based on a
15 second cycle per
minute average use.

10mm
CHUCK

10mm Reversible Angle Drill

DAR1510

10mm Jacobs chuck, fingertip control of reverse and reverse exhaust.

Air inlet thread: 1/4" NPT.**Minimum hose size:** 3/8" (10mm).**Air pressure:** 90psi/6.3bar.**Air consumption:** 4cfm***Spindle thread:** 3/8" - 24.**Heah Height:** 94mm.

Sound pressure level: 94dBA.
Sound power level: 106dBA.
Vibration level: 2.6m/s².
Overall length: 178mm.

Free Speed (rpm)	Weight each	Order Code KBE-270
1,500	1.80kg	-1425M


*Based on a
15 second cycle per
minute average use.

10mm
CHUCK

10mm Pistol Drill

DP2210

10mm Jacobs chuck, stall resistant, heavy duty bearings.

Air inlet thread: 1/4" NPT.**Minimum air hose size (ID):** 3/8" (10mm).**Spindle thread:** 3/8" - 24.**Air pressure:** 90psi/6.3bar.**Air consumption:** 4cfm* (144ltr/min).**Motor:** 1/2hp10mm
CHUCK

**Sound pressure
level:** 87dBA.

Sound power level: 103dBA.**Vibration level:** 1.5m/s².**Overall length:** 165mm.


*Based on a 15 second
cycle per minute average use.

Free Speed (rpm)	Weight each	Order Code KBE-270
2,200	1.10kg	-1375C

10mm Heavy Duty Pistol Drill

DP2610

10mm Jacobs chuck, stall resistant, directional front exhaust, hammer finish casing, needle bearing gears.

Air inlet thread: 1/4" NPT.**Minimum air hose size (ID):** 3/8" (10mm).**Spindle thread:** 3/8" - 24.**Air pressure:** 90psi/6.3bar.10mm
CHUCKHEAVY
DUTY

Air consumption:
4cfm* (144ltr/min).

Sound pressure level: 87dBA.**Sound power level:** 103dBA.**Vibration level:** 2.5m/s².**Overall length:** 180mm.

*Based on a 15 second
cycle per minute average use.

Free Speed (rpm)	Weight each	Order Code KBE-270
2,600	0.90kg	-1390D

10mm Reversible Pistol Drill

DPR1810

10mm Jacobs chuck, stall resistant, heavy duty bearings, thumb switch for reverse, suitable for screwdriving.

Air inlet thread: 1/4" NPT.**Minimum air hose size (ID):** 3/8" (10mm).**Spindle:** 3/8" - 24.**Spindle thread:** 3/8" - 24.**Air pressure:** 90psi/6.3bar.10mm
CHUCK

Air consumption:
4cfm* (144ltr/min).

Sound pressure level: 85dBA.**Sound power level:** 101dBA.**Vibration level:** 5.4m/s².**Overall length:** 165mm.

*Based on a 15 second
cycle per minute average use.

Free Speed (rpm)	Weight each	Order Code KBE-270
1,800	1.40kg	-1400L


BEST
SELLER**KOBE** 10mm Reversible Pistol Drill

FPD375

Suitable for drilling and screwdriving. Rubber handle provides grip and operator comfort. 3/8" keyless chuck. Stall resistant. Short gear case design. Heavy duty gearing system with oil-less bushing. Spring loaded rotor vanes. Rear exhaust. Ball bearing construction for a long tool life.

10mm
CHUCKHEAVY
DUTY**Spindle thread:** 3/8" - 24.**Air inlet thread:** 1/4" NPT.**Minimum air hose****size (ID):** 3/8" (10mm).**Air pressure:** 90psi/6.2bar.**Air consumption:** 3.35cfm*.**Sound pressure level:** 95dBA.**Sound power level:** 100dBA.**Vibration level:** 0.7m/s².**Overall length:** 188mm.

*Based on a 15 second
cycle per minute average use.



Free Speed (rpm)	Weight each	Order Code KBE-270
1,800	1.4kg	-2152K

KOBE 10mm Reversible Pistol Grip Drill

B2834

Use for drilling and screwdriving.

Two speed trigger (slow speed when pushed halfway). Directional lever accessible from both sides for left/right handed use. 10mm (3/8") chuck included. Planetary gears for longer life and smoother running. Ergonomic comfortable grip.

10mm
CHUCK

**Recommended air
pressure:** 6.2bar (90psi).
Air consumption: 4cfm* (113ltr/min).
Air inlet thread: 1/4" NPT.
Spindle thread: 3/8" - 24.
Minimum air hose size (ID): 3/8" (10mm).
Noise level: 85dBA.
Sound power level: 96dBA.
Vibration level #: 0.4m/s².
Overall length: 185mm.
***Per EN ISO 15744:2002.**
#Per EN 28927-5.



Free Speed (rpm)	Weight each	Order Code KBE-270
1,800	1.10kg	-4310K

*Based on a
15 second cycle per
minute average use.

KOBE 13mm Reversible Pistol Drill**FPD500**

Suitable for high torque drilling applications as well as screwdriving, hole sawing and cylinder honing. Rubber handle provides grip and operator comfort. 1/2" chuck. Adjustable side handle. Short gear case design. Heavy duty gearing system with oil-less bushing. Spring loaded rotor vanes. Rear exhaust. Ball bearing construction for a long tool life.



Spindle thread: 3/8" - 24.
Air inlet thread: 1/4" NPT.
Minimum air hose size (ID): 3/8" (10mm).
Air pressure: 90psi/6.2bar.
Air consumption: 3.65cfm*.
Sound pressure level: 95dBA.
Sound power level: 100dBA.
Vibration level: 0.4m/s².
Overall length: 240mm.



*Based on a 15 second cycle per minute average use.

Free Speed (rpm)	Order Code
500	-2142K

KOBE 10mm Straight Air Drill**BCSD10**

Exhaust outlet adjusts 360° to direct air flow away from the operator. Keyless chuck and safety lever throttle. Ergonomic and comfortable hand grip.

Motor power: 0.45hp.
Air inlet thread: 1/4" BSP.
Operating pressure: 90psi/6.2bar.
Minimum air hose size (ID): 3/8" (10mm).
Sound pressure level: 92dBA.
Sound power level: 110dBA.
Vibration level: 0.49m/s².
Overall length: 215mm.



*Based on a 15 second cycle per minute average use.

Free Speed (rpm)	Weight each	Order Code
2,500	1.80kg	-6050K


**KOBE 13mm Heavy Duty Pistol Drill****DP513**

13mm Jacobs chuck, high reduction gearbox, high torque, with side handle, 1/2hp motor.

Air inlet thread: 1/4" NPT.
Minimum hose: 3/8" (10mm)
Spindle thread: 3/8" - 24.

Air pressure: 90psi/6.3bar.
Air consumption: 4cfm*.
Sound pressure level: 85dBA.
Sound power level: 101dBA.
Vibration level: 5.4m/s².
Overall length: 180mm.

*Based on a 15 second cycle per minute average use.



Free Speed (rpm)	Weight each	Order Code
500	1.80kg	-1500E

13mm Reversible Heavy Duty Pistol Drill**DPR813**

Jacobs chuck, thumb switch for reverse, auxiliary handle, suitable for screwdriving, heavy duty planetary gearing.

Air inlet thread: 1/4" NPT.
Minimum hose: 3/8" (10mm).
Spindle thread: 3/8" - 24.
Air pressure: 90psi/6.3bar.

Air consumption: 4cfm*.
Sound pressure level: 89dBA.
Sound power level: 101dBA.
Vibration level: 2.5m/s².
Overall length: 178mm.

*Based on a 15 second cycle per minute average use.



Free Speed (rpm)	Weight each	Order Code
800	1.80kg	-1525F

13mm Reversible Pistol Grip Drill**B2842**

Use for drilling and screwdriving. Two speed trigger (slow speed when pushed halfway). Directional lever accessible from both sides for left/right handed use. 13mm (1/2") chuck and detachable side handle included. Planetary gears for longer life and smoother running. Ergonomic comfortable grip.

Recommended air pressure: 6.2bar (90psi).
Air inlet thread: 1/4" NPT.
Minimum air hose size (ID): 3/8" (10mm).
Vibration level #: 0.4m/s².
Air consumption: 4cfm* (113ltr/min).
Spindle thread: 3/8" - 24.
Noise level†: 86dBA. **Sound power level†:** 93dBA.
Overall length: 218mm.

†Per EN ISO 15744:2002.
#Per EN 28927-5.



Ergonomic comfortable grip.



Two speed trigger for slow or fast action.



Forward/Reverse lever action.



Complete with industrial chuck.

*Based on a 15 second cycle per minute average use.



Free Speed (rpm)	Weight each	Order Code
800	1.30kg	-4330K

KOBE 100mm Angle Grinder

GA1011L

Adjustable safety guard, safety lever throttle. Supplied with auxiliary side handle, flanges and spanners, lightweight and compact. 100 x 3 x 16mm cut-off disc.

Air inlet thread: 1/4" NPT. **Spindle thread:** 3/8" - 24.

Minimum air hose size: 10mm (3/8").

Air pressure: 6.3bar (90psi).

Air consumption: 6cfm* (216ltr/min).

Motor power: 0.7hp.

Sound pressure level: 89dBA.

Sound power level: 96dBA.

Vibration level: 4.0m/s².

Overall length: 230mm.



Free Speed (rpm)	Weight each	Order Code
11,000	1.80kg	-2050P

*Based on a 15 second cycle per minute average use.

115mm Angle Grinder

GA1211L

Suitable for grinding, cutting-off and sanding. Safety lever throttle. Supplied with auxiliary side handle, flanges and spanners. 115 x 3 x 22mm cut off disc.

Air inlet thread: 1/4" NPT. **Spindle thread:** M10 x 1.5mm.

Minimum air hose size: 10mm (3/8").

Air pressure: 6.3bar (90psi).

Air consumption: 6cfm* (216ltr/min).

Motor power: 0.7hp.

Sound pressure level: 89dBA.



Sound power level: 96dBA.
Vibration level: 4.0m/s².
Overall length: 240mm.

Free Speed (rpm)	Weight each	Order Code
11,000	1.80kg	-2060Q

*Based on a 15 second cycle per minute average use.

180mm Heavy Duty Angle Grinder

GA1807L

Supplied with front exhaust, safety lever throttle, auxiliary side handle and adjustable safety guard. For grinding only.

Air inlet thread: 1/4" NPT. **Spindle thread:** 5/8" UNC.

Minimum air hose size (ID): 10mm. **Air pressure:** 90psi.

Air consumption: 6 1/2cfm*. **Sound pressure level:** 103dBA.

Sound power level: 109dBA.

Vibration level: 2.6m/s².

Overall length: 340mm.



Free Speed (rpm)	Weight each	Order Code
7,000	3.50kg	-2070R

*Based on a 15 second cycle per minute average use.

KOBE 50mm Mini Angle Grinder

FAG050m

For metal dressing, rust removal, weld preparation and automotive bodywork fabrication in hard to reach areas. Speed regulator. Safety release throttle. Heavy duty disc guard. Side exhaust. Ball bearing construction. Supplied with: 2x A60 (KEN230-0040K), 1x A80 (KEN230-0050K) and 1x A120 (KEN230-0060K) 50mm grinding discs.

Disc size: 50 x 4 x 9.6mm (2" x 5/32" x 3/8").

Air inlet thread: 1/4" NPT.

Minimum air hose size (ID): 3/8" (10mm).

Air pressure: 90psi/6.3bar.

Air consumption: 4cfm*.

Sound pressure level: 83dBA.

Sound power level: 92dBA.

Vibration level: 1.7m/s².

Overall length: 140mm.



Free Speed (rpm)	Weight each	Order Code
20,000	530g	-2090K

*Based on a 15 second cycle per minute average use.

76mm Reversible Cut-off Tool

FCT076

For cutting auto panels, light sheet metal, fibreglass, nuts and bolts. Powerful 0.5HP motor. Speed regulator. Safety release throttle. Rear exhaust. Rotating air inlet. Reverse feature. Ball bearing construction. Supplied with one 76mm cutting disc (KEN230-0020K).

Disc size: 76 x 1.8 x 9.6mm (3" x 1/16" x 3/8").

Minimum air hose size (ID): 3/8" (10mm).

Air inlet thread: 1/4" NPT.

Air pressure: 90psi/6.2bar.

Air consumption: 4cfm*. **Sound pressure level:** 98dBA.

Sound power level: 103dBA. **Vibration level:** 0.5m/s².

Overall length: 185mm.



Free Speed (rpm)	Weight each	Order Code
18,000	950g	-1200K

*Based on a 15 second cycle per minute average use.

115 & 125mm Angle Grinder

Suitable for metal dressing, rust removal, weld preparation and automotive bodywork fabrication. Rubber-cushioned side handle provides grip and operator comfort.

Air inlet thread: 1/4" NPT. **Spindle thread:** M14 x 2.0mm.

Minimum air hose size: 10mm (3/8"). **Air pressure:** 6.2bar (90psi).

Air consumption: 4cfm* (113ltr/min).

Motor power: 0.7hp.

Sound pressure: 89dBA.

Sound power level: 92dBA.

Vibration level: 1.2m/s².

Overall length: 240mm.



Model Number	Disc Size	Free Speed (rpm)	Weight each	Order Code
FGA120g	115mm (4 1/2")	10,000	1.95kg	-1960K
FGA130g	125mm (5")	10,000	1.96kg	-1980K

*Based on a 15 second cycle per minute average use.

KOBE High Speed Mini Die Grinder

GD2806L

For precision engineers' mould making etc. Safety lever throttle, front exhaust, ultra compact and lightweight.

Collet size: 6mm. **Air inlet thread:** 1/4" NPT.
Minimum air hose size (ID): 10mm (3/8"). **Air pressure:** 90psi.
Air consumption: 4cfm*. **Sound pressure level:** 94dBA.
Sound power level: 103dBA. **Vibration level:** 5.0m/s².
Overall length: 120mm.



Uses Long Collet Nut

Free Speed (rpm)	Weight each	Order Code
25,000	450g	-2035M


*Based on a 15 second cycle per minute average use.

Extended Spindle Die Grinder

GES2506L

For extra reach in 'hard to get at' areas, extended spindle housing allowing two-handed operation, rear exhaust, safety lever throttle.

Collet size: 6mm. **Air inlet thread:** 1/4" NPT.
Minimum air hose size (ID): 10mm (3/8"). **Air pressure:** 90psi.



Uses Long Collet Nut

Additional Collets to suit Kobe and similar grinders

Collet Size	Order Code
3mm	-0073A
1/8" (3.175mm)	-0079A
6mm	-0070A
1/4" (6.35mm)	-0076A
Collet Nut (Short)	-0064A
Collet Nut (Long)	-0067A

Air consumption: 4cfm*.
Sound pressure level: 93dBA.
Sound power level: 103dBA.
Vibration level: 5.4m/s².
Overall length: 248mm.

Free Speed (rpm)	Weight each	Order Code
25,000	850g	-2040N

*Based on a 15 second cycle per minute average use.

Surface Conditioning & Finishing Kit

SCF2206K

Multi-purpose kit containing: one of each of the following surface preparation discs - fine, medium and coarse.
 2x abrasive disc grades - P36, P60, P80 and P120.

1x 6mm diameter shank to fit the backing pad.
 Includes: GDA2206L, Angle Die Grinder as shown right. Supplied in a sturdy plastic carry case.



Uses Long Collet Nut

Free Speed (rpm)	Weight each	Order Code
22,000	1.25kg	-7000K

*Based on a 15 second cycle per minute average use.

Air Tools - Grinders

Straight Die Grinder

GD2206L

Suitable for polishing, buffing and grinding. The robust and durable single piece aluminium body houses the 1/2hp motor and precision balanced bearings provide reliability in the most demanding of industrial/ automotive applications. The trigger has a safety catch to prevent accidental starts.

Collet size: 6mm. **Air inlet thread:** 1/4" NPT.
Minimum air hose size (ID): 10mm (3/8"). **Air pressure:** 90psi.
Air consumption: 4cfm*. **Sound pressure level:** 93dBA.
Sound power level: 103dBA. **Vibration level:** 5.4m/s².
Overall length: 170mm. **Motor:** 1/2hp.



Uses Short Collet Nut

Free Speed (rpm)	Weight each	Order Code
22,000	500g	-2024K

*Based on a 15 second cycle per minute average use.

Die Grinder Kit

GD22LK

Includes: GD2206L, as shown above. With 3 and 6mm collets, 10 assorted mounted points and robust blow moulded case.



Uses Short Collet Nut

Free Speed (rpm)	Weight each	Order Code
22,000	600g	-2030L

*Based on a 15 second cycle per minute average use.

90° Angle Die Grinder

GDA2206L

Safety lever throttle, reverse exhaust, Ideal for polishing, grinding and buffing, suitable for use in confined areas.

Collet size: 6mm. **Air inlet thread:** 1/4" NPT.
Minimum air hose size: 10mm (3/8").
Air pressure: 90psi/6.2bar. **Air consumption:** 4cfm*.
Sound pressure level: 85dBA. **Sound power level:** 99dBA.
Vibration level: 7.0m/s². **Overall length:** 160mm.



Uses Long Collet Nut

Free Speed (rpm)	Weight each	Order Code
22,000	500g	-2020H

*Based on a 15 second cycle per minute average use.

KOBE Straight Die Grinder**FDG180m**

For polishing, buffing, deburring and grinding. Rubber handle provides grip and operator comfort. Speed regulator, safety release throttle, rear exhaust, ball bearing construction for long tool life.

Contents: mini die grinder, two collet spanners and instructions.

Collet size: 1/4" (6mm).

Air inlet thread: 1/4" NPT.

Minimum air hose size (ID): 3/8" (10mm).

Air pressure: 90psi/6.3bar.

Air consumption: 4cfm* (144ltr/min).

Sound pressure level: 91dBA.

Sound power level: 98dBA.

Vibration level: 4.53m/s².

Overall length: 158mm.

Speed regulator

Safety release throttle

Uses Long Collet Nut



Free Speed (rpm)	Weight each	Order Code
25,000	600g	KBE-270 -2262K

*Based on a 15 second cycle per minute average use.



HEAVY DUTY

Extended Spindle Die Grinder**FDG180e**

For polishing, buffing, deburring and grinding. Rubber handle provides grip and comfort. Extended head for flexibility in tight areas. Speed regulator. Safety release throttle. Rear exhaust. Ball bearing construction for long tool life.

Collet size: 6mm. **Air inlet thread:** 1/4" NPT.

Minimum air hose size (ID): 3/8" (10mm).

Air pressure: 90psi/6.2bar. **Air consumption:** 4cfm*.

Sound pressure level: 91dBA. **Sound power level:** 98dBA.

Vibration level: 4.53m/s². **Overall length:** 235mm.

Uses Long Collet Nut

Free Speed (rpm)	Weight each	Order Code
25,000	657g	KBE-270 -2272K

*Based on a 15 second cycle per minute average use.

**90° Angle Die Grinder****FDG090**

For polishing, buffing, deburring and grinding. Rubber handle provides grip and operator comfort. Speed regulator. Safety release throttle. Rear exhaust. Ball bearing construction for long tool life.

Collet size: 6mm.

Air inlet thread: 1/4" NPT.

Minimum air hose size (ID): 3/8" (10mm).

Air pressure: 90psi/6.2bar. **Air consumption:** 4cfm*.

Sound pressure level: 90dBA. **Sound power level:** 97dBA.

Vibration level: 1.24m/s². **Overall length:** 160mm.

Uses Long Collet Nut

Free Speed (rpm)	Weight each	Order Code
22,000	500g	KBE-270 -2222K

*Based on a 15 second cycle per minute average use.

**115° Angle Die Grinder****FDG115**

For polishing, buffing, deburring and grinding. Rubber handle provides grip and operator comfort. 115° angle head for flexibility in tight areas. Speed regulator. Safety release throttle. Rear exhaust.

Ball bearing construction for long tool life.

Collet size: 6mm.

Air inlet thread: 1/4" NPT. **Minimum air hose size:** 3/8" (10mm).

Air pressure: 90psi/6.2bar. **Air consumption:** 4cfm*.

Sound pressure level: 90dBA. **Sound power level:** 97dBA.

Vibration level: 1.05m/s². **Overall length:** 195mm.

Uses Long Collet Nut

Free Speed (rpm)	Weight each	Order Code
22,000	524g	KBE-270 -2242K

*Based on a 15 second cycle per minute average use.



KOBE Extended Straight Die Grinder

HEAVY DUTY

Air & Power Tools

B3555

Use for grinding, polishing, buffing and deburring. The extra length allows you to reach more confined areas. Planetary gears for longer life and smoother running. Low profile teasing throttle for precise speed control. Rotating air inlet to prevent the air hose tangling.

Collet size: 1/4" (6mm), 1/8" (3mm). **Recommended air pressure:** 90psi/6.2bar. **Air consumption:** 4cfm* (113ltr/min). **Air inlet thread:** 1/4" NPT. **Minimum air hose size (ID):** 10mm (3/8"). **Sound pressure level:** 91dBA. **Sound power level:** 98dBA. **Vibration level:** 4.53m/s². **Overall length:** 260mm.



Uses Long Collet Nut



Free Speed (rpm)	Weight each	Order Code
25,000	0.68kg	KBE-270 -4140K

*Based on a 15 second cycle per minute average use.

90° Angle Die Grinder**B3144**

Short body length allowing access into hard to reach areas. Planetary gears for longer life and smoother running. Low profile teasing throttle for precise speed control. Rotating air inlet to prevent the air hose tangling.

Collet size: 1/4" (6mm), 1/8" (3mm).

Air pressure: 6.2bar (90psi). **Air consumption:** 4cfm* (113ltr/min). **Air inlet thread:** 1/4" NPT. **Minimum air hose size (ID):** 10mm (3/8"). **Sound pressure level:** 90dBA. **Sound power level:** 97dBA. **Vibration level:** 1.24m/s². **Overall length:** 165mm.



Free Speed (rpm)	Weight each	Order Code
20,000	0.50kg	KBE-270 -4080K

*Based on a 15 second cycle per minute average use.

115° Angle Die Grinder**B3244**

Short body length allowing access into hard to reach areas. Planetary gears for longer life and smoother running. Low profile teasing throttle for precise speed control. Rotating air inlet to prevent the air hose tangling.

Collet size: 1/4" (6mm), 1/8" (3mm).

Recommended air pressure: 6.2bar (90psi).

Air consumption: 4cfm* (113ltr/min).

Air inlet thread: 1/4" NPT.

Minimum air hose size (ID): 10mm (3/8").

Sound pressure level: 90dBA.

Sound power level: 97dBA. **Vibration level:** 1.24m/s².

Overall length: 200mm.



Uses Long Collet Nut



Free Speed (rpm)	Weight each	Order Code
20,000	0.55kg	KBE-270 -4110K

*Based on a 15 second cycle per minute average use.

Straight Continuous Use Die Grinder**B3456**

Short body length allowing access into hard to reach areas. Planetary gears for longer life and smoother running. Low profile teasing throttle for precise speed control. Rotating air inlet to prevent the air hose tangling.

Drive size: 1/4" (6mm), 1/8" (3mm).

Air pressure: 6.2bar (90psi). **Air consumption:** 4cfm* (113ltr/min).

Air inlet thread: 1/4" NPT. **Minimum air hose size (ID):** 10mm (3/8").

Sound pressure level: 91dBA. **Sound power level:** 98dBA.

Vibration level: 4.53m/s². **Overall length:** 160mm.



Uses Short Collet Nut

Free Speed (rpm)	Weight each	Order Code
25,000	0.60kg	KBE-270 -4090K

*Based on a 15 second cycle per minute average use.

KOBE Micro Die Grinder**GM5603**

For precision grinding etc. With hose and silencer.

Collet size: 3mm.

Sound pressure level: 76dBA.

Sound power level: N/A dBA.

Vibration level: 4.80m/s².

Overall length: 156mm.

Air inlet thread: 1/4" NPT.

Recommended air pressure: 6.2bar (90psi).

Air consumption: 7cfm*

*Based on a 15 second cycle per minute average use.

Collets for Kobe and similar micro grinders

Collet Size	Order Code
1/8"	KBE-280 -0088A
3mm	-0091A
3/32"	-0094A
Collet nut	-0097A

Free Speed (rpm)	Weight each	Order Code
56,000	210g	KBE-270 -2543K



KOBE Air Nibbler**NB160**

Produces burr free cuts without distortion. Ideal for body shop and sheet metal work, teasing throttle for precise control, 1/4" NPT air inlet thread for 10mm air hose, 90psi air pressure, 4cfm* air consumption and a cutting capacity of 1.6mm (steel) to 2.0mm (aluminium).

Sound pressure level: 91dBA.

Sound power level: 104dBA.



Vibration level: 5.9m/s².
Overall length: 180mm.


*Based on a 15 second cycle per minute average use.

Cutting Rate Per Min.	Weight each	Order Code KBE-270
2.6m	900g	-3400K

Punches & Dies for Nibblers

Produce burr free cuts without distortion. Ideal for body shop and sheet metal work. Suitable for use with Kobe NB160 high performance nibbler.

KBE-298 parts cut on upstroke.
KBE-280 parts cut on downstroke.



Upstroke			
Type	To Suit Model	Weight each	Order Code KBE-298
Punch	Newer NB160	5g	-5003C
Die		75g	-5004D
Downstroke			
Type	To Suit Model	Weight each	Order Code KBE-280
Punch	Older NB160	5g	-0025A
Die		75g	-0028A

Shear Head

Produces burr free cuts without distortion. Ideal for body shop and sheet metal work. Suitable for use with Kobe SH120 rapid cutting metal shear.

To Suit Model	Weight each	Order Code KBE-280
SH120	360g	-0022A

Rapid Cutting Metal Shear**SH120**

Produces burr-free cuts without distortion. Ideal for body shop and sheet metal work. Teasing throttle for precise control, 1/4" NPT air inlet thread for 10mm air hose, 90psi air pressure, 4cfm* air consumption, cutting capacity of 1.2mm steel to 1.6mm aluminium.



Sound pressure level: 82dBA.

Vibration level: 4.2m/s².

Overall length: 200mm.

*Based on a 15 second cycle per minute average use.

Strokes Per Min.	Weight each	Order Code KBE-270
2,200	2.30kg	-3900K

Multi-Purpose Body Saw**BS920L**

Produces burr free cuts without distortion. Ideal for body shop and sheet metal work. Teasing throttle for precise control, 1/4" NPT air inlet thread, 90psi air pressure, 4cfm* air consumption and a cutting capacity of 1.6mm (steel) to 2mm (aluminium).

Sound pressure level: 91dBA.

Sound power level: 102dBA. **Vibration level:** 5.1m/s².

Overall length: 235mm.



Free Speed (rpm)	Weight each	Order Code KBE-270
9,000	550g	-3500K

*Based on a 15 second cycle per minute average use.

Accepts most square-ended blades up to 1mm thick x 12mm wide

Shatter Resistant Body Saw Blades

HSS body saw blade with two tooth pitch variations. 24 tooth (medium) and 32 tooth (fine) to suit a wide range of applications. Sold in packs of two.

Type	Teeth Per Inch	Pack Quantity	Order Code KBE-280
All Hard -	24	2	-5670K
For Straight Cuts	32	2	-5672K
Bi-Metal -	24	2	-5674K
For Curved Cuts	32	2	-5676K


Hammer & Chisel Kit**HP2090K**

Supplied with flat chisel, spot weld breaker, taper punch, rivet cutter and sheet metal cutter. Hard hitting long stroke. Accepts all standard 0.401" shank tools. 1/4" NPT air inlet thread for 10mm air hose, 90psi air pressure, 4cfm* air consumption.

Stroke length: 90mm. **Sound pressure level:** 105dBA.

Sound power level: 118dBA. **Vibration level:** 11.5m/s².

Overall length: 230mm.



Free Speed (rpm)	Weight each	Order Code KBE-270
2,000	3.00kg	-3100K

*Based on a 15 second cycle per minute average use.

Heavy Duty Needle Scaler**NS4030**

10 needles for quick removal of rust, paint, scale, flux and corrosion. Slimline body. Lightweight. (For replacement scaling needles, please refer to parts drawing supplied with tool), 1/4" NPT air inlet thread for 10mm air hose, 90psi air pressure, 4cfm* air consumption.

Needle diameter: 3mm. **Sound pressure level:** 95dBA.

Sound power level: 109dBA. **Vibration level:** 12.8m/s².

Overall length: 250mm.



*Based on a 15 second cycle per minute average use.

Scaler Needles for use with Kobe Needle Scaler NS4030

Blows Per Minute	Weight each	Order Code KBE-270
5,000	1.25kg	-3300K

Number of Needles	Order Code KBE-280
Set 10	-0019A

KOBE Heavy Duty Pistol Grip Hammer**HP2190**

For a wide range of workshop and automotive uses. Supplied with retainer spring. Accepts all standard 0.401" shank tools, 1/4" NPT air inlet thread for 10mm air hose, 90psi air pressure, 4cfm* air consumption.

Stroke length: 90mm.

Sound pressure level: 109dBA.

Sound power level: 119dBA.

Vibration level: 11.2m/s².

Overall length: 225mm.



KOBE
COMPLETE
RANGE OF
SPARE
PARTS &
ACCESSORIES
ARE
AVAILABLE



Group
259

Blows Per Minute	Weight each	Order Code
2,100	2.00kg	-3050K

*Based on a 15 second cycle per minute average use.

Pistol Grip Hammer**HP4540**

Suitable for use with cutters, punches, spot weld breakers and flat chisels. Supplied with retainer spring. Accepts all standard 0.401" shank tools, 1/4" NPT air inlet thread for 10mm air hose, 90psi air pressure, 4cfm* air consumption.


Stroke length: 40mm.

Sound pressure level: 112dBA.

Sound power level: 121dBA.

Vibration level: 15.5m/s².

Overall length: 145mm.



Group
289

Blows Per Minute	Weight each	Order Code
4,500	1.40kg	-3000K

*Based on a 15 second cycle per minute average use.

Hammer & Chisel Kit**HP5040K**

Supplied with flat chisel, spot weld breaker, taper punch and rivet cutter. Variable power regulator. Accepts all standard 0.401" shank tools. 1/4" NPT air inlet thread for 10mm air hose, 90psi air pressure, 4cfm* air consumption.

Stroke length: 40mm.

Sound pressure level: 112dBA.

Sound power level: 119dBA.

Vibration level: 14.8m/s².

Overall length: 135mm.



Blows Per Minute	Weight each	Order Code
5,000	1.60kg	-3150K

*Based on a 15 second cycle per minute average use.

Retainers

Suitable for use with all Kobe air hammers.



Retainer Type	Weight each	Order Code
Quick Change	60g	-0001A
Beehive	80g	-0004A
Zip Change	70g	-0007A

Air Hammer Chucks

Suitable for use with all Kobe air hammers. Cannot accidentally be released.

Safety Chuck

Spring loaded retainer, that must be unscrewed to allow tool release.

**Quick Change Chuck**

Spring loaded front collar, that must be pulled forward to allow tool release.



Chuck Type	Weight each	Order Code
Safety	70g	-0010A
Quick Change	530g	-0013A

Needle Scaler Attachment

Converts a pneumatic hammer into a needle scaler.



To Suit	Weight each	Order Code
All Kobe Air Hammers	865g	-0116A

KOBE Mini Belt Sander Kit**MBS025-X**

Suitable for shaping, paint removal, weld sanding, smoothing and rust removal on flat or curved surfaces. Supplied with 9 flexible abrasive belts and 5 contact arms. Rated for continuous use. Uses 6, 10, 13 and 20mm wide by 457mm long abrasive belts. Adjustable multi-positional sanding arm angle with a speed regulator and rear handle exhaust with noise baffler.

Free speed: 18,000rpm.

Air inlet thread: 1/4" NPT.

Minimum air hose size (ID): 10mm (3/8").

Air consumption: 4cfm* (113ltr/min).

Air pressure: 90psi/6.3bar.

Motor power: 0.6hp.

Sound pressure level: 84dBA.


Sound power level: 92dBA.

Vibration level: 0.80m/s².

Overall length: 390mm.

File Belts

Grit	Weight per 10	Order Code	00
		YRK-204	
13mm Wide x 457mm Long			
P80	600g	-3342K	



Free Speed (rpm)	Weight each	Order Code
18,000	1.36kg	-2880K



Kit contents:
Contact arms:
 6, 10, 13, 20mm with flat roller.
 10mm with rounded roller.
Surface preparation file belts:
 20mm: P80 grit (coarse),
 13mm: P300 grit (fine)
Aluminium oxide file belts:
 20mm: P60, P80 grit,
 13mm: P80, P120 grit,
 10mm: P120, P150 grit,
 6mm: P150 grit.
 4mm hexagon key L-wrench.

*Based on a 15 second cycle per minute average use.

KOBE Mini Belt Sanders

Suitable for flat, concave and convex surfaces. Sanding arm can be rotated to any angle - improved access in confined spaces, saves space when storing the tool. Spare belt and hex wrench included. Ergonomic and comfortable rubber grip for reduced vibration. Low profile teasing throttle for precise speed control. Directional rear exhaust.

Air inlet thread: 1/4" NPT

Minimum air hose size (ID): 10mm (3/8").

Air consumption: 4cfm* (113ltr/min).

Air pressure: 90psi/6.2bar.

Overall length/folded length:

R5218: 305/207mm,

R5228: 470/310mm,

R5238: 420/255mm.



Product Number	Belt Size W x L (mm)	No Load Speed	Weight each	Order Code
R5218	6 x 330	18,000rpm	0.85kg	-4250K
R5228	13 x 610	18,000rpm	0.95kg	-4270K
R5238	20 x 520	16,000rpm	1.60kg	-4200K

KOBE Air Rivet Nut Tool**KHRN01**

Lightweight, high speed tool ideal for flow-line or batch assembly in a variety of applications. Features one-step rocker type trigger, quick and easy stroke adjustment, and left and right hand side air inlet for ease of operational control. Suitable for rivet nuts M4 - M12 and can be suspended or hand held. Supplied in storage case.

Comes with: oiler, 5mm hex wrench, 2mm hex wrench, 10 x 11 wrench, 27 x 30 wrench and rivet nut heads: M4, M5, M6, M7, M8, M9, M10, M11 and M12.

Air inlet thread: 1/4" NPT.

Minimum air hose size: 10mm (3/8").

Min./max. air pressure:

min: 90psi/6.2 bar, **max:** 110 psi/7.5 bar.

Sound power level: 92.8dBA.

Vibration level: 0.48m/s².

Dimensions (H x W x D): 277 x 118 x 105mm.

Product Number	Weight each	Order Code
KHRN01	2.2kg	-1150K



KOBE 75mm Air Random Orbital Sander**BROS3 - Heavy Duty**

High speed random orbital sander with an adjustable power regulator to match the speed to the job. Lightweight design makes it easy to use in confined areas. Ball bearing construction for long tool life.

Motor power: 0.40hp
Air inlet thread: 1/4" BSP.
Backing pad size: 75mm (3").
Sound power level: 91dBA.
Vibration level: 6.3m/s².

Backing pad: Hook-n-Loop.
Operating pressure: 90psi/6.2bar.
Minimum air hose size (ID): 3/8" (10mm).
Overall length: 125mm.



Free Speed (rpm)	Order Code	Spare Flexible Backing Pad Diameter (mm)	Order Code
15,000	-6010K	75	-0210A

KOBE Mini Polisher Kit**GMPK3 - 75mm (3") Mini Polisher Kit**

Compact and lightweight for ease of use in confined areas. Ergonomic and comfortable hand grip.

Kit contents: mini polisher, backing pad, spanner, 90mm (3 1/2") fine polishing sponge (white), 90mm (3 1/2") coarse polishing sponge (yellow) and 90mm (3 1/2") lambs wool polishing bonnet.

Motor power: 0.25hp. **Air inlet thread:** 1/4" BSP. **Backing pad:** Hook-n-Loop.
Backing pad size: 75mm (3"). **Operating pressure:** 90psi/6.2bar.
Sound power level: 94dBA. **Minimum air hose size (ID):** 3/8" (10mm).
Vibration level: 0.77m/s².
Overall length: 115mm.

6 PIECES



Free Speed (rpm)	Order Code	Spare 3 1/2" Polishing Sponges Colour/Grade	Order Code
3,200	-6740K	White/Fine	-0160A
		Yellow/Coarse	-0161A
		Lamb Wool	-0162A

**Mini Random Orbital Sander Kit****FO5003mk**

Uses 2" and 3" backing pads. Rubber handle provides grip and operator comfort. Two finger throttle for easier control and less fatigue. Adjustable power regulator to match the speed to the job. Ball bearing construction for a long tool life.

Accessories included: 2" and 3" backing pads. 10x 2" diameter sanding discs - 320, 400 and 600 grit. 10x 3" diameter sanding discs - 320, 400 and 600 grit. Spindle key and instructions. Supplied in a robust blow-moulded carry case.

Free speed: 15,000rpm. **Air inlet thread:** 1/4" NPT.
Minimum air hose size (ID): 3/8" (10mm). **Air consumption:** 4cfm*.
Vibration level: 0.9m/s².

Free Speed (rpm)	Weight each	Order Code	*Based on a 15 second cycle per minute average use.
15,000	611g	-2103K	

**KOBE Dust Free Orbital Palm Grip Sander****FPS874**

Complete with 1m dust removal hose, large capacity dust collection bag and foam backed hook-n-loop pad. Connects to dust extraction. Adjustable speed regulator.

Air inlet thread: 1/4" NPT.
Minimum air hose size (ID): 3/8" (10mm).
Air pressure: 6.3bar/90psi.
Air consumption: 4cfm* (144ltr/min).
Sheet size: 93 x 230mm.
Pad size: 74 x 150mm.
Overall length: 175mm.



*Based on a 15 second cycle per minute average use.

Free Speed (rpm)	Weight each	Order Code
8,000	1.80kg	-2650K

1/3 Sheet Heavy Duty Orbital Sander**FOS890**

For use on wood, metal, plastics, fibre glass, fillers etc. Connects to 10mm hose, dust extraction, adjustable speed regulator, low noise, vibration damped.

Pad size: 165 x 90mm. **Sheet size:** 93 x 230mm. **Air inlet thread:** 1/4" NPT.
Minimum air hose size (ID): 3/8" (10mm).
Air pressure: 6.3bar/90psi.
Air consumption: 4cfm* (144ltr/min).
Sound pressure level: 91dBA.
Sound power level: 105dBA.
Vibration level: 16.6m/s².
Overall length: 175mm.



*Based on a 15 second cycle per minute average use.

Free Speed (rpm)	Weight each	Order Code
8,000	1.80kg	-2900K

180mm Angle Polisher**PA1825**

For high performance buffing and polishing on bodywork and paintwork. Built-in regulator for consistent performance. Can be used with compounding heads and polishing sponges.

Spindle thread: 5/8" - 11 NPT. **Air inlet thread:** 1/4" NPT. **Minimum air hose size (ID):** 3/8" (10mm). **Air pressure:** 6.3bar/90psi.
Air consumption: 4cfm* (144ltr/min).
Pad size: 180mm. **Sound pressure level:** 96dBA. **Sound power level:** 103dBA.
Vibration level: 8.2m/s².
Length: 380mm.



*Based on a 15 second cycle per minute average use.

Free Speed (rpm)	Weight each	Order Code
2,500	2.30kg	-3600K

KOBE 150mm Random Orbital Palm Sander Self-Vacuum Type**R5666**

Suitable for shaping, blending and smoothing of body filler and rapid material removal. Random 5mm diameter orbit for a swirl-free finish - can be used for wet sanding. 150mm diameter Hook-n-Loop backing pad with a 600A hole pattern. 1.6m extraction hose. Can be connected to a portable dust collection system or supplied cotton bag to help reduce airborne dust and clean-up time. One handed operation with a rubber grip. Rotating air inlet to prevent the air hose tangling.

Spindle size: 5/16".**Recommended air pressure:** 6.2bar/90psi.**Air consumption:** 3cfm* (85ltr/min).**Air inlet thread:** 1/4" NPT.**Minimum air hose size (ID):** 10mm (3/8").**Motor power:** 0.25hp.**Sound pressure level:** 88dBA.**Sound power level:** 76dBA.**Vibration level:** 5.2m/s².**Overall length:** 210mm.

Free Speed (rpm)	Weight each	Order Code
11,000	1.47kg	KBE-270 -4170K

*Based on a 15 second cycle per minute average use.

KOBE 150mm Random Orbital Sander**FSO150**

Suitable for shaping, blending, smoothing body filler and rapid material removal. Rubber handle. Random orbit. Can be used for wet sanding. Rotating air inlet to prevent tangling. Speed control for easy adjustment. Ball bearing construction for a long tool life.

Backing pad size: 150mm (6"). **Backing pad type:** hook and loop. **Orbit diameter:** 5mm (3/16"). **Suction type:** self-generating vacuum.

Spindle size: 5/16" NPT.**Air inlet thread:** 1/4" NPT. **Minimum air hose size (ID):** 10mm (3/8").**Air pressure:** 6.2bar/90psi. **Motor power:** 0.2hp.**Air consumption:** 3cfm* (85ltr/min).**Sound pressure level:** 84dBA. **Sound power level:** 90dBA.**Vibration level:** 5.6m/s². **Overall length:** 280mm.

Free Speed (rpm)	Weight each	Order Code
10,000	1.04kg	KBE-270 -2720K

*Based on a 15 second cycle per minute average use.

150 mm

Pistol Screwdriver Kit**SP1825K**

1/4" NPT air inlet thread for 10mm air hose, 90psi air pressure, 4cfm* air consumption, 45 - 115lbs/inch. 1/4" hex drive capacity.

Sound pressure level: 86dBA. **Sound power level:** 102dBA.**Vibration level:** 4.6m/s². **Overall length:** 178mm.

Contents: SP1825 screwdriver, hexagon wrench and spanner, No.1, 2 and 3 x 50mm crosspoint bits, 4, 5 and 6mm x 50mm slotted bits, No.2 x 100mm crosspoint double-ended bit.



Free Speed (rpm)	Weight each	Order Code
1,800	900g	KBE-270 -3850K

*Based on a 15 second cycle per minute average use.

Straight Screwdriver Kit**SS1525K**

1/4" NPT air inlet thread for 10mm air hose, 90psi air pressure, 4cfm* air consumption, 10 - 30lbs/inch torque. 1/4" hex drive capacity.

Sound pressure level: 90dBA.**Sound power level:** 104dBA.**Vibration level:** 3.2m/s².**Overall length:** 210mm.**Contents:**

SS1525 screwdriver, two clutch springs: clutch spring No.06-703-13 dia. 2.3mm, 1Nm - 3Nm, clutch spring No.06-703-23 dia. 1.8mm, 0.3Nm - 0.7Nm, 2x spanners, clutch adjusting wrench, 1/4 NPT nipple, mini oil bottle, No.1 x 65mm crosspoint double ended bit, 5 x 50mm slotted bit.



Free Speed (rpm)	Weight each	Order Code
1,700	900g	KBE-270 -3800K

*Based on a 15 second cycle per minute average use.


KOBE Automatic Shut-off Screwdriver

CSP0055

Heavy duty reverse action pistol grip screwdriver suitable for production and assembly applications. Push to start type with auto shut-off clutch for precision applications. Three interchangeable torque springs allow for easy conversion for new applications. 1/4" hex drive. External torque adjustment does not require disassembly of the tool. Variable speed throttle. Ergonomically contoured grip for operator comfort. Handle exhaust directs air away from the workpiece and operator. Hanging ring included.

Chuck size: 1/4" (6mm) hex. **Air inlet thread:** 1/4" NPT.
Minimum air hose size (ID): 3/8" (10mm).
Green torque spring: 0.6 - 2.1Nm (5 - 19in/lbs).
Black torque spring: 1.1 - 4.3Nm (10 - 38in/lbs).
Yellow torque spring: 1.7 - 5.1Nm (15 - 45in/lbs).

Air pressure: 6.3bar/90psi.
Air consumption: 4cfm* (144ltr/min).
Sound pressure level: 84dBA.
Sound power level: 93dBA.
Vibration level: <0.5m/s².
Overall length: 210mm.



Weight each	Order Code
815g	KBE-270 -3760K

*Based on a 15 second cycle per minute average use.

KOBE Speed Ratchets

3/8 1/2

SR375 3/8" square drive, 10mm bolt capacity.
SR500 1/2" square drive, 13mm bolt capacity.
 Ball type retainer, disc type reversing action, compact, lightweight design, ideal for automotive work, front exhaust.

Free speed: 150rpm. **Air inlet thread:** 1/4" NPT.
Minimum air hose size (ID): 10mm (3/8").
Air pressure: 6.2bar/90psi.
Air consumption: 4cfm* (113ltr/m).
Torque: 50ft/lbs.
Overall length: 255mm.



	KBE-270	2375K	2500K
Sound pressure level:		89dBA	89dBA
Sound power level:		96dBA	89dBA
Vibration level:		4.0m/s ²	4.0m/s ²

*Based on a 15 second cycle per minute average use.

Model Number	Weight each	Order Code
SR375	1.10kg	-2375K
SR500	1.10kg	-2500K

KOBE Speed Ratchet 1/4" Square Drive

1/4

R7722

Suitable for the removal and installation of threaded fasteners. Reversible hardened steel 1/4" square drive. Short body length allowing access into hard to reach areas. Planetary gears for longer life and smoother running. Low profile throttle for precise speed control. Rotating air inlet to prevent the air hose tangling.

Drive size: 1/4" (6mm). **Free speed:** 200rpm.
Recommended air pressure: 6.2bar/90psi. **Air consumption:** 4cfm* (113ltr/min). **Working torque range:** 7 - 27nm (5 - 20ft/lbs).
Air inlet thread: 1/4" NPT. **Minimum air hose size (ID):** 10mm (3/8").
Sound pressure level: 80dBA. **Sound power level:** 88dBA.
Vibration level: 1.8m/s².
Overall length: 200mm.



Weight each	Order Code
0.65kg	KBE-270 -4010K

*Based on a 15 second cycle per minute average use.

KOBE Speed Ratchets

3/8 1/2

FSR375 3/8" square drive.
Working torque range: 5 - 20ft.lbs (7 - 27Nm).
Overall length: 205mm. **Free speed:** 200rpm.

FSR500 1/2" square drive.
Working torque range: 10 - 50ft.lbs (14 - 68Nm).
Overall length: 265mm. **Free speed:** 150rpm.

Suitable for the removal and installation of threaded fasteners when doing automotive and light assembly work. Reversible hardened steel square drive. Rubber handle provides grip and operator comfort. Three planetary gears for longer life and smoother running. Rubber cover protects the ratchet head and the workpiece. Short body length allows access into hard to reach areas. Low profile teasing throttle for precise speed control. Rotating rear exhaust with baffle. Rotating air inlet to prevent the air hose tangling. Adjustable air regulator.

Air inlet thread: 1/4" NPT.
Minimum air hose size (ID): 10mm (3/8").
Air pressure: 6.2bar/90psi.
Air consumption: 4cfm* (113ltr/min).



	KBE-270	2360K	2300K
Sound pressure level:		84dBA	80dBA
Sound power level:		88dBA	87dBA
Vibration level:		1.8m/s ²	2.6m/s ²

Model Number	Weight each	Order Code
FSR375	640g	-2360K
FSR500	1.20kg	-2300K

*Based on a 15 second cycle per minute average use.

KOBE Impact Wrench**IW500**

One piece aluminium housing, 10 position power regulator, thumb switch for reversing, 1/4" NPT air inlet thread for 10mm air hose, 90psi air pressure, 300ft/lbs torque, 4cfm* air consumption, 16mm bolt capacity.

Sound pressure level: 88dBA.
Sound power level: N/A dBA.
Vibration level: 4.2m/s².
Overall length: 191mm.



Free Speed (rpm)	Weight each	Order Code
7,000	2.30kg	-2316P

*Based on a 15 second cycle per minute average use.

KOBE Impact Wrench

Suitable for light workshop and garage use. Twin hammer mechanism with a 4-point adjustable air (speed) forward/reverse speed regulator. Ergonomic and comfortable handle grip with vibration dampening a fixed inlet and exhaust. One finger stop/start trigger operation. Downward facing external exhaust in handle.

Free speed: 10,100rpm,
forward position 1: 8,000rpm,
position 2: 9,100rpm,
position 3: 10,100rpm,
reverse: 10,200rpm.
Maximum torque: 393Nm (290ft/lbs).
Working torque: 339Nm (250ft/lbs).
Recommended air pressure: 6.2bar (90psi).
Air consumption: 3.4cfm*.
Air inlet thread: 1/4" NPT.
Minimum air hose size (ID): 10mm (3/8").
Overall length: 160mm.



Product Number	Order Code
G7321	-5820K

*Based on a 15 second cycle per minute average use.

KOBE Impact Wrench**B7444**

Suitable for production and assembly applications. Twin hammer mechanism. Three position dial style speed regulator. Forward/reverse selection. Ergonomic and comfortable handle grip. Fixed inlet and exhaust.

Forward position 1: 4,000rpm,
position 2: 5,000rpm,
position 3: 7,000rpm.
Reverse position 1: 3,000rpm,
position 2: 5,000rpm,
position 3: 7,000rpm.
Collet size: 1/2" (13mm).
Maximum torque: 813Nm (600ft/lbs).
Recommended air pressure: 6.2bar/90psi.
Air consumption: 4cfm* (113ltr/min).
Air inlet thread: 1/4" NPT.
Minimum air hose size (ID): 10mm (3/8").
Sound pressure level: 83dBA.
Sound power level: 90dBA.
Vibration level: 6.8m/s².
Overall length: 183mm.



Free Speed (rpm)	Weight each	Order Code
7,000	1.94g	-4040K

*Based on a 15 second cycle per minute average use.

1/2

Impact Wrench Kit**IWS500**

Kit supplied complete in robust blow-moulded case.

Includes: 1/2" impact wrench IW500. 10 metric sockets: 9 - 27mm. Threaded tailpiece, in-line mini-oiler and oil bottle. One piece aluminium housing, 10 position power regulator, thumb switch for reversing, 1/4" NPT air inlet thread for 10mm air hose, 90psi air pressure, 300ft/lbs torque, 4cfm* air consumption, 16mm bolt capacity.

Sound pressure level: 93dBA.
Sound power level: N/A dBA.
Vibration level: 1.219m/s².
Overall length: 191mm.



Free Speed (rpm)	Weight each	Order Code
7,000	4.30kg	-2350K

*Based on a 15 second cycle per minute average use.

1/2

Stubby Impact Wrench - Twin Hammer

Suitable for light workshop and garage use. Stubby design allows access to hard to reach work spaces and soft grip handle helps to reduce vibration. Other features include a forward/reverse speed regulator, as well as a downward facing exhaust in handle to lower noise level.

Free speed: 10,000rpm,
forward position 1: 8,000rpm,
position 2: 10,000rpm,
position 3: 11,000rpm,
reverse position 1: 8,000rpm,
position 2: 10,000rpm,
position 3: 11,000rpm.
Maximum torque: 678Nm (500ft/lbs).
Working torque range: 34 - 407Nm (25 - 300ft/lbs).
Recommended air pressure: 6.2bar (90psi).
Air consumption: 4cfm*.
Air inlet thread: 1/4" NPT.
Hose size (ID): 10mm (3/8").
Overall length: 120mm.



Product Number	Order Code
KSW120	-2310K

*Based on a 15 second cycle per minute average use.

1/2

KOBE Impact Wrench**IW750**

One-piece aluminium housing, 10 position power regulator, thumb switch for reversing, 1/4" NPT air inlet thread for 10mm air hose, 25mm bolt capacity. 90psi air pressure, 7.5cfm* air consumption. 500ft/lbs torque.

Sound pressure level: 83dBA.
Sound power level: N/A dBA.
Vibration level: 0.449m/s².
Overall length: 245mm.



Free Speed (rpm)	Weight each	Order Code
4,200	5.00kg	-2325S

*Based on a 15 second cycle per minute average use.

3/4

KOBE Heavy Duty In-Line
Air Impact Wrench

1

IWS100X

1" square drive. Suitable for industrial and commercial production and assembly applications. Side handle for two-handed operation. Top mounted spring balance loop. Easy to use forward/reverse switch and three position power regulator. Top venting exhaust. Oiling points for daily maintenance.

Final drive: 1" (25mm) hex.

Working torque: 2,030Nm (1,500lb/ft).

Maximum torque: 2,300Nm (1,700lb/ft).

Safe working pressure: 6.2bar/90psi.

Air inlet thread: 1/2" NPT.

Minimum air hose size (ID): 1/2" (13mm).


Air pressure: 6.3bar/90psi.

Air consumption: 7.0cfm.

Sound pressure level: 87dBA.

Vibration level: 5.9m/s².

Overall length: 500mm.



Free Speed (rpm)	Weight each	Order Code KBE-270
3,300	9.34kg	-1630B

Pistol Grip Air Impact Wrench

1

IWP100-X

Suitable for industrial and commercial production and assembly applications. Front or rear mounting spring balance loop. Forward/reverse switch and three position power regulator. Forward facing exhaust. Oiling points for daily maintenance.

Final drive: 1" (25mm) hex.

Working torque: 2,170Nm (1,600lb/ft).

Maximum torque: 2,440Nm (1,800lb/ft).

Air inlet thread: 1/2" NPT.

Minimum air hose size (ID): 1/2" (13mm).


Air pressure: 6.3bar/90psi.

Air consumption: 0.8cfm.

Sound pressure level: 87dBA.

Vibration level: 5.9m/s².

Overall length: 295mm.



Free Speed (rpm)	Weight each	Order Code KBE-270
3,400	9.70kg	-1620A

KOBE Air Riveter
Kit**KRK001**

A production rivet gun kit with four different rivet heads for blind rivets 2.4, 3.2, 4.0, and 4.8mm. The rivet is easily set with a pull on the trigger and without the risk of damaged knuckles. On the rear of the gun is a receiver which catches rivet shanks and stores them ready for later disposal. Supplied in a kit box with an impressive collection of rivets, jaws, noses, spare parts and tools. This gun will work on virtually any compressor with a reservoir tank. 1/4" BSP female fitting.

- For blind riveting.
- Adjustable Safety cap which collects ejected rivet pins.
- Suitable for both aluminium and steel rivets up to 4.8mm (3/16").
- Swivel adaptor
- Supplied in carry case.

Maximum Rivet Diameter:

2.4, 3.2, 4.0, 4.8mm.



Model Number	Weight each	Order Code KBE-270
KRK001	1.42kg	-3710K

OSAKI Mini Milling/
Drilling Machine**MMD250**

A must for model makers. Bench mounted, this milling/drilling machine has a spindle rotation of up to 45°, making it a very capable tool. An assortment of useful accessories are available (see list). This versatile tool has been manufactured to meet European Machinery Directive 98/37/EC and is both CE and RoSH compliant.

Swing over bed: 180mm. **Drilling capacity:** 13mm.

End milling capacity: 16mm. **Face milling capacity:** 30mm.

Headstock travel (Z): 180mm. **Cross axis:** 100mm.

Longitudinal axis: 220mm.

Spindle rotary angle: ±45°.

Output power: 350W.

Spindle speed: low

range 0 - 1,100rpm

±10%, high range

0 - 2,500rpm ±10%.

Spindle taper: MT#3.

T-slot: 12mm.

Net/gross weight:

50/68kg.

Packing size:

540 x 500 x

760mm.




FOR DIY USE
Not warranted
for Industrial Use

Product Number	Volts	Motor	Order Code OSA-271
MMD250	240	350W (3/4hp)	-5500K

Toolmaker's Vices**10036**

Made from alloy steel with a quick release mechanism and knurled grip handle. For use with mini milling/drilling machines.




Jaw Dimension
Width x Opening x Height

100 x 85 x 28mm

Order Code
OSA-280

-2410A

Spares**10126****10037****10046**

Product Number	Description	Order Code OSA-280
10126	3MT Direct Drive Collet Set	-2411A
10037	3MT Double Angle Collet Set	-2412A
10046	3MT Indexable Milling Cutter	-2413A
-	Chuck Guard Assembly	-2414A

Order online at cromwell.co.uk or call 0870 850 0055

217

KOBE Magnetic Drilling & Milling Machines

Suitable for light industrial use, these machines have a powerful 1,200W motor providing enough power to drill holes up to 35mm diameter. They have a gravity feed coolant bottle, 13mm chuck, key and weldon adaptor, safety chain, drilling guard and hexagon keys.

Motor: 1,200W.
Arbor: 19mm weldon.
Chuck size: 13mm.
Speed: 595rpm.
Magnetic adhesion: 13,000N.
Dimensions (H x W x D): 390 x 260 x 100mm.
Drilling capacities: core drill 12 - 35mm, twist drill 1.5 - 13mm, countersink 10 - 40mm.
Cutting depth: 50mm.
Stroke: 165mm.



Model Number	Voltage	Weight each	Order Code
DMM3050	230V	13.5kg	KBE-268 -4220K

KENNEDY QUALITY INDUSTRIAL TOOLING

M2 Multi-Tooth Milling Cutter Set

Short Series
Shank diameter: 19mm/3/4".
Depth of cut: 25mm.
Bore: 6mm.
Overall length: 60mm.
 Compatible with all magnetic drilling and broaching units. Complete with pilot pin and fitted case.
Sizes: 14, 16, 18, 20, 22 and 24mm.



Weight each	Order Code
800g	KEN-288 -3000K

6
PIECES

KENNEDY QUALITY INDUSTRIAL TOOLING Morse Taper Adaptors

For use with Magtron broaching units, drill presses, lathes etc.

Bore diameter: 20mm.
Overall length: 156mm.



Adaptor	Weight each	Order Code
No.2 MT	0.6kg	KEN-288 -4120K
No.3 MT	1.0kg	-4130K

Pilot Pins

For use with all multi-tooth milling cutters with 6mm bore. Pilots locate into pre-drilled pilot holes ensuring positional accuracy of the cutter. Suitable for 'blind' or 'through' pilot holes, pin will retract into cutter adaptor on 'bottoming'.

Short series: 77mm.
Long series: 102mm.



* For 12mm cutters only

Description	Weight each	Order Code
Short Series	15g	KEN-288 -4010K
Short Series*	15g	-4050K
Long Series	20g	-4020K
Long Series*	20g	-4060K

M2 Multi-Tooth Milling Cutters

Proven value and success based upon the low energy required to cut more holes accurately with extended tool life. The cutter is designed to enable a faster feed rate with lower cutting resistance, resulting in consistency of finish and tolerance.

Sizes available:
 2 - 52mm diameter short and
 13 - 52mm diameter long series.

Long Series
Shank diameter: 19mm/3/4".
Depth of cut: 50mm.
Bore: 6mm.
Overall length: 85mm.



Cutting Dia. (mm)	Weight each	Order Code
13	80g	KEN-288 -2130K
14	80g	-2140K
15	90g	-2150K
16	90g	-2160K
17	100g	-2170K
18	110g	-2180K
19	110g	-2190K
20	120g	-2200K
21	130g	-2210K
22	130g	-2220K
23	130g	-2230K
24	140g	-2240K
25	150g	-2250K
26	160g	-2260K
27	160g	-2270K
28	170g	-2280K
29	180g	-2290K
30	180g	-2300K
31	190g	-2310K
32	190g	-2320K
33	210g	-2330K
34	210g	-2340K
35	210g	-2350K
36	220g	-2360K
37	290g	-2370K
38	260g	-2380K
39	260g	-2390K
40	260g	-2400K
41	260g	-2410K
42	260g	-2420K
43	280g	-2430K
44	300g	-2440K
45	320g	-2450K
46	280g	-2460K
48	400g	-2480K
49	410g	-2490K
50	360g	-2500K
51	420g	-2510K
52	520g	-2520K

Short Series
Shank diameter: 19mm/3/4".
Depth of cut: 25mm.
Bore: 6mm.
Overall length: 60mm.



Cutting Dia. (mm)	Weight each	Order Code
12	70g	KEN-288 -1120K
13	70g	-1130K
14	70g	-1140K
15	75g	-1150K
16	80g	-1160K
17	80g	-1170K
18	85g	-1180K
19	90g	-1190K
20	90g	-1200K
21	100g	-1210K
22	100g	-1220K
23	120g	-1230K
24	110g	-1240K
25	110g	-1250K
26	120g	-1260K
27	120g	-1270K
28	130g	-1280K
29	135g	-1290K
30	140g	-1300K
31	150g	-1310K
32	150g	-1320K
33	160g	-1330K
34	160g	-1340K
35	170g	-1350K
36	170g	-1360K
37	175g	-1370K
38	180g	-1380K
39	185g	-1390K
40	190g	-1400K
41	200g	-1410K
42	220g	-1420K
43	260g	-1430K
44	220g	-1440K
45	220g	-1450K
46	240g	-1460K
48	250g	-1480K
49	260g	-1490K
50	240g	-1500K
51	270g	-1510K
52	290g	-1520K

KOBE 'Combi-Sand' Belt & Disc Sander

Semi-portable, yet its robust construction makes it ideal for workshop use. Disc sanding table that tilts to 45° for bevel sanding and when used with the mitring guide is ideal for sanding compound angles. The sanding belt is ideal for flat surface sanding but tilts up to 90° for end sanding. Can be directly connected to dust extraction by way of the 61mm outlet port on the end of the sander.

Power input: 370W.

Sanding disc: 150mm PSA (Stikit).

Sanding belt: 100 x 914mm (4" x 36").



Product Number	Weight each	Order Code
SBD370	18.6kg	KBE-271 -4140K

Belts to Suit Al-Ox
Also suitable for SIP 01946

Size (W x L): 100 x 915mm.

Grit	Order Code	0
P60	-1120K	
P80	-1140K	
P100	-1160K	
P120	-1180K	

370
WATTS

Variable Speed Scroll Saw

High performance scroll saw suitable for home woodworking and model making projects, pattern makers and technical colleges. Variable speed motor gives ultimate control regardless of the material being cut. Parallel arm design ideal for cutting curves. Dust blower to keep work area free of sawdust. Table can be adjusted 0 - 45°. Adjustable safety guard and drop foot. Cast iron base.

Variable speed: 550 - 1,600spm.

Max cutting length: 405mm.

Max cutting depth: 50mm.

Stroke: 20mm.

Table size: 415 x 255mm.

Supplied with: pinless blade adaptors.

Blades: 1x 133 x 3mm x 15TPI and 1x 133 x 2mm x 18TPI.




Product Number	Weight each	Order Code	
KSS406	18.6kg	KBE-271 -8520K	NA

90
WATTS
VARIABLE
SPEED

Air & Power Tools

Al-Ox



KOBE Submersible Water Pump

Suitable for the effective draining of cellars, cisterns and the general transfer of water. Capable of continuous and reliable running, strong double insulated case with no metal parts are in contact with the water. Overload protection and easy to remove filters for cleaning and access to the impeller. Fitted with an automatic float switch and a multi hose adaptor (25, 32, 38mm), can handle solids up to 5mm diameter.

Motor: 750W.

Maximum delivery height: 8.5m.

Power cable: 10m.

Flow rate: 230ltr.



Product Number
WPS 750

Order Code
KBE-279
-4470K

750
WATTS

240V

230ltr
PER MIN

10m
CABLE

Wet & Dry Vacuum Cleaner & Blower

Lightweight, compact and portable design with powerful 1,200W two stage motor. Vacuums up dirt, debris and liquid. Low noise model with 30 litre capacity and safety shut-off for wet operation.

Supplied with: 2m vacuum hose, 2x aluminium extension pipes, 32mm brush tool, squeegee tool, round brush tool, crevice tool, paper filter cartridge, cylinder for wet vacuuming and 11 litre fleece vacuum bag.

Suction hose: 2m.

Capacity: 30 ltr.

Size (H x W x D):

600 x 370 x 360mm.

1200
WATTS

30
LTR



Product Number	Voltage	Weight each	Order Code
KWDVB30L	240V	11.0kg	KBE-279 -3140K

Replacement Fleece Bag

Product Number	Suitable for	Order Code
3573BJ-07	KWDVB30L	KBE-280 -7690K

Wet & Dry Vacuum Cleaner

Suitable for industrial and commercial use. Two powerful motors, 1,200W and 2,400W for superior performance in cleaning large areas. Portable design with swivel stainless steel drum for easy emptying of waste and liquids. Trolley with two front swivel castor wheels for ease of movement and 2 large rear fixed wheels for enhanced stability.

Supplied with: 3m vacuum hose, 2x stainless steel extension pipes, 38mm brush tool, crevice tool, squeegee tool, round brush tool, crevice tool, paper filter cartridge for dry vacuuming and cloth filter for wet vacuuming.

Suction hose: 3m.

Capacity: 55 ltr.

Size (H x W x D):

880 x 490 x 540mm.

2400
WATTS

55
LTR



Product Number
KWDV55L

Voltage
240V

Weight each
25.5kg

Order Code
KBE-279
-3170K

OSAKI High Pressure Washer

For easy cleaning of vehicles, patios and other light duty applications. Compact and portable design with 5m length high pressure hose and trigger gun. Automatic on/off. Adjustable lance nozzle for fan or open jet wash pattern and an attachable soap dispenser bottle. Comes with 5m length of power cord.

Power: 1.5kW.
Max rated pressure: 90bar.
Max water flow: 360ltr/hr.
Dimensions (L x W x H): 290 x 330 x 610mm.

90
BAR



Product Number	Weight each	Order Code	
HPW090	12.14kg	OSA-279-9610K	NA



Air & Power Tools

Spare Parts

To suit: OSA- 279- 6100K, OSA- 279- 6110K, OSA- 279- 9610K, OSA- 279- 9620K.

Spare Parts:
Replacement lance and trigger assembly.

Description	Order Code	
Lance & Trigger Assembly	OSA-280-1701W	NA

SOLENT Wash & Wax

High foam, high gloss vehicle shampoo. Mild formula, neutral pH, water based. Effectively lifts traffic film without harm to polished paintwork and trim. With foam boosters for fast removal of dirt and grease. High gloss wax finish. Can be used with hot or cold pressure washing systems or hand washing. Easy to handle container.



Type	Size	Order Code
Poly Bottle	5ltr	SOL-780-6500A
Plastic Drum	20ltr	-6510B

Traffic Film Remover Concentrate

Effectively removes dirt, grime, grease and tenacious traffic film from all vehicles. Suitable for cleaning chassis and bodywork on vehicles. Designed for high pressure washing with mechanical power wash systems. Concentrated formula can also be used to clean machinery, floors, walls, asphalt, will also remove co-polymer waxes used in new car production.



Type	Size	Order Code
Poly Bottle	5ltr	SOL-780-6400A

KOBE

12V Drill/Driver Combo

Featuring ergonomic soft grip handle, fast charging time, trigger with speed adjustment and reverse option, LED light.

• Supplied with carry case and strap

Combo contains:

- 1x Combi drill
- 1x Impact driver
- 2x 1.3Ah Li-Ion batteries
- 1x Charger with battery power indicator lights



No. of Batteries	Battery Capacity Ah	Order Code
2	1.3	KBE-279 -4600K

12V Combi Drill

Featuring 20 torque settings and 3 function settings (driving, drilling and drilling with impact), 2 speed setting with reverse, built-in LED light, keyless chuck, ergonomic soft grip handle.

Max. load speed: 1,300rpm

Max. chuck capacity: 10mm

Max. torque: 45Nm

Max. drilling: 10mm (steel), 18mm (wood)

Charging time: 60 minutes

Weight (net): 0.84kg

Supplied with 2x 1.3Ah Li-ion batteries, charger and carry case



No. of Batteries	Battery Capacity Ah	Order Code
2	1.3	KBE-279 -4620K

12V Cordless Impact Driver

Featuring built-in LED light, trigger with speed adjustment and reverse, quick release chuck and ergonomic soft grip handle.

Max. load speed: 2,000rpm

Max. impact rate: 3,000bpm

Collet size: 6mm (1/4")

Torque: 80-90Nm

Weight (net): 900g

Supplied with 2x 1.3Ah Li-ion batteries, charger and carry case



No. of Batteries	Battery Capacity Ah	Order Code
2	1.3	KBE-279 -4640K

Li-ion Battery Chargers

Output voltage: 18V

Supply voltage: 230V

Charging current: 1.5A

Battery capacity: 2.0Ah

Charging time: 60m



Volts V	Voltage V	Charging Time min.	Battery Capacity Ah	Order Code
18	230	60	2.0	KBE-280 -5911A

18V Li-ion Battery Pack

LSBH4945-2

Spare Li-ion battery to suit Kobe chargers. 2.0Ah



Model	Volts V	Battery Capacity Ah	Order Code
LSBH4945-2	18	2.0	KBE-280 -5910A NA

KOBE 18V Cordless Combi Drill & Impact Driver Twin Pack

Pack comes with carry case and includes charger and 2x 2.0Ah Li-Ion Batteries. Both drill and driver feature ergonomic soft grip handles, built-in LED light and bit holder, and trigger with speed adjustment feature.

Box Contents:

- 18V Li-Ion combi drill
- 18V Li-Ion impact driver
- 2 x 2.0Ah Li-Ion batteries
- 2.0Ah Li-Ion battery charger with battery power indicator lights
- Carry case with shoulder strap



Carry Case



Built-in LED Light

**LI-ION
TECH**



Product Number	Battery Size	Order Code
KDD182	2x 2.0Ah	-2300K

18V
Li-Ion

Air & Power Tools

18V Cordless Impact Driver Pack

KID18

Comes with carry case, charger and 2x 2.0Ah Li-Ion batteries. Features LED light, bit holder, quick release chuck.



Carry Case



Pack includes Charger & 2x 2.0Ah Li-Ion Batteries

Battery Size	Order Code	
2x 2.0Ah	KBE-279 -2360K	NA

50 Years of Keeping Industry Working
© 2022

18V
Li-Ion

18V Cordless Combi Drill Pack

KCD18

Comes with carry case, charger and 2x 2.0Ah Li-Ion batteries. 15 torque settings and three function settings (driving, drilling and drilling with impact), two speed settings, LED light, keyless chuck.



Carry Case



Pack includes Charger & 2x 2.0Ah Li-Ion Batteries

Battery Size	Order Code	
2x 2.0Ah	KBE-279 -2330K	NA

18V
Li-Ion



KOBE Professional Heat Gun Kit

For use in a variety of settings such as soldering, welding PVC, shaping, drying, shrink-fitting, stripping paint, removing sticky labels etc. Temperature and air flow controls allow for precise settings to be achieved. LCD display to show temperature and air flow settings. Ceramic heating element increases longevity and provides optimal quality. Thermal cut-out protection prevents the tool from damage due to overheating. Memory storage of last used settings for quick start-up. Can be used free-standing on a work surface facing upwards for hands-free use.

Power input: 2000W.

Working temperature: 50 - 650°C.

Accessories:


4 detachable nozzles, paint scraper and moulded carry case.



Voltage	Order Code
240V	KBE-279 -2150K

Triangular Paint Scraper

For flat and fine complex shapes.



Order Code
KBE-280 -3420K

Angle Grinder - 115mm (4½")

700W motor. Aluminium alloy gear housing. Slim, low profile body design for easy use and access. Multi-position side handle. Protective guard that can be turned 60°. Spindle locking device.

Frequency: 50Hz.

No load speed: 11,500rpm.


Spindle thread: M14.

Disc size: 115mm (not included).



Product Number	Voltage	Order Code
KAG115	230V	KBE-279 -1420G

NA

**SIP 8" Professional Bench Grinder**

550 kW

07628

Designed with a robust metal housing and precision sealed, lubricated spindle bearings this grinder has been manufactured to a high standard giving maximum performance and a longer working life. The powerful 550kW induction motor powers 2 grinding wheels which are 8" diameter, 1" width with ¾" bore. Supplied with a wire wheel, adjustable tool rests, eye shields, spark arrestors and wheel guards.

Motor: 230V / 550kW

Max. grinding wheel width: 25mm.



Motor	Order Code	List
550kW	SIP-277 -0759N	

150mm Professional Bench Grinder**07625**

Single phase, NVR emergency stop switch, robust metal housing and precision sealed spindle bearings.

- Ideal for sharpening of workshop and garage tools
- IP23
- Supplied with 2x grinding wheels and 1x wire wheel, 6" rotary wire brush

Power: 350W.

Voltage: 240V (13A).

Max. speed: 2,850rpm.

Spindle diameter: 12.7mm.

Wheel width: 20mm.

Weight: 6.3kg.



Product Number	Motor w	Order Code
07625	350	SIP-277 -0759P

OSAKI Engraver Kit
POWER TOOLS
ENG003

Electric hand held engraver with positive on/off switch and 5 position stroke adjuster for varied engraving depths. For use on metals, plastics, glass, ceramics, wood and leather.

- 5-Position adjustable engraving depth.
- Includes 2 tips and template for letters and numbers.
- Soft grip.
- Positive On/Off.
- 1.8m cable.



Voltage	Weight each	Order Code
230V	375g	OSA-279 -9810K

KOBE Multi-Tool Accessory Kit

Fitted plastic case containing 53 piece multi-tool kit for a range of surface cleaning and polishing tasks.

Contents: 1x silicon carbide sanding wheel with $\frac{1}{8}$ " diameter shank, 1x aluminium oxide sanding wheel with $\frac{1}{8}$ " diameter shank, 1x holder $\frac{1}{4}$ " x $\frac{1}{2}$ ", 1x holder $\frac{1}{2}$ " x $\frac{1}{2}$ ", 1x mandrel shank dia: $\frac{1}{8}$ ", 1x nylon end brush, 1x wire cup brush, 2x grinding wheel $\frac{1}{8}$ " x $\frac{13}{16}$ ", 30x cutting disc $\frac{1}{32}$ " x $\frac{15}{16}$ ", 6x sanding band $\frac{1}{2}$ " x $\frac{1}{2}$ ", 8x sanding band $\frac{1}{4}$ " x $\frac{1}{2}$ ".

53
PIECES


Product Number	Order Code
KIT53PC	KBE-280 -3380K

Spindle

Taper screw.



Product Number	Shank Dia.(mm)	Order Code
M1	3.2	KBE-280 -3371K

50 Years of Keeping Industry Working
© 2022

Sanding Pads & Polishing Foams

KENNEDY Flexible Backing Pads for Hook-n-Loop Sanding Discs

Suitable for use with Kennedy Hook-n-Loop sanding discs.



To Suit Disc	Thread Size	Hole Configuration	Order Code KEN-280
115mm	M14 x 2.0	No Hole	-3110K
125mm	M14 x 2.0	No Hole	-3230K
	5/8" UNC	No Hole	-3210K
	M14 x 2.0	No Hole	-3330K
	5/8" UNC	No Hole	-3310K
150mm	5/16" UNF Male	No Hole	-3370K
	5/16" UNF Male	6 Hole	-3390K

Flexible Backing Pads

Suitable for use with all portable and air disc grinders and sanders. Recommended for use with York abrasive discs.



To Suit Disc	Thread Size	Weight each	Order Code KEN-280
100mm	M10 x 1.25	60g	-2010K
	M10 x 1.5	60g	-2030K
	3/8" UNF	70g	-2050K
115mm	M10 x 1.5	80g	-2110K
	M14 x 2.0	80g	-2130K
125mm	5/8" UNC	100g	-2210K
	M14 x 2.0	100g	-2230K
	5/8" UNC	180g	-2310K
	M14 x 2.0	180g	-2330K
178mm	5/8" UNC	150g	-2350K
	Quick Release		
	M14 x 2.0	150g	-2370K
	Quick Release		NA

Flexible Backing Pads for Self-Stick Sanding Discs


Designed for use with orbital sanders.



To Suit Disc	Thread Size	Hole Configuration	Order Code KEN-280
150mm	5/16" UNF	No Hole	-3870K
	5/16" UNF	6 Hole	-3920K

Sander Polisher Pads

Hook-n-Loop faced for use as a super buffing pad holder or foam holder. Can be used with tie on bonnets. Max 8,500rpm. Foams and bonnets supplied separately.



Diameter (mm)	Thread Size	Order Code KEN-280	List
178	M14 x 2	-5220K	

KOBE Flexible Backing Pads for Hook-n-Loop Sanding Discs

For use with Kobe Hook-n-Loop backed sanding discs, for rapid abrasive disc changing.



To Suit Disc	Thread Size	Hole Configuration	Order Code KBE-280
50mm	M6	No Hole	-0201A
75mm			-0202A

Hook-n-Loop Backed Sanding Discs

No spanners required. 100% of disc can be used, material removal rate is therefore increased. Can be repeatedly removed and re-applied. Silicon carbide abrasive especially suitable for automotive body preparation prior to spraying and for cutting back two-pack paint finishes. Can be used wet or dry.




Disc Diameter	Grade	Pack Quantity	Order Code KBE-280	Price/Pk
50mm (2")	320	25	-0203A	
	400		-0204A	
	600		-0205A	
75mm (3")	320	25	-0206A	
	400		-0207A	
	600		-0208A	

KENNEDY Buffing & Polishing Foams

A range of professional polishing foams for use with all makes of power tools. Offers a complete surface finishing solution. All pads are 150mm diameter x 50mm deep.

White Compounding Foam

Excellent results with all leading makes of compound and polish. Very firm material, ideal for all modern paints including LVHM.



Diameter (mm)	Thread Size	Order Code KEN-280
150	M14 x 2	-5260K

Blue Regular Compounding Foam

Softer, all purpose foam for polishing and compounding of cellulose and acrylic. With a medium density grade.



Diameter (mm)	Thread Size	Order Code KEN-280
150	M14 x 2	-5300K

Red Final Polishing Foam

Ultra soft reticulated foam for final polishing/finishing. Designed to allow free flow of air.



Diameter (mm)	Thread Size	Order Code KEN-280
150	M14 x 2	-5380K

Drill Bit Sets, Core Drills & Fix-It Kits

055|280 Group

Air & Power Tools

KOBE Diamond Core Drills

Manufactured from tool grade steel to ensure perfect concentricity with good weld strength. Can be used across a wide range of building materials such as: facing bricks, concrete blocks, breeze blocks, building blocks, hand made bricks and soft to medium hard natural stones.

Set Contents:

42, 52, 65, 117 and 127mm core.
Chuck adaptor
chuck extension
SDS adaptor
SDS extension
guide rod taper drill guide
drift key.

12
PIECES



Size	Order Code KBE-280
42mm	-0310K
52mm	-0312K
65mm	-0314K
117mm	-0316K
127mm	-0318K
12 Piece Core Drill Set	-0300K

KENNEDY Fix-it Kits

Wall Plugs

Contents: yellow, red, brown and blue.



Average Quantity	Order Code KEN-615
220	-4740K

Tile & Masonry Drill Sets

2 Piece Sets

Two piece sets for drilling through glass, tiles, mirrors and ceramics.

Set contents:

1x masonry drill bit and 1x tile and glass drill bit.

2
PIECES



Diameter	Order Code KBE-280
6.00mm	-7510K
6.50mm	-7520K
7.00mm	-7530K

SENATOR QUALITY TOOLING 18 Piece Drill Set

Sizes: 3, 4, 5, 6, 8 and 10mm.

Supplied in 'dial a drill' case for easy selection.

6 x each drills
Wood, Masonry
and HSS

18
PIECES

Weight each	Order Code SEN-025
452g	-9500K



KOBE Diamond Core Drills

Manufactured from tool grade steel to ensure perfect concentricity with good weld strength. Can be used across a wide range of building materials such as: facing bricks, concrete blocks, breeze blocks, building blocks, hand made bricks and soft to medium hard natural stones.



Description	Order Code KBE-280
10 x 200mm 'A' Taper Pilotdrill	-0150A
240mm SDS Long Series Arbor	-0151A
240mm Hex Series Arbor	-0152A
Guide Rod	-0153A
Drift Key	-0154A
110mm Hex Short Series Arbor	-0155A
85mm SDS Short Series Arbor	-0156A

KENNEDY Rotary Masonry Drill Bit Sets

7 Piece - Standard Length

Standard Length: No.6 x 75,
No.8 x 85, No.10 x 85,
No.10A x 100, No.12 x 100,
No.16 x 120, No.20 x 120mm.

7
PIECES

7 Piece - Standard & Medium Length

Standard Length:
No.10 x 85, No.12 x 100,
No.14 x 100, No.16 x 120,
No.20 x 120.

Medium Length:

No.24 x 150, No.26 x 150mm.

7
PIECES


16 Piece - Standard & Medium Length

Standard Length:
No.6 x 75, No.8 x 85, No.10 x 85,
No.10A x 100, No.14 x 100,
No.16 x 120, No.18 x 120, No.20 x 120.

Medium Length:

No.8 x 150, No.10 x 150, No.10A x 150,
No.14 x 150, No.16 x 150, No.18 x 150,
No.20 x 150, No.24 x 150mm.

16
PIECES



Number of Pieces	Order Code KEN-055
7 - Standard	-5070K
7 - Standard & Medium	-5170K
16 - Standard & Medium	-5320K

50 Years of Keeping Industry Working
© 2022

KENNEDY
QUALITY INDUSTRIAL TOOLING**Rotary Masonry
Drill Bits**

Tungsten carbide tipped with roll forged flutes. A general purpose mortar and masonry drill bit suitable for workshop and maintenance. Manufactured to **DIN 8039**.

Standard Length**75.0mm to 120.0mm Length**

Diameter	Overall Length	Weight each	Order Code KEN-055
No.6 (4.0mm)	75.0	6g	-0060K
No.8 (5.0mm)	85.0	10g	-0080K
No.10 (5.5mm)	85.0	14g	-0100K
No.10A (6.0mm)	100.0	14g	-0110K
No.12 (6.5mm)	100.0	17g	-0120K

Diameter	Overall Length	Weight each	Order Code KEN-055
No.14 (7.0mm)	100.0	17g	-0140K
No.16 (8.0mm)	120.0	27g	-0160K
No.18 (9.0mm)	120.0	28g	-0180K
No.20 (10.0mm)	120.0	40g	-0200K
No.23 (12.0mm)	120.0	55g	-0450K

Medium Length**150.0mm to 160.0mm Length**

Diameter	Overall Length	Weight each	Order Code KEN-055
No. 8 (5.0mm)	150.0	17g	-1080K
No.10 (5.5mm)	150.0	22g	-1100K
No.10A (6.0mm)	150.0	22g	-1110K
No.12 (6.5mm)	150.0	50g	-1120K
No.14 (7.0mm)	150.0	25g	-1140K
No.16 (8.0mm)	150.0	34g	-1160K
No.18 (9.0mm)	150.0	35g	-1180K
No.20 (10.0mm)	150.0	50g	-1200K

Diameter	Overall Length	Weight each	Order Code KEN-055
No.22 (11.0mm)	150.0	50g	-1220K
No.24 (13.0mm)	150.0	84g	-1240K
No.25 (14.0mm)	150.0	100g	-1250K
No.26 (16.0mm)	150.0	128g	-1260K
No.27 (18.0mm)	160.0	132g	-1270K
No.28 (20.0mm)	160.0	195g	-1280K
No.29 (22.0mm)	160.0	245g	-1290K
No.30 (25.0mm)	160.0	308g	-1300K

Extra Length**300.0mm Length**

Diameter	Overall Length	Weight each	Order Code KEN-055
No.12 (6.5mm)	300.0	58g	-3120K
No.14 (7.0mm)	300.0	58g	-3140K
No.16 (8.0mm)	300.0	91g	-3160K
No.20 (10.0mm)	300.0	98g	-3200K
No.22 (11.0mm)	300.0	130g	-3220K
No.24 (13.0mm)	300.0	164g	-3240K

400.0mm Length

Diameter	Overall Length	Weight each	Order Code KEN-055
No.16 (8.0mm)	400.0	124g	-4160K
No.18 (9.0mm)	400.0	125g	-4180K
No.20 (10.0mm)	400.0	130g	-4200K
No.24 (13.0mm)	400.0	219g	-4240K

Rotary Masonry Drill Bit Sets**7 Piece - Standard Length**

Standard Length: No.6 x 75, No.8 x 85, No.10 x 85, No.10A x 100, No.12 x 100, No.16 x 120, No.20 x 120mm.

7 Piece - Standard & Medium Length**Standard Length:**

No.10 x 85, No.12 x 100, No.14 x 100, No.16 x 120, No.20 x 120.

Medium Length:

No.24 x 150, No.26 x 150mm.

16 Piece - Standard &**Medium Length****Standard Length:**

No.6 x 75, No.8 x 85, No.10 x 85, No.10A x 100, No.14 x 100, No.16 x 120, No.18 x 120, No.20 x 120.

Medium Length: No.8 x 150, No.10 x 150, No.10A x 150,

No.14 x 150, No.16 x 150, No.18 x 150, No.20 x 150, No.24 x 150mm.

**7
PIECES****16
PIECES**

Number of Pieces	Weight each	Order Code KEN-055
7 - Standard	140g	-5070K
7 - Standard & Medium	400g	-5170K
16 - Standard & Medium	460g	-5320K



SDS-Style Fitting Hammer Drill Bits

Tungsten carbide tipped and suitable for all SDS direct fitting hammer drills. High performance drill bits that withstand extreme heat generation ensuring maximum performance coupled with wear resistance. Manufactured to **DIN 8035**.



Diameter	Overall Length	Weight each	Order Code KEN-057	Diameter	Overall Length	Weight each	Order Code KEN-057
5.0mm	110.0	50g	-1000K	13.0mm	166.0	110g	-3020K
5.0mm	160.0	50g	-1020K	13.0mm	210.0	100g	-3040K
5.5mm	110.0	50g	-1200K	13.0mm	466.0	300g	-3140K
5.5mm	160.0	50g	-1220K	14.0mm	166.0	155g	-3220K
6.0mm	110.0	50g	-1400K	14.0mm	216.0	170g	-3240K
6.0mm	160.0	50g	-1420K	14.0mm	266.0	180g	-3280K
6.0mm	210.0	60g	-1440K	14.0mm	316.0	200g	-3300K
6.5mm	110.0	50g	-1600K	14.0mm	466.0	300g	-3340K
6.5mm	160.0	50g	-1620K	14.0mm	600.0	410g	-3380K
7.0mm	110.0	60g	-1800K	15.0mm	166.0	200g	-3420K
7.0mm	160.0	70g	-1820K	15.0mm	266.0	200g	-3480K
8.0mm	110.0	80g	-2000K	15.0mm	450.0	250g	-3540K
8.0mm	160.0	80g	-2020K	16.0mm	250.0	150g	-3640K
8.0mm	210.0	90g	-2040K	16.0mm	300.0	200g	-3700K
8.0mm	260.0	110g	-2080K	16.0mm	450.0	350g	-3740K
8.0mm	400.0	180g	-2120K	16.0mm	600.0	450g	-3760K
9.0mm	210.0	100g	-2240K	18.0mm	250.0	240g	-4040K
10.0mm	110.0	70g	-2400K	18.0mm	450.0	400g	-4140K
10.0mm	160.0	90g	-2420K	20.0mm	200.0	200g	-4440K
10.0mm	210.0	110g	-2440K	20.0mm	300.0	300g	-4500K
10.0mm	260.0	150g	-2480K	20.0mm	450.0	480g	-4540K
10.0mm	360.0	180g	-2520K	22.0mm	250.0	350g	-4680K
10.0mm	460.0	280g	-2540K	22.0mm	450.0	720g	-4740K
11.0mm	160.0	110g	-2620K	24.0mm	250.0	390g	-4880K
11.0mm	300.0	130g	-2680K	24.0mm	450.0	770g	-4940K
12.0mm	166.0	100g	-2820K	25.0mm	250.0	430g	-5080K
12.0mm	216.0	130g	-2840K	25.0mm	450.0	770g	-5140K
12.0mm	316.0	170g	-2900K	26.0mm	250.0	430g	-5280K
12.0mm	466.0	240g	-2940K	26.0mm	450.0	850g	-5340K
12.0mm	600.0	350g	-2980K				

SDS-Style Fitting Drill Bit Sets

Tungsten carbide tipped and suitable for all SDS direct fitting hammer drills. High performance drill bits that withstand extreme heat generation ensuring maximum performance coupled with wear resistance.

Manufactured to **DIN 8035**.

7 Piece

5, 6 and 8mm x 110mm overall length.

6, 8, 10 and 12mm x 160mm overall length.

9 Piece

5, 5.5, 6 and 7mm x 160mm overall length.

8 x 210mm,

8 x 260mm,

12 x 216mm,

12 x 316mm,

16 x 250mm overall length.

**7
PIECES**

**9
PIECES**



Number of Pieces	Order Code KEN-057
7	-7000K
9	-7020K

KENNEDY
QUALITY INDUSTRIAL TOOLING**Constant Pitch
Bi-Metal HSS
Holesaws**

Featuring a constant pitch - first choice for cutting thin sheet materials up to 3mm thick. For producing high quality holes in wood, steel, brass, bronze, cast iron, aluminium and plastic. Featuring a hardened HSS cutting edge welded to a tough alloy steel body. Heavy duty shatter-resistant construction, virtually unbreakable.

**6 teeth per inch.
38mm (1½")
cutting depth.**



**CONSTANT
PITCH FOR
SHEET
UP TO 3mm**

Holesaw Sizes	Use Arbor
14 to 30mm	K1 or K4
32 to 210mm	K2 or K10

Cutting Dia. (mm)	Weight each	Order Code KEN-050
14 (9/16")	27g	-0140K
16 (5/8")	28g	-0160K
17 (11/16")	35g	-0170K
19 (3/4")	34g	-0190K
20 (25/32")	39g	-0200K
21 (13/16")	39g	-0210K
22 (7/8")	46g	-0220K
24 (15/16")	57g	-0240K
25 (1")	61g	-0250K
27 (1 1/16")	74g	-0270K
29 (1 1/8")	83g	-0290K
30 (1 3/16")	93g	-0300K
32 (1 1/4")	75g	-0320K
33 (1 3/16")	81g	-0330K
35 (1 3/8")	93g	-0350K
37 (1 7/16")	100g	-0370K
38 (1 1/2")	86g	-0380K
40 (1 9/16")	91g	-0400K
41 (1 5/8")	100g	-0410K
43 (1 11/16")	100g	-0430K
44 (1 3/4")	100g	-0440K
46 (1 13/16")	110g	-0460K
48 (1 7/8")	110g	-0480K
51 (2")	120g	-0510K
52 (2 1/16")	120g	-0520K
54 (2 1/8")	130g	-0540K
56 (2 3/16")	135g	-0560K
57 (2 1/4")	140g	-0570K
59 (2 5/16")	150g	-0590K
60 (2 3/8")	160g	-0600K
64 (2 1/2")	170g	-0640K
65 (2 9/16")	180g	-0650K
67 (2 5/8")	190g	-0670K
68 (2 11/16")	200g	-0680K
70 (2 3/4")	210g	-0700K
73 (2 7/8")	230g	-0730K
76 (3")	230g	-0760K
79 (3 1/8")	260g	-0790K
83 (3 1/4")	310g	-0830K
86 (3 3/8")	330g	-0860K
89 (3 1/2")	330g	-0890K
92 (3 5/8")	330g	-0920K
95 (3 3/4")	365g	-0950K
102 (4")	365g	-1020K
105 (4 1/8")	400g	-1050K
108 (4 1/4")	400g	-1080K
111 (4 3/8")	435g	-1110K
114 (4 1/2")	465g	-1140K
121 (4 3/4")	500g	-1210K
127 (5")	565g	-1270K
133 (5 1/4")	600g	-1330K
140 (5 1/2")	650g	-1400K
152 (6")	800g	-1520K
168 (6 5/8")	1000g	-1680K
177 (6 31/32")	1050g	-1770K
210 (8 9/32")	1200g	-1540K

**Variable Pitch Bi-Metal
HSS Holesaws**

For wood, steel, brass, bronze, cast iron, aluminium and plastic. Aggressive cutting action and M3 HSS cutting teeth to give a very smooth finish. Cuts up to 40% faster than constant pitch saws. The varying tooth pitch gives substantial reductions in noise by disrupting harmonics. Tooth life is greatly extended, as is battery life when used with a cordless drill. Suitable for all uses: engineering, construction and maintenance.

**4 to 6 teeth per inch.
28.5mm (1 1/8") cutting depth.**

**VARIABLE
PITCH FOR
IMPROVED
ACTION**



Cutting Dia. (mm)	Weight each	Order Code KEN-050
14 (9/16")	30g	-5140K
16 (5/8")	40g	-5160K
17 (11/16")	40g	-5170K
19 (3/4")	40g	-5190K
20 (25/32")	50g	-5200K
21 (13/16")	50g	-5210K
22 (7/8")	60g	-5220K
24 (15/16")	70g	-5240K
25 (1")	80g	-5250K
27 (1 1/16")	80g	-5270K
29 (1 1/8")	90g	-5290K
30 (1 3/16")	100g	-5300K
32 (1 1/4")	100g	-5320K
33 (1 3/16")	110g	-5330K
35 (1 3/8")	120g	-5350K
37 (1 7/16")	130g	-5370K
38 (1 1/2")	80g	-5380K
40 (1 9/16")	90g	-5400K
41 (1 5/8")	90g	-5410K
43 (1 11/16")	100g	-5430K
44 (1 3/4")	110g	-5440K
46 (1 13/16")	110g	-5460K
48 (1 7/8")	130g	-5480K
51 (2")	140g	-5510K
52 (2 1/16")	150g	-5520K
54 (2 1/8")	150g	-5540K
56 (2 3/16")	160g	-5560K
57 (2 1/4")	170g	-5570K
59 (2 5/16")	170g	-5590K
60 (2 3/8")	180g	-5600K
64 (2 1/2")	200g	-5640K
65 (2 9/16")	210g	-5650K
67 (2 5/8")	220g	-5670K
68 (2 11/16")	225g	-5680K
70 (2 3/4")	230g	-5700K
73 (2 7/8")	240g	-5730K
76 (3")	260g	-5760K
79 (3 1/8")	280g	-5790K
83 (3 1/4")	300g	-5830K
86 (3 3/8")	330g	-5860K
89 (3 1/2")	340g	-5890K
92 (3 5/8")	370g	-5920K
95 (3 3/4")	390g	-5950K
102 (4")	430g	-6020K
105 (4 1/8")	460g	-6050K
108 (4 1/4")	470g	-6080K
111 (4 3/8")	500g	-6110K
114 (4 1/2")	540g	-6140K
121 (4 3/4")	590g	-6210K
127 (5")	650g	-6270K
133 (5 1/4")	710g	-6330K
140 (5 1/2")	770g	-6400K
152 (6")	900g	-6520K
168 (6 5/8")	1060g	-6680K
177 (6 31/32")	1100g	-6770K

**Carbide Tipped
Holesaws**

Kennedy® carbide tipped hole saws last up to 10 times longer than standard hole saws and resist wear and heat caused by friction much better than traditional holesaws, making them the best choice for cutting tough material such as tile, stainless steel.

Use standard arbors.




Holesaw Sizes	Use Arbor
14 to 30mm	K1 or K4
32 to 210mm	K2 or K10

Cutting Dia. (mm)	Order Code KEN-050	
18 (23/32")	-7180K	NA
19 (3/4")	-7190K	
20 (25/32")	-7200K	
22 (7/8")	-7220K	
25 (1")	-7250K	
26 (1 1/32")	-7260K	
28 (1 3/32")	-7280K	NA
29 (1 1/8")	-7290K	NA
30 (1 3/16")	-7300K	
31 (17/32")	-7310K	
32 (1 1/4")	-7320K	
35 (1 3/8")	-7350K	
36 (113/32")	-7360K	NA
40 (1 9/16")	-7400K	
41 (1 5/8")	-7410K	
44 (1 3/4")	-7440K	
45 (125/32")	-7450K	
50 (131/32")	-7500K	
51 (2")	-7510K	
55 (5 5/32")	-7550K	NA
60 (2 3/8")	-7600K	
70 (2 3/4")	-7700K	
80 (3 5/32")	-7800K	NA
85 (3 11/32")	-7850K	
95 (3 3/4")	-7950K	
100 (3 7/8")	-8000K	
102 (4")	-8002K	
105 (4 1/8")	-8005K	NA

KENNEDY Holesaw Arbors

Precision machined and threaded, guaranteeing a smooth secure fit to all popular brands of holesaws. Made from alloy steel. Suitable for use with all power tools.

For Saw Sizes up to 32mm




K1-SDS
Pilot supplied separately.



Product Number	For Saw Size	Order Code KEN-050
K4	14 - 30mm	-1750K
K1	14 - 30mm	-1600K
K1-SDS	14 - 32mm	-1550K

For Saw Sizes up to 152mm



K10-SDS
Pilot supplied separately.



Product Number	For Saw Size	Order Code KEN-050
K10	32 - 152mm	-1850K
K2	32 - 152mm	-1650K
K10-SDS	33 - 152mm	-1560K

Pilot Drills

HSS, ground flute. Not suitable for stainless steel.



Product Number	To Suit Arbors	Weight each	Order Code KEN-050
K14C	All except K4	20g	-1930K
K14D	K4 only	30g	-1960K

Ejector Spring

Manufactured from hardened spring steel. Presses over pilot to give quick release of core piece after cut.



Product Number	To Suit Saw Diameter	Weight each	Order Code KEN-050
K7	14 to 210mm	10g	-1970K

Variable Pitch Bi-Metal HSS Holesaw Kits

For producing high quality holes in wood, steel, brass, bronze, cast iron, aluminium and plastic. Featuring a very aggressive cutting action and M3 HSS cutting teeth to give a very smooth finish. Cuts up to 40% faster than constant pitch saws. The varying tooth pitch gives substantial reductions in noise by disrupting harmonics produced when sawing materials such as tubing, angle etc. Improved swarf clearance is also achieved requiring less effort to complete each cut. Tooth life is greatly extended, as is battery life when used with a cordless drill. Suitable for all uses: engineering, construction and maintenance. **4 to 6 teeth per inch. 28.5mm (1 1/8") cutting depth.**

Service Engineer's Kit

Comprises of 22, 29, 35, 44, 51 and 64mm variable pitch bi-metal high speed steel holesaws with hardened cutting edges, K7 spring, K4 and K10 arbors with pilot drills.

Supplied in a robust plastic carry case.

Electrician's Kit

Comprises of 16, 20, 25, 32, 40 and 51mm variable pitch bi-metal high speed steel holesaws with hardened cutting edges, K7 Spring, K1 and K10 arbors with pilot drills.

Supplied in a robust plastic carry case.



**9
PIECES**

Number of Pieces	Weight each	Order Code KEN-050
9	110g	-2400K



**9
PIECES**

Number of Pieces	Weight each	Order Code KEN-050
9	90g	-2300K

Tradesman's Compact Kits

High quality variable pitch bi-metal high speed steel holesaws with hardened cutting edges. Supplied in a handy storage tube. Ideal size to fit into power tool cases and tool boxes.

5 Piece: Comprises of 16, 20, 25 and 30mm holesaws with K1 arbor.

11 Piece: Comprises of 16, 19, 20, 22, 25, 30, 32, 38 and 51mm holesaws with K1 and K10 arbors.



**5
PIECES**



**11
PIECES**

Number of Pieces	Weight each	Order Code KEN-050
5	30g	-2100K
11	160g	-2500K

Constant Pitch Bi-Metal HSS Holesaw Kit

Featuring a constant pitch - First choice for cutting thin sheet materials up to 3mm thick. For producing high quality holes in wood, steel, brass, bronze, cast iron, aluminium and plastic. Featuring an hardened HSS cutting edge welded to a tough alloy steel body. Heavy duty shatter-resistant construction; virtually unbreakable. **6 teeth per inch. 38mm (1 1/2") cutting depth.**








Contents: 22, 29, 35, 44, 51 and 64mm constant pitch bi-metal high speed steel holesaws with hardened cutting edges. Complete with K4 and K10 arbors and K7 Spring.

Supplied in a robust plastic carry case.



**9
PIECES**

Number of Pieces	Weight each	Order Code KEN-050
9	1.20kg	-2000K




KENNEDY
QUALITY INDUSTRIAL TOOLING**Jigsaw
Blades Continued****Recommendations:****Plastics****Timber****Sandwich
Material****Plywood****Chipboards****Hard & Soft
Wood****Curved
Cutting****'T' Type Shank**

'T' Style or bayonet fitting as used by AEG, Atlas Copco, Bosch, Dewalt, Elu, Hitachi, Holz-Her, Kobe, Makita, Metabo and Osaki.



Capacity (mm)	Effective Tooth Length (mm)	Wood	Plastics	Pitch	Features/Recommendations	Equiv.	Order Code	Price/Pk	KEN-240
HCS - Medium Duty (Pack 5)									
Wavy Set Teeth									
15.0	8.0	1.2	48			T119A	-1190K		
Ground Set Teeth									
15.0	-	1.4	50			T101AOF	-1017K		
Tapered & Ground									
15.0	-	1.4	50			T101AO	-1015K		
Wavy Set Teeth									
20.0	20.0	2.5	50			T119BO	-1210K		
Wavy Set Teeth									
30.0	20.0	2.0	48			T119B	-1200K	NA	
Tapered & Ground									
50.0	30.0	2.5	64			T101BR	-1030K		
Tapered & Ground									
50.0	30.0	2.5	75			T101B	*-1020K		
Ground & Side Set									
50.0	-	4.0	75			T144DP	-1450K		
Side Set Teeth									
60.0	30.0	3.0	75			T111C	*-1110K		
Tapered & Ground									
60.0	30.0	4.0	75			T101D	-1040K		
Tapered & Ground									
60.0	50.0	4.0	75			T144D	*-1440K	NA	
Side Set Teeth									
60.0	50.0	4.0	75			T244D	-2440K		
Tapered & Ground									
70.0	50.0	4.0	85			T301D	-3010K		
Bi-Metal - High Performance (Pack 5)									
Side Set Teeth									
60.0	30.0	4.0	70			Combi	-3320K		
Cuts on Both Edges									
1.8	40								

*Best Sellers are also available in 'Contractor Packs' of 20 blades - See below



PACK OF
5

Cuts on
Down
Stroke

Jigsaw Blade Assortment

'T'-Shank - Fits 90% of all current jigsaw makes and models including Bosch, DeWalt, Hitachi, Kobe, Makita and Osaki. Supplied in a tough plastic storage case.

Contains one of each of the most popular wood cutting blades:
Clean cut wood blades: **T101AO, T101B, T101BR, T101AOF, T101BF, T101BRF.**

Speed cut wood blades:

T144D, T244D.

Speed cut hardwood blades:

T144DF.

Precision cut wood blades:

T144DP.

PACK OF
10



Order Code

KEN-240**-5620K**

Price/Pk

'Contractor Packs'

The most popular 'T' style blades bulk packed in 20's for economy. Supplied in telescopic 'pocket' cases that are ideal for the industrial user.


PACK OF
20



Capacity (mm)	Effective Tooth Length (mm)	Wood	Plastics	Pitch	Features	Equiv.	Order Code	Price/Pk	KEN-240
HCS - Medium Duty (Pack 20)									
50.0	30.0	2.5	75		Tapered & Ground	T101B	-1025K		
60.0	30.0	3.0	75		Side Set Teeth	T111C	-1115K		
60.0	50.0	4.0	75		Tapered & Ground	T144D	-1445K		

KENNEDY Jigsaw
Blades


Manufactured from high quality steels to meet the demands of most industrial and DIY applications. Supplied display carded. High teeth per inch (TPI) blades will be slower cutting and produce a better edge finish. Low teeth per inch blades will be faster cutting but produce coarse edges on the workpiece. Different materials will also give different edge finishes depending on the make up of the material and direction of cut in relation to the direction of the grain. When cutting certain metals, lubricant or grease may be required to reduce friction and dissipate heat. Various techniques can be employed to prevent splintering of cut edges on wood, especially laminated materials. These include the use of an anti-splinter guard. This is a plastic insert that locates in the jigsaw base plate, reducing the gap around the blade and the splinter area. Another technique is to score a guide line on the wood. This creates a pre-cut line that must then be followed accurately. The last technique is to place adhesive tape over the proposed cut line. This holds the material in place whilst the cut is being made.




Mild Steel




Stainless Steel




Non-Ferrous metal



Sheet Metal




Aluminium











































Plastics










Profiles



Sandwich Material

Capacity (mm)				Effective Tooth Length		Features/ Recommendations	Equiv.	Order Code KEN-240	Price/Pk
Steel	Wood	Alum.	Plastics	Pitch					
HSS - Heavy Duty (Pack 5)									
Tapered & Ground									
-	-	10.0	20.0	2.0	75	   	T101A	-1010K	
Wavy Set Teeth									
1.5-4.0	-	1.5-4.0	8.0	1.2	48	   	T118A	*-1160K	
Wavy Set Teeth									
2.0	-	2.0	-	0.7	50	   	T118G	-1180K	
Side Set Teeth									
3.0-6.0	-	3.0-15.0	30.0	3.0	75	   	T127D	*-1270K	
Wavy Set Teeth									
3.0-6.0	-	3.0-10.0	-	2.0	48	   	T118B	*-1170K	
Wavy Set Teeth									
3.0-6.0	-	3.0-10.0	-	2.0	100	   	T318B	-3190K	
Side Set Teeth									
3.0-6.0	-	3.0-15.0	30.0	3.0	75	   	T227D	-2270K	
Wavy Set Teeth									
10.0	-	10.0	-	2.6	75	   	T123X	-1240K	
Wavy Set Teeth									
10.0	10.0	10.0	-	5.0	110	   	T1345X	-3450K	
Bi-Metal - High Performance (Pack 5)									
Wavy Set Teeth									
1.5-4.0	-	1.5-4.0	8.0	1.2	50	   	T118AF	-1150K	

*Best Sellers are also available in 'Contractor Packs' of 20 blades - See below



PACK OF
5

Jigsaw Blades



Manufactured from high quality steels to meet the demands of most industrial and DIY applications. The quality and speed of cut is dependent on the pitch and the material being cut. Lubricant or grease may be required to reduce friction and dissipate heat when cutting some materials.

*Except Tungsten Carbide

Capacity (mm)				Effective Tooth Length (mm)		Features	Equiv.	Weight per Pk	Order Code	Price/Pk
Steel	Wood	Alum.	Plastics	Pitch						
Two Hole Type Suitable for old style Makita. HCS - Medium Duty (Pack 5)										
-	30.0	-	20.0	2.0	60	Wavy set teeth	No.2	29g	-5020K	
-	40.0	-	30.0	3.0	60	Side set teeth	No.3	29g	-5030K	
'U' Type Suitable for Black & Decker and Hitachi DIY. HSS - Medium Duty (Pack 5)										
-	20.0	-	20.0	2.5	60	For cutting curves, Wavy set	A5033	19g	-4280K	

PACK OF
50

Prices per pack



'Contractor Packs'

The most popular 'T' style blades bulk packed in 20s for economy. Supplied in telescopic 'pocket' cases that are ideal for the industrial user.

PACK OF
20

Capacity (mm)				Tooth Pitch	Effective Length (mm)	Features	Equiv.	Order Code KEN-240	Price/Pk
Steel	Wood	Alum.	Plastics						
HSS - Heavy Duty (Pack 20)									
1.5-4.0	-	1.5-4.0	8.0	1.2	48	Wavy Set Teeth	T118A	-1165K	
3.0-6.0	-	3.0-10.0	-	2.0	48	Wavy Set Teeth	T118B	-1175K	
3.0-6.0	-	3.0-15.0	30.0	3.0	75	Side Set Teeth	T127D	-1275K	



50 Years of Keeping Industry Working
© 2022

KENNEDY QUALITY INDUSTRIAL TOOLING

Sheepskin Bonnets

Genuine 100% natural long lasting sheepskin tie-on bonnets for professional use. For polishing metal, glass fibre, wood and painted surfaces. With tie cord. Maximum 2,500rpm - best results are obtained with a tool speed of 1,500 - 2,000rpm. Not suitable for wet use. Support pads supplied separately, see below.

Merino Sheepskin Bonnets

With a unique double skin making this the longest lasting bonnet we know. For professional use. 32mm pile.



Diameter (mm)	Weight each	Order Code KEN-280
125	50g	-5000K
150	55g	-5020K
180	60g	-3900K

Tie Cord Bonnet Support Pads

High quality 23mm foam pads with rigid back plates. For use with all tie cord bonnets. Bonnets supplied separately. Max 2500rpm. *125mm and 150mm pads are dual purpose - also for use with velcro bonnets or foams.



Bonnet Dia. (mm)	Thread Size	Order Code KEN-280
125*	M14 x 2	-3230K
	5/8" UNC	-3210K
150*	M14 x 2	-4030K

Double Sided Buffing Pads

Twisted 100% wool pads - for fast results on large areas. Pad can be flipped over to use both sides, thus doubling the life of the pad.



Diameter (mm)	Order Code KEN-280
220	-5120K

Cupped Super Buffing Pad

Twisted 100% wool pads - for fast results on large areas. Hook-n-Loop backed.



Diameter (mm)	Order Code KEN-280
220	-5200K

KOBE Circular Saw Blades

HSS TCT circular saw blade for precision ground cutting angles on softwood, hardwood, MDF, plywood etc. Excellent blade sharpness and faster cutting make it ideal for general purpose use on both corded and cordless circular saws.

Coarse Pitch

Ripping blades, with fewer teeth per inch (less TPI). Suitable for cutting long grain solid wood.



Size Dia. x Thickness x Bore	Blade Type	Order Code KBE-280
160 x 2.4 x 30mm	12T - Coarse	-5695K
190 x 2.4 x 30mm	12T - Coarse	-5698K
235 x 2.8 x 30mm	24T - Coarse	-5702K

Medium Pitch

General purpose blades, with medium teeth per inch. For cutting both long grain and cross grain solid wood. These blades produce a good surface finish that requires less finishing.



Size Dia. x Thickness x Bore	Blade Type	Order Code KBE-280
150 x 2.4 x 16mm	24T - Medium	-5711K
150 x 2.4 x 20mm	24T - Medium	-5712K
160 x 2.4 x 16mm	24T - Medium	-5713K
160 x 2.4 x 20mm	24T - Medium	-5714K
180 x 2.4 x 20mm	24T - Medium	-5715K
184 x 2.4 x 16mm	24T - Medium	-5716K
190 x 2.4 x 16mm	24T - Medium	-5717K
190 x 2.4 x 30mm	24T - Medium	-5718K
200 x 2.4 x 30mm	30T - Medium	-5719K
210 x 2.4 x 30mm	30T - Medium	-5720K
230 x 2.8 x 30mm	34T - Medium	-5721K
235 x 2.8 x 30mm	34T - Medium	-5722K
250 x 2.8 x 30mm	40T - Medium	-5723K

Fine Pitch

Perfect for cross cutting, with high teeth per inch. Suitable for cross grain cutting solid wood, producing a smooth surface that requires less finishing.



Size Dia. x Thickness x Bore	Blade Type	Order Code KBE-280
184 x 2.4 x 16mm	40T - Fine	-5736K
190 x 2.4 x 16mm	40T - Fine	-5737K
190 x 2.4 x 30mm	40T - Fine	-5738K
216 x 2.4 x 30mm	64T - Fine	-5740K
235 x 2.8 x 30mm	48T - Fine	-5742K
250 x 2.8 x 30mm	60T - Fine	-5743K



SDS Max Chisels

High grade forged-steel with shot-blast finish. Suitable for all tools with SDS Max system.

Flat Breaker Chisel - 500 x 25mm



Type	Size (mm)	Weight each	Order Code KEN-289
Flat Breaker Chisel	500 x 25	1.0kg	-2720K
Point	500 x 18 x 5	1.0kg	-2760K
Wide Chisel	400 x 50	0.9kg	-2780K
Spade Chisel	300 x 75	0.7kg	-2800K
Chasing Gouge	300 x 25	0.7kg	-2820K

Moil Point - 500mm




Wide Chisel - 400 x 50mm



Spade Chisel - 300 x 75mm



Chasing Gouge - 300 x 25mm



Air Tool Chisels with 0.401" Shank

For all brands of portable air chisels including CP, Desoutter, Kobe, Toku and YK.

Flat Chisel - 178 x 15mm.



Smoothing Hammer - 75 x 25mm.



Rivet Cutter - 145 x 25mm.



Panel Cutter - 150mm.



Taper Punch - 180 x 3mm.



Straight Punch - 180 x 12mm.



Bushing Splitter - 180 x 12mm.



Spot Weld - 180 x 12mm.



Type	Weight each	Order Code KEN-289	NA
Flat Chisel	150g	-1070K	
Smoothing	100g	-2300K	
Rivet Cutter	130g	-2350K	
Panel Cutter	150g	-2400K	
Taper Punch	150g	-2450K	
Straight Punch	150g	-2500K	
Bushing Splitter	170g	-2550K	
Spot Weld	160g	-2600K	

Power Tool Chisels

Hilti Style Chisels

For Hilti: TE54, TE72, TE92, TE504.

18mm Round Shank with Hilti Direct Fit Retainer.

Flat Chisel - 355 x 25mm.



Moil Point - 355 x 3mm.



Type	Weight each	Order Code KEN-289
Flat Chisel	700g	-1270K
Moil Point	700g	-1930K

Kango Style Chisels

For Kango: 501, 627, 628, 637, 638, 430 - Type 750 shanks.

19mm Hex Shank with Single Flat & Round Tang

Flat Chisel - 380 x 25mm.



Wide Chisel - 305 x 50mm/305 x 75mm.



Moil Point - 380 x 3mm.



Type	Weight each	Order Code KEN-289
Flat Chisel	800g	-1330K
Wide Chisel	700g	-1800K
Moil Point	730g	-1830K
	800g	-2000K

For Kango: 900K, 928, 950K, 978, 1400. Hitachi: DH38YD, DH50SA, H55SA. Makita: HM1200K, HR3850K.

21mm Hex Shank with Single Flat & Round Tang

Flat Chisel - 380 x 25mm.



Wide Chisel - 305 x 50mm/305 x 75mm.



Moil Point - 380 x 3mm.



Type	Weight each	Order Code KEN-289
Flat Chisel	1000g	-1350K
Wide Chisel	900g	-1640K
Moil Point	930g	-1670K
	1000g	-2030K

Makita Style Chisels

For Makita: HM0810, HR3500, HR3520, 8035NB.

17mm Hex Shank with Round Tang & Round Retainer Recess

Wide Chisel - 280 x 50mm.



Moil Point - 280 x 3mm.



Type	Weight each	Order Code KEN-289
Wide Chisel	530g	-1550K
Moil Point	430g	-1900K

Bosch Style Chisels

For Bosch: GBH7/45, UBH6/35, UBH12/50, USH6, 11202, 11203, 11204, 11206, 11208, 11209. AEG

(Atlas Copco): PHD26, PH38, PHD38, PH240D, PH350D. Black & Decker: HD2032, HD2038, P8032, P8038.

19mm Hex Shank with Single Flat & Round Tang

Flat Chisel - 380 x 25mm.



Wide Chisel - 305 x 50mm/305 x 75mm.



Moil Point - 380 x 3mm.



Type	Weight each	Order Code KEN-289
Flat Chisel	880g	-1300K
Wide Chisel	830g	-1610K
Moil Point	880g	-1970K

For Bosch: USH10, 11305, 12312.

19mm Hex Shank with Single Flat

Flat Chisel - 380 x 25mm.



Wide Chisel - 305 x 50mm/305 x 75mm.



Moil Point - 380 x 6mm.



Type	Weight each	Order Code KEN-289
Flat Chisel	900g	-1400K
Wide Chisel	820g	-1700K
Moil Point	880g	-1730K
	900g	-2090K

For Bosch: USH27, USH28, 11304, 11308, 12314

29mm Hex Shank with Single Flat

Flat Chisel - 380 x 31mm/455 x 25mm.



Moil Point - 380 x 6mm/455 x 6mm.



Type	Weight each	Order Code KEN-289
Flat Chisel	2.0kg	-1430K
	2.4kg	-1480K
Moil Point	2.0kg	-2060K
	2.4kg	-2120K



Push-Fit Pneumatic Fittings

Quick and simple tube insertion. Compact lightweight design with a well proven tube retaining system. Tapered threads have a re-usable thread seal and parallel threads have a rubber washer. Main body manufactured from nickel plated brass, acetal resin, PBT with a stainless steel retaining ring, nitrile tube seal and acetal resin tube release collar.

Pressure range: -0.9bar min to +10bar max. **Temp range:** -20°C min to +70°C max. **Tube suitability:** Nylon, polyurethane.

Thread Forms:
G = BSPP - British Standard Pipe, **Parallel**
R = BSPT - British Standard Pipe, **Taper**
M = ISO Metric [mm = Tube diameter]

Straight Connector




Model Number	Size (mm)	Order Code KEN-291
KC4	4	-2200K
KC6	6	-2210K
KC8	8	-2220K

Connector to Female Parallel



Model Number	Size (mm)	Order Code KEN-291
KC4-1FP	4 - G $\frac{1}{8}$	-2260K
KC6-1FP	6 - G $\frac{1}{8}$	-2270K
KC6-2FP	6 - G $\frac{1}{4}$	-2280K
KC8-2FP	8 - G $\frac{1}{4}$	-2290K
KC8-3FP	8 - G $\frac{3}{8}$	-2300K
KC10-2FP	10 - G $\frac{1}{4}$	-2310K

Connector to Male Parallel



Model Number	Size (mm)	Order Code KEN-291
KC4-1MP	4 - G $\frac{1}{8}$	-2350K
KC4-2MP	4 - G $\frac{1}{4}$	-2360K
KC4-5MP	4 - M5	-2370K
KC6-1MP	6 - G $\frac{1}{8}$	-2380K
KC6-2MP	6 - G $\frac{1}{4}$	-2390K
KC6-5MP	6 - M5	-2400K
KC8-1MP	8 - G $\frac{1}{8}$	-2410K
KC8-2MP	8 - G $\frac{1}{4}$	-2420K
KC8-3MP	8 - G $\frac{3}{8}$	-2430K
KC10-2MP	10 - G $\frac{1}{4}$	-2440K

Connector to Male Taper



Model Number	Size (mm)	Order Code KEN-291
KC4-1MT	4 - G $\frac{1}{8}$	-2500K
KC4-2MT	4 - G $\frac{1}{4}$	-2510K
KC6-3MT	6 - G $\frac{3}{8}$	-2540K
KC8-1MT	8 - G $\frac{1}{8}$	-2550K
KC8-2MT	8 - G $\frac{1}{4}$	-2560K
KC8-3MT	8 - G $\frac{3}{8}$	-2570K
KC8-4MT	8 - G $\frac{1}{2}$	-2580K
KC10-1MT	10 - G $\frac{1}{8}$	-2600K
KC10-4MT	10 - G $\frac{1}{2}$	-2630K
KC12-3MT	12 - G $\frac{3}{8}$	-2650K
KC12-4MT	12 - G $\frac{1}{2}$	-2660K

Elbow Connector



Model Number	Size (mm)	Order Code KEN-291
KEC4	4	-2700K
KEC6	6	-2710K
KEC8	8	-2720K
KEC10	10	-2730K
KEC12	12	-2740K

Elbow Connector to Stem



Model Number	Size (mm)	Order Code KEN-291
KEC8S-8	8 - 8	-2820K
KEC12S-12	12 - 12	-2840K

Elbow Connector to Male Parallel



Model Number	Size (mm)	Order Code KEN-291
KEC4-1MP	4 - G $\frac{1}{8}$	-2900K
KEC4-2MP	4 - G $\frac{1}{4}$	-2910K
KEC4-5MP	4 - M5	-2920K
KEC6-1MP	6 - G $\frac{1}{8}$	-2930K
KEC6-2MP	6 - G $\frac{1}{4}$	-2940K
KEC6-5MP	6 - M5	-2950K
KEC8-1MP	8 - G $\frac{1}{8}$	-2960K
KEC8-2MP	8 - G $\frac{1}{4}$	-2970K
KEC10-2MP	10 - G $\frac{1}{4}$	-2980K

Elbow Connector to Male Taper



Model Number	Size (mm)	Order Code KEN-291
KEC4-1MT	4 - G $\frac{1}{8}$	-3100K
KEC4-2MT	4 - G $\frac{1}{4}$	-3110K
KEC6-1MT	6 - G $\frac{1}{8}$	-3120K
KEC6-2MT	6 - G $\frac{1}{4}$	-3130K
KEC6-3MT	6 - G $\frac{3}{8}$	-3140K
KEC8-1MT	8 - G $\frac{1}{8}$	-3150K
KEC8-3MT	8 - G $\frac{3}{8}$	-3170K
KEC8-4MT	8 - G $\frac{1}{2}$	-3180K
KEC10-1MT	10 - G $\frac{1}{8}$	-3190K
KEC10-2MT	10 - G $\frac{1}{4}$	-3200K
KEC10-3MT	10 - G $\frac{3}{8}$	-3210K
KEC10-4MT	10 - G $\frac{1}{2}$	-3220K
KEC12-2MT	12 - G $\frac{1}{4}$	-3230K
KEC12-3MT	12 - G $\frac{3}{8}$	-3240K

'Y' Piece



Model Number	Size (mm)	Order Code KEN-291
KY4	4	-6800K
KY6	6	-6810K
KY8	8	-6820K
KY10	10	-6830K
KY12	12	-6840K

'Y' Reducers



Model Number	Size (mm)	Order Code KEN-291
KYR6-4	6 - 4	-7500K
KYR8-6	8 - 6	-7510K
KYR10-8	10 - 8	-7520K
KYR12-10	12 - 10	-7530K

In-line Reducer



Model Number	Size (mm)	Order Code KEN-291
KR10-8	10 - 8	-5420K

Elbow Reducer to Stem




Model Number	Size (mm)	Order Code KEN-291
KER10S-8	10 - 8	-3640K

Reducing Triple Branch Manifolds



Model Number	Size (mm)	Order Code KEN-291
KMT6-4	6 - 4	-5000K
KMT8-6	8 - 6	-5010K

In-line Flow Restrictor



Model Number	Size (mm)	Order Code KEN-291
KFR-4	4	-3800K
KFR-6	6	-3810K
KFR-8	8	-3830K

Out-flow Restrictor to Male Taper



Model Number	Size (mm)	Order Code KEN-291
KFRE4-1MT	4 - G $\frac{1}{8}$	-4000K
KFRE6-1MT	6 - G $\frac{1}{8}$	-4020K
KFRE6-2MT	6 - G $\frac{1}{4}$	-4030K
KFRE6-3MT	6 - G $\frac{3}{8}$	-4040K
KFRE8-1MT	8 - G $\frac{1}{8}$	-4050K
KFRE8-2MT	8 - G $\frac{1}{4}$	-4060K
KFRE8-3MT	8 - G $\frac{3}{8}$	-4070K
KFRE10-2MT	10 - G $\frac{1}{4}$	-4080K

In-flow Restrictor



MT = Male Taper Thread

Model Number	Size (mm)	Order Code KEN-291
KFRT6-2MT	6 - G $\frac{1}{4}$	-4530K
KFRT8-1MT	8 - G $\frac{1}{8}$	-4540K
KFRT8-2MT	8 - G $\frac{1}{4}$	-4550K
KFRT10-2MT	10 - G $\frac{1}{4}$	-4570K

KENNEDY
 QUALITY INDUSTRIAL TOOLING

Thread Forms:
G = BSPP - British Standard Pipe, **Parallel**
R = BSPT - British Standard Pipe, **Taper**
M = ISO Metric [mm = Tube diameter]

Push-Fit Pneumatic Fittings
Equal Tees


Model Number	Size (mm)	Order Code KEN-291
KT4	4	-5700K
KT6	6	-5710K
KT8	8	-5720K
KT10	10	-5730K
KT12	12	-5740K

Branch Tee to Male Taper


Model Number	Size (mm)	Order Code KEN-291
KTB4-1MT	4 - G $\frac{1}{8}$	-6500K
KTB6-1MT	6 - G $\frac{1}{8}$	-6520K
KTB6-2MT	6 - G $\frac{1}{4}$	-6530K
KTB6-3MT	6 - G $\frac{3}{8}$	-6540K
KTB8-1MT	8 - G $\frac{1}{8}$	-6550K
KTB8-2MT	8 - G $\frac{1}{4}$	-6560K
KTB8-3MT	8 - G $\frac{3}{8}$	-6570K
KTB10-1MT	10 - G $\frac{1}{8}$	-6590K
KTB10-2MT	10 - G $\frac{1}{4}$	-6600K
KTB10-4MT	10 - G $\frac{1}{2}$	-6620K
KTB12-2MT	12 - G $\frac{1}{4}$	-6630K
KTB12-4MT	12 - G $\frac{1}{2}$	-6650K

Bulkhead Adaptors


Model Number	Size (mm)	Order Code KEN-291
KBH4	4 - 4	-2010K
KBH8	8 - 8	-2030K

Bulkhead to Female Parallel


Model Number	Size (mm)	Order Code KEN-291
KBH6-2FP	6 - G $\frac{1}{4}$	-2110K
KBH8-1FP	8 - G $\frac{1}{8}$	-2120K
KBH8-2FP	8 - G $\frac{1}{4}$	-2130K
KBH10-2FP	10 - G $\frac{1}{4}$	-2150K
KBH12-3FP	12 - G $\frac{3}{8}$	-2180K

Stem Reducers


Model Number	Size (mm)	Order Code KEN-291
KR6S-4	6 - 4	-5500K
KR8S-6	8 - 6	-5520K
KR10S-6	10 - 6	-5530K
KR10S-8	10 - 8	-5540K
KR12S-8	12 - 8	-5560K
KR12S-10	12 - 10	-5570K

Push-Fit Pneumatic Fittings
Push-In 54 Piece Spares Kit
Contents:

- Tee Connectors**
(2x 4mm, 6mm and 8mm).
- Elbow Connectors**
(2x 4mm, 6mm and 8mm).
- Straight Connectors**
2x 4mm, 6mm and 8mm).
- Blanking Plugs**
(6x 4mm, 6mm and 8mm).
- G $\frac{1}{8}$ Tapered Stud Connectors**
(3x 4mm, 6mm and 8mm).
- G $\frac{1}{4}$ Tapered Stud Connectors**
(3x 4mm, 6mm and 8mm).

Sizes	Order Code KEN-291
4, 6 & 8mm	-9100K

Blanking Plugs


Model Number	Size (mm)	Order Code KEN-291
EPP4	4	-5200K
EPP8	8	-5220K
EPP10	10	-5230K

Non-Return Valve - Female to Female
Pressure range: +2 to +8bar.

Temperature range: -25 to +90°C.


Model Number	Size (mm)	Order Code KEN-259
VNR1FF	G $\frac{1}{8}$ - G $\frac{1}{8}$	-7400K
VNR3FF	G $\frac{3}{8}$ - G $\frac{3}{8}$	-7420K
VNR4FF	G $\frac{1}{2}$ - G $\frac{1}{2}$	-7430K

Exhausting Slide Valve - Female to Female
Pressure range: 0 to +10bar.

Temperature range: -18 to +70°C.


Model Number	Size (mm)	Order Code KEN-259
VAS1FF	G $\frac{1}{8}$ - G $\frac{1}{8}$	-7250K
VAS4FF	G $\frac{1}{2}$ - G $\frac{1}{2}$	-7280K

Conical Silencer
Sintered (with Hex) Type 1


Model Number	Size Male	Order Code KEN-259
S1-1	G $\frac{1}{8}$	-6800K
S1-2	G $\frac{1}{4}$	-6810K
S1-3	G $\frac{3}{8}$	-6820K
S1-4	G $\frac{1}{2}$	-6830K
S1-6	G $\frac{3}{4}$	-6840K

Conical Silencer
Sintered (with Hex) Type 2


Model Number	Size Male	Order Code KEN-259
S2-1	G $\frac{1}{8}$	-6870K
S2-2	G $\frac{1}{4}$	-6880K
S2-3	G $\frac{3}{8}$	-6890K
S2-4	G $\frac{1}{2}$	-6900K


Flow Regulators
Pressure range: +1 to +10 bar.

Temperature range: 0 to +80°C.


Model Number	Size (mm)	Order Code KEN-259
--------------	-----------	--------------------

Bi-Directional

FR1-1	G $\frac{1}{8}$	-6400K
FR1-2	G $\frac{1}{4}$	-6410K
FR1-3	G $\frac{3}{8}$	-6420K

Quick Exhaust Valve - Female to Female
Pressure range: +0.3 to +10bar.

Temperature range: -18 to +70°C.


Model Number	Size (mm)	Order Code KEN-259
--------------	-----------	--------------------

VQE1FF	G $\frac{1}{8}$ - G $\frac{1}{8}$	-7500K
VQE2FF	G $\frac{1}{4}$ - G $\frac{1}{4}$	-7510K
VQE3FF	G $\frac{3}{8}$ - G $\frac{3}{8}$	-7520K
VQE4FF	G $\frac{1}{2}$ - G $\frac{1}{2}$	-7530K

Flat Head Silencer Sintered (with Hex) Type 3


Model Number	Size Male	Order Code KEN-259
--------------	-----------	--------------------

S3-1	G $\frac{1}{8}$	-6940K
S3-2	G $\frac{1}{4}$	-6950K
S3-3	G $\frac{3}{8}$	-6960K
S3-4	G $\frac{1}{2}$	-6970K
S3-6	G $\frac{3}{4}$	-6980K

Dome Head Silencer Sintered (with Hex) Type 4


Model Number	Size Male	Order Code KEN-259
--------------	-----------	--------------------

S4-1	G $\frac{1}{8}$	-7000K
S4-2	G $\frac{1}{4}$	-7010K

Instant Air Couplings

Bayonet type range, positive seal, quick release couplings.
Nominal Bore: 5.6mm
Flow rate @ 6 bar - 54cfm @ 100psi
Maximum working pressure: 17 bar/250psi
Adaptor series: InstantAir



Female Thread

Product Number	Thread Size	Order Code PCL-259
Male Thread		
AC51CM	G $\frac{1}{4}$	-1978B
AC51EM	G $\frac{3}{8}$	-1978D
AC51JM	R $\frac{1}{2}$	-1978F
Female Thread		
AC51EF	Rp $\frac{3}{8}$	-1978J
Hose Tailpiece		
AC51R	6.35mm/ $\frac{1}{4}$	-1978N
AC51S	7.9mm/ $\frac{3}{16}$	-1978Q
AC51T	9.55mm/ $\frac{3}{8}$	-1978S

InstantAir Adaptors

Made in the UK. Bayonet style and are zinc plated steel.
Nominal Bore: 5.6mm
Flow rate @ 6 bar - 54 cfm @ 100psi
Maximum working pressure: 17 bar/250psi
Coupling series: InstantAir



Male Thread

Product Number	Thread Size	Order Code PCL-259
Hose Tailpiece		
AA5110	6.35mm/ $\frac{1}{4}$	-1006P
AA5111	7.9mm/ $\frac{3}{16}$	-1006Q
AA5112	9.55mm/ $\frac{3}{8}$	-1006R

XF Couplings

Offers excellent flow character providing the workshop with increase airflow when required.
Nominal Bore: 7.4mm
Flow rate @ 6 bar - 43cfm @ 100psi 2,200 l/min
Adaptor series: XF Series
Interchangeable:
 Cein 320, Legris 25/26, Norgren 234/238, Rectus 25/26, Schrader Intercheck 35



Product Number	Thread Size	Order Code PCL-259
Hose Tailpiece		
AC7106	6mm	-1982N
AC7108	8mm	-1982X
AC7109	9mm	-1982Z
AC7110	10mm	-1982P
AC7113	13mm	-1982L

XF Coupling and Adaptor Air Tool Hose

Rubber PVC Alloy (PTE) compound that is available in popular cut lengths.
Burst pressure: 63 bar
Working pressure @20°C: 300 lbf/in² (21 bar)



Product Number	Length (Meters)	Inside Dia. (mm)	Order Code PCL-259
HA2140	5	10	-3318K
HA2141	10	10	-3318L
HA2142	15	10	-3318M
HA2143	20	10	-3318N

100 Series Coupling and Adaptor Air Tool Hose

Rubber PVC Alloy (PTE) compound. Complete with coupling and adaptor ends to suit 100 series.
Burst pressure: 63 bar
Working pressure @20°C: 300 lbf/in² (21 bar)



Product Number	Length (Meters)	Inside Dia. (mm)	Order Code PCL-259
HA2144	10	13	-3312K
HA2150	15	13	-3312L
HA2128	20	13	-3312M
HA2152	30	13	-3312N

High Visibility Air Hoses with Fitting

Reinforced air hose manufactured in high visibility yellow material.
Burst pressure: 63 bar
Working pressure @20°C: 300 lbf/in² (21 bar)
Fittings: Rp $\frac{1}{2}$ swivel ends



Product Number	Length (Meters)	Inside Dia. (mm)	Order Code PCL-259
HA2044HV	10	10	-3331M
HA2046HV	20	10	-3331N

Air Line Whip Hoses

The vibrations caused in the use of air tools make a coupling connection subject to Health & Safety Regulations.
 The international Standard (ISO 6150:1998) recommends a minimum of 300mm of flexible hose to be used between a vibrating tool and quick release coupling.
Burst pressure: 63 bar
Working pressure @ 20°C: 300 lbf/in² (21 bar).
 Comprises of adaptor and male thread fitting

Product Number	Length (Meters)	Inside Dia. (mm)	Adaptor Series	Thread Size	Order Code PCL-259
HA2108	0.6	7	Standard	R $\frac{1}{4}$	-3300F
HA2124N	0.6	7	Standard	NPT $\frac{1}{4}$	-3300G
HA2149	0.6	10	Standard	R $\frac{1}{4}$	-3300H
HA2109	0.6	10	Standard	R $\frac{3}{8}$	-3300J
HA2155	0.4	8	Standard	R $\frac{3}{8}$	-3300K
HA2116	0.6	13	100 Series	R $\frac{1}{2}$	-3300L
HA2132	0.6	10	XF Series	R $\frac{1}{4}$	-3300M

Standard & Vertex Coupling Air Tool Hose

Rubber PVC Alloy (PTE) compound.
Burst pressure: 63 bar
Working pressure@20°C: 300lbf/in² (21bar)



Product Number	Length (Meters)	Inside Dia. (mm)	Order Code PCL-259
HA2133	5	8	-3305K
HA2134	10	8	-3305L
HA2139	15	8	-3305M
HA2129	20	8	-3305N
HA2135	5	10	-3310K
HA2125	10	10	-3310L
HA2137	15	10	-3310M
HA2138	20	10	-3310N

Air Hose with Fittings

Rubber PVC Alloy (PTE). Coupling and adaptor ends to suit Standard & Vertex series.
Burst pressure: 63 bar
Working pressure@20°C: 300lbf/in² (21bar)




Product Number	Length (Meters)	Order Code PCL-259
$\frac{5}{16}$ Hose, 8mm/$\frac{5}{16}$" inside diameter Rp$\frac{1}{4}$ swivel ends		
HA2012	5	-3321K
HA2017	10	-3321L
HA2021	15	-3321M
HA2002	20	-3321N
$\frac{3}{8}$ Hose, 10mm/$\frac{3}{8}$" inside diameter Rp$\frac{1}{4}$ swivel ends		
HA2043	5	-3325K
HA2044	10	-3325L
HA2045	15	-3325M
HA2046	20	-3325N
$\frac{1}{2}$ Hose, 13mm/$\frac{1}{2}$" inside diameter Rp$\frac{1}{2}$ swivel ends		
HA2019	10	-3328L
HA2023	15	-3328M
HA2004	20	-3328N



PCL PF Couplings

Designed to offer a competitive alternative to the genuine Schrader range
Nominal Bore: 5mm
Flow rate @ 6 bar - 2,200 l/min
Maximum working pressure: 35 bar/508psi
Adaptors: PF Series



Product Number	Thread Size	Order Code PCL-259
Male Thread		
AC77CM	R $\frac{1}{4}$	-1982S
AC77EM	R $\frac{3}{8}$	-1982R
AC77JM	R $\frac{1}{2}$	-1982V
Female Thread		
AC77CF	Rp $\frac{1}{4}$	-1982Q
AC77EF	Rp $\frac{3}{8}$	-1982Y
AC77JF	Rp $\frac{1}{2}$	-1982W
Hose Tailpiece		
AC7706	6mm	-1982B
AC7708	8mm	-1982C
AC7710	10mm	-1982H
AC7713	13mm	-1982J

KF Couplings

Excellent flow characteristics for industrial applications.
Nominal Bore: 7.6mm
Flow rate @ 6 bar - 2,100 l/min
Maximum working pressure: 35 bar/508 psi
Adaptors: KF Series
Interchangeable: Cejn 314/315, Nitto Kohki 200, Rectus 13



Product Number	Thread Size	Order Code PCL-259
Male Thread		
AC78CM	R $\frac{1}{4}$	-1520A
AC78EM	R $\frac{3}{8}$	-1520B
AC78JM	R $\frac{1}{2}$	-1520C
Female Thread		
AC78CF	Rp $\frac{1}{4}$	-1520D
AC78EF	Rp $\frac{3}{8}$	-1520E
AC78JF	Rp $\frac{1}{2}$	-1520F
Hose Tailpiece		
AC7806	6mm	-1520G
AC7808	8mm	-1520H
AC7810	10mm	-1520J
AC7813	13mm	-1520K

ISO B12 Adaptors

For use with the ISO B12 Series coupling range.
Nominal Bore: 5.5mm
Flow rate @ 6 bar - 117 cfm @ 100 psi
Maximum working pressure: 35 bar/508psi
Couplings: ISO B12 Series



Product Number	Thread Size	Order Code PCL-259
Male Thread		
AA7502	R $\frac{1}{4}$	-1502A
AA7503	R $\frac{3}{8}$	-1502B
AA7504	R $\frac{1}{2}$	-1502C
Female Thread		
AA7506	Rp $\frac{1}{4}$	-1502D
AA7507	Rp $\frac{3}{8}$	-1502E
Hose Tailpiece		
AA7510	6mm	-1502F
AA7511	8mm	-1502G
AA7512	10mm	-1502H
AA7513	13mm	-1502J

ISO B12 Couplings

Excellent flow characteristics for industrial applications.
Nominal Bore: 5.5mm
Flow rate @ 6 bar - 1,100 l/min
Maximum working pressure: 35 bar/508psi
Adaptors: ISO B12 Series
Interchangeable: Cejn 310, Hanson 3000, Legris 24, Rectus 23/24



Product Number	Thread Size	Order Code PCL-259
Male Thread		
AC75CM	R $\frac{1}{4}$	-1530A
AC75EM	R $\frac{3}{8}$	-1530B
AC75JM	R $\frac{1}{2}$	-1530C
Female Thread		
AC75CF	Rp $\frac{1}{4}$	-1530D
AC75EF	Rp $\frac{3}{8}$	-1530E
AC75JF	Rp $\frac{1}{2}$	-1530F
Hose Tailpiece		
AC7506	6mm	-1530G
AC7508	8mm	-1530H
AC7510	10mm	-1530J
AC7513	13mm	-1530K

KF Adaptors

For use with the KF Series coupling range.
Nominal Bore: 7.6mm
Flow rate @ 6 bar - 117 cfm @ 100psi
Maximum working pressure: 35 bar/508psi
Couplings: KF Series



Product Number	Thread Size	Order Code PCL-259
Male Thread		
AA7802	R $\frac{1}{4}$	-1510A
AA7803	R $\frac{3}{8}$	-1510B
AA7804	R $\frac{1}{2}$	-1510C
Female Thread		
AA7806	Rp $\frac{1}{4}$	-1510D
AA7807	Rp $\frac{3}{8}$	-1510E
AA7808	Rp $\frac{1}{2}$	-1510F
Hose Tailpiece		
AA7810	6mm	-1510G
AA7811	8mm	-1510H
AA7812	10mm	-1510J
AA7813	13mm	-1510K

Mini Speed Regulator

For use in conjunction with airline couplings.
 Case hardened with zinc finish. Male threaded tailpieces for connecting a hose to a female fitting.



Product Number	Thread Size	Order Code PCL-259
APA91	R $\frac{1}{4}$	-2028H

Did you know...

We supply a full range of Air Tools

Contact us for details





Wire Brushes 30SWG

Industrial rotary wire wheels and brushes are available as a comprehensive range including circular brushes, shaft mounted arbor style and de-carbonising brushes for use with power tools, machine tools and flexible drives. Suitable for removal of rust, paint and dirt from heavily covered parts.



Diameter x Width x Bore (mm)	Max. RPM	Order Code YRK-295
80 x 15 x 20	10,000	-0030K
80 x 22 x 20	10,000	-0060K
100 x 20 x 30	6,000	-0140K
100 x 28 x 30	6,000	-0170K
125 x 22 x 30	6,000	-0360K
125 x 30 x 30	6,000	-0390K
150 x 11 x 51	6,000	-0430K
150 x 21 x 51	6,000	-0450K
150 x 29 x 51	6,000	-0480K
200 x 21 x 80	4,500	-0650K
200 x 29 x 80	4,500	-0680K
250 x 29 x 100	3,600	-0880K

Shaft Mounted Cup Brushes

For all round use, ideal for work on larger surfaces removing burrs, rust and paint. 30 Standard Wire Gauge.



Diameter x Width (mm)	Max. RPM	Order Code YRK-295
40 x 10	12,000	-3120K
45 x 10	11,000	-3220K
50 x 10	11,000	-3320K
50 x 50	12,000	-3380K
60 x 15	12,000	-3450K
60 x 60	12,000	-3490K
70 x 15	4,500	-3650K
40 x 10	11,000	-3820K
50 x 10	11,000	-3840K
70 x 70	11,000	-3860K
40 x 10	12,000	-3900K
50 x 10	12,000	-3920K
70 x 70	12,000	-3940K

Twisted Knot Brushes

A more aggressive circular brush. The twist knot construction allows a higher surface speed. 35 SWG



Diameter x Width x Bore (mm)	Max. RPM	Order Code YRK-295
100 x 11 x 22	12,500	-1110K
115 x 11 x 22	12,500	-1210K
115 x 11 x M14 Threaded	11,000	-1220K

Shaft Mounted Brushes

Industrial rotary wire wheels & brushes are available as a comprehensive range including circular brushes, shaft mounted arbor style and de-carbonising brushes for use with power tools, machine tools and flexible drives.

Shaft Mounted: Suitable for use in power drills. Most suitable for hard to reach areas and grooves. 30 SWG.



Diameter x Width (mm)	Max. RPM	Order Code YRK-295
30 x 5	20,000	-2000K
30 x 10	20,000	-2010K
30 x 12	20,000	-2030K
40 x 13.5	20,000	-2140K
40 x 18	20,000	-2160K
50 x 10	15,000	-2320K
50 x 15	15,000	-2350K
50 x 20	15,000	-2370K
60 x 10	15,000	-2420K
60 x 15	15,000	-2450K
60 x 20	15,000	-2470K
70 x 10	15,000	-2620K
70 x 15	15,000	-2650K
70 x 20	15,000	-2670K
80 x 10	12,000	-2720K
80 x 15	12,000	-2750K
80 x 20	12,000	-2770K

Arbor Cup Brushes

Multi purpose brush for removal of rust, paint and burrs. Ideally suited for use on bench machines and angle grinders. 30 SWG



Dia (mm)	Arbor	Max. RPM	Order Code YRK-295
75	M14 Threaded	12,500	-4160K
100	M14 Threaded	10,000	-4180K
75	20mm Plain	12,500	-4310K
75	M14 Thrd	12,500	-4330K
75	5/8" BSW	12,500	-4340K
100	22mm Plain	10,000	-4400K
100	22mm Plain	10,000	-4420K
100	M14 Threaded	10,000	-4430K
100	5/8" BSW	10,000	-4440K
125	M14 Threaded	65,000	-4530K
125	5/8" BSW	65,000	-4540K
150	22mm Plain	65,000	-4620K
150	M14 Threaded	60,000	-4630K
75	M14 Threaded	12,500	-4700K
100	M14 Threaded	10,000	-4720K
100	M22 Plain	10,000	-4740K
65	M14 Threaded	12,500	-5230K
75	22mm Plain	85,000	-5320K
75	M14 Threaded	9,000	-5330K

Shaft Mounted Brass Wire Brushes

Suitable for use in power drills. Most suitable for hard to reach areas and grooves. 30SWG



Diameter x Width (mm)	Max. RPM	Order Code YRK-295
30 x 12	20,000	-2900K
50 x 10	15,000	-2920K
70 x 15	15,000	-2940K
80 x 20	12,000	-2960K

Brass Coated Wire Brushes

Suitable for removal of rust, paint and dirt from heavily covered parts. 30 SWG



Diameter x Width (mm)	Max. RPM	Order Code YRK-295
80 x 22	4,500	-0920K
100 x 20	6,000	-0940K
200 x 29	4,500	-0980K

Shaft Mounted Brass Coated Brushes

Suitable for use in power drills. Most suitable for hard to reach areas and grooves. 30SWG



Diameter x Width (mm)	Max. RPM	Order Code YRK-295
30 x 12	20,000	-2800K
50 x 10	15,000	-2820K
70 x 15	15,000	-2840K
80 x 20	12,000	-2860K

Stainless Steel Wire Cup Brush

Ideal for work on larger surfaces removing burrs, rust and paint.



Diameter x Width (mm)	Max. RPM	Order Code YRK-295
60 x 20	11,000	-4060K

Brass Wire Brushes

Suitable for removal of rust, paint and dirt from heavily covered parts. 30SWG



Diameter x Width (mm)	Max. RPM	Order Code YRK-295
80 x 22 x 20	4,500	-1300K
100 x 20 x 30	6,000	-1320K
150 x 21 x 51	6,000	-1340K
200 x 29 x 80	4,500	-1360K

Stainless Steel Wire Brush

For use in power drills and suitable for hard to reach areas and grooves.



Diameter x Width (mm)	Max. RPM	Order Code YRK-295
60 x 10	15,000	-8160K



Flat End Decarbonising Brushes

For hard to reach areas such as drilled holes, recesses and corners.
For removal of burrs, rust and paint.
30 SWG

Diameter (mm)	Max. RPM	Order Code YRK-295
Steel		
12	20,000	-6320K
17	20,000	-6440K
24	20,000	-6600K
30	20,000	-6800K
Brass		
12	20,000	-7100K
24	20,000	-7120K

Pointed End Decarbonising Brushes

For use in high speed air and electrical tools. Ideal for hard to reach areas. For the removal of paint, carbon and for de-burring.
30 SWG

Diameter (mm)	Max. RPM	Order Code YRK-295
Steel		
12	20,000	-7320K
17	20,000	-7440K
24	20,000	-7600K
30	20,000	-7800K
Brass		
12	20,000	-7980K
24	20,000	-8000K

Open Twist Tube Cleaning Brushes

For machine use in cleaning tubes and removing soft deposits in condenser and heat exchanger equipment. 1/4" BSW female universal thread for fitting to male extension rod joint (extension rods supplied separately). Available in brass coated or nylon open twist, sizes 1/4" to 1".



Dia. (mm)	Brush Length	Overall Length	Order Code YRK-295	
1/4"	60	100	-5700K	NA
3/8"	80	130	-5710K	
7/16"	60	130	-5720K	
1/2"	90	140	-5730K	
9/16"	90	140	-5740K	
5/8"	90	140	-5750K	
11/16"	90	140	-5760K	
3/4"	90	140	-5770K	
13/16"	90	140	-5780K	
7/8"	110	190	-5790K	
15/16"	110	190	-5800K	
1"	110	190	-5810K	

Dia. (mm)	Brush Length	Overall Length	Order Code YRK-295
1/4"	60	130	-5860K
3/8"	80	130	-5870K
7/16"	80	130	-5880K
1/2"	90	140	-5890K
9/16"	90	140	-5900K
5/8"	90	140	-5910K
11/16"	90	140	-5920K
3/4"	90	140	-5930K
7/8"	110	190	-5940K
15/16"	110	190	-5950K
1"	110	190	-5960K

KOBE

LED Floodlights

- Single Head
- COB LED bulb
- 230V
- Beam: 120°
- Aluminium Die-cast Alloy
- Includes: Wall Bracket



-5020K
No Sensor

-5220K

Product No.	Watts W	Volts V	Lumens lm	Sensor Type	Order Code KBE-282
KLF010	10	230	700	No Sensor	-5020K
KLF020	20	230	1400	No Sensor	-5040K
KLF030	30	230	2100	No Sensor	-5060K
KLF050	50	230	3500	No Sensor	-5080K
KFP010	10	230	700	PIR	-5220K
KFP020	20	230	1400	PIR	-5240K
KFP030	30	230	2100	PIR	-5260K
KFP050	50	230	3500	PIR	-5280K

Rechargeable LED Worklight

KLF010

- Single Head
- COB LED bulb
- 100W
- 12V/240V
- Beam: 120°
- Aluminium Die-cast alloy body
- 700 Lumens
- No Sensor
- IP65



Product No.	Watts W	Lumens lm	Order Code KBE-282
KLF010	100	700	-5500K

KENNEDY

Portable Task Lights

- Energy saving 38W 2D fluorescent bulb
- Tough poly-carbonate case
- Virtually shatterproof lens
- IP44
- For use indoor or outdoor
- Supplied with 3m rubberised mains lead



Volts V	Watts W	Order Code KEN-282
240	38	-4120K

KENNEDY

Mini-Pod Halogen Floodlights

- 500W
- 3m cable
- Halogen tube
- Epoxy coated
- Non-tipping frame
- For industrial, heavy duty use




Product No.	Watts W	Volts V	Order Code KEN-282
SMP240	500	240	-3820K

Replacement Halogen Mini-Pod Bulbs

Product No.	Watts W	Volts V	Order Code KEN-282
LP02824	500	240	-3100K

Cables for Site Use

- Waterproof spring loaded socket caps
- 1.5mm 2 core cables rated to 16A over six hours
- Number of sockets: 1
- Socket Type: 16A 3 Pin
- Type: Extensions
- Colour: Yellow (110V) and Blue (240V)



Cable Length m	No. of Sockets	Volts V	Order Code KEN-282
14	1	240	-2520K

KOBE

LED Telescopic Site Lights

- 20W
- 1400 Lumens
- Eco-friendly COB LED with low consumption
- Easy to transport and suitable for outdoor use
- IP65 Rated



Product No.	Volts V	Type	Order Code KBE-282
KSW020	240	Single	-5400K
KTW020	240	Twin	-5420K

EDISON Combi Stretch Light**TCS060**

Six LED stretch torch that can be used as either a torch or a lantern. Ultra bright energy-saving LEDs give a typical battery life of approximately 24 hours. Requires 4x AAA batteries (not included).

Overall length: 115mm.



Pull the housing open to illuminate a wider area or push to close for a focused beam of light



14m



10 lm

**LED**

Product Number	Weight	Order Code	
TCS060	100g	-2700K	NA

Super Bright LED Rechargeable Spotlight**ELRW306**

36 super bright LEDs. Push up telescopic design. Three light modes: 30 LED worklight - directional six LED torch - dual operation. Incorporated magnetic base. Shock, water and oil resistant. Rechargeable Li-ion battery. LED indicator and overcharge protection. Supplied with mains charger and in-car charger.

Operating times: 6 LED up to 25 hours, 30 LED up to five hours, 30+6 LED up to four hours.



Pull the housing open to illuminate a wider area or push to close for a focused beam of light

**LED**

Product Number	Weight	Order Code	
ELRW306	530g	-2730K	NA



80 lm



4/25hr

Torches

LED Torches

Six super bright white LEDs. 100,000 hour LED life. Battery life up to 50 hours (continuous). High strength aluminium alloy case. Corrosion-resistant anodised finish. Water and impact resistant. All joints sealed with 'O' rings.

Batteries required:

2x AA.

Length: 175 mm.

LED

Never needs a replacement bulb



Model Number	Casing	Order Code	
TAL010S	Aluminium	-2550K	NA
TAL010B	Black	-2560K	NA

LED Torch Battery Sets

2x LED torches with six super bright white LEDs. 100,000 hour LED life. Never needs a replacement bulb.

Contents: Two LED torches plus 4 packs (16) of AA batteries.

**LED**

Torch Casing	Length (mm)	Order Code	
Aluminium	175	-2922K	NA
Black	175	-2923K	NA

Aluminium Soft Grip LED Torches

Water and impact resistant anodised aluminium case with rubber grip. Ultra bright long life LEDs with optical lens to produce a clear white light. Positive push button operation. All joints sealed with 'O' rings.

Lumens/Beam Distance:

TAS03M: 15/20

TAS03S: 13/35

TAS05L: 14/22

TAS07L: 35/42



Lumens



Beam Distance



Model Number	Batteries Required	Length (mm)	Order Code	
TAS03M	3x AAA	130	-2610K	NA
TAS05L	2x C	180	-2620K	NA
TAS07L	2x D	213	-2630K	NA

EDISON 10W CREE LED Aluminum Torch

- Anodized aluminium body
- Adjustable beam focus
- 600 lumens
- IPx4

Beam distance: 140m.

Operating time: 8hrs.

Requires 3 x C batteries (not included)



600 lm



8 hr



140m

Product
Number

EAT010

Order Code
EDI-904

-5020K

NA

12 LED Headband Torch

- 35 lumens
- Beam distance: 20m
- Operating time: 8 hrs
- IPx4
- Requires: 3x AAA batteries (not included)

4 Lighting modes: 4 LEDs on, 8 LEDs on, 12 LEDs on, 12 LEDs flashing.



35 lm



8 hr



20m

Product
Number

EHT012

Order Code
EDI-904

-5060K

NA

3W COB + 7LED Rechargeable Lamp

- 2 lights - COB as lamp and 7 LED lights on the top
- Magnetic base and back
- 360° swivel hanging hooks
- IP20

Operating time: 2 - 2.5 hrs (high mode), 4 - 4.5 hrs (low mode), 10 hrs (top LEDs).

Charge time: 4 - 5 hrs.



7 LED Torch



320 lm



10 hr



20m

Product
Number

ERW230

Order Code
EDI-904

-1625E

NA

Aluminum LED Pen Light

- 40 lumens
- IPx4
- Requires 2 x AAA batteries (not included)

Beam distance: 20m.

Operating time: 2hrs.



40 lm



2 hr



20m

Product
Number

EPL005

Order Code
EDI-904

-5040K

NA

Aluminium Rechargeable Head Torch

Aluminium head and plastic body

- 120 lumens
- 1 x Li-ion battery included
- Operating time: 2 hrs
- IPx4
- Includes USB cable for charging

3 working modes: 100% on, 50% on and flashing

Beam distance: 115m.

Operating time: 2 hrs.



120 lm



2 hr



115m

Product
Number

ERH120

Order Code
EDI-904

-5080K

NA

Under Bonnet COB LED Rechargeable Worklight

- 36 COB LEDs
- Two power settings: 18/36 LEDs
- Detachable and extendable foam covered mounting bracket
- Strong magnets for hands-free applications
- Supplied with charger and 1x Li-ion rechargeable battery

Bracket range:

1210-1670mm

Overall lamp length:

1070mm



900 lm



3 hr

Product
Number

EBW230

Order Code
EDI-904

-1630H

NA

KENNEDY
QUALITY INDUSTRIAL TOOLING**5W COB + 1 LED
Rechargeable
Worklight**

Combined worklight and torch.

- 160 lumens
- Integrated magnet on the back
- Adjustable magnetic base
- USB charging cable
- IPx4
- 1 x Li-ion battery included



160 lm



3-4 hr



20m



Product Number	Weight each	Order Code	
ERW005	250g	EDI-904 -5120K	NA

**18 SMD LED Lithium-Ion
Rechargeable Worklight**

- Rubberised finish
- 300 lumens
- 3.7 V 2200mAh Li-ion battery
- 360 degree swivel hanging hook
- Integrated magnet on back

2 lighting modes: 100% on and 30% on

300 lm



2 hr



30m



Product Number	Weight each	Order Code	
DKWL2012U	280g	EDI-904 -5140K	NA

**EDISON 60 LED
Inspection Lights**

60 super bright white LEDs

- LED usage life: 100,000 hrs
- 120 lumens
- Built-in lithium rechargeable batteries
- Complete with 360 degree swivel hanging hook
- IPx4



120 lm



3-4 hr



20m

Product Number	Weight each	Order Code	
DKKH-8601	370g	EDI-904 -5160K	NA

**360 5W COB + 1 LED
Inspection Worklight**

Combined worklight and torch

- ABS plastic with rubberised finish
- 160 lumens
- Magnetic base
- IPx4
- Requires 3x AA batteries (not included)



160 lm



3-4 hr



20m

Product Number	Weight each	Order Code	
DKTN1003	180g	EDI-904 -5180K	NA

**3W CREE LED Rubber
Waterproof Torches**

Durable TPE rubber

- 150 lumens
- IPx7
- Requires 2 x D batteries (not included)

Beam distance: 110m.
Operating time: 16hrs.

150 lm



16 hr



110m

Product Number	Weight each	Order Code	
EWT003	300g	EDI-904 -5200K	NA

EDISON**Rechargeable Lantern**

- Candle Power: 1 Million
- Super bright quartz halogen spotlight/lantern
- Dual position locking handle
- 6V 4Ah sealed lead acid battery
- Weatherproof
- Supplied with AC/DC mains charger
- Cigarette RVDC car plug adapter
- Automatic thermal cut-out



Product Number	Length mm	Order Code	
ERS001	210	EDI-904 -2000K	NA

LED Rechargeable Spotlight**ELRS002**

90 lumens LED rechargeable spotlight. Super bright one watt LED light. Side LED tube light. Two position handle, to ensure comfortable and ergonomic access. Swivel handle. 4V 4Ah sealed lead acid battery. Supplied with AC/DC mains charger and 12V DC car plug adaptor for portable charging.

Battery operation times (10 hours full charge):

- Main spot light up to 6 hours.
- Side LED tube light up to 30 hours.

**Battery included****90 lm****6/30 hr****75m****RECHARGE ADAPTOR INCLUDED****LED****90 LUMENS**

Product Number	Length mm	Order Code	
ELRS002	2.0M	EDI-904 -1070K	NA

EDISON Super Bright LED Rechargeable Spotlight**ELRS001**

Weatherproof. High and standard brightness mode. SOS distress signal. Emergency light/blinking light. Two position handle, to ensure comfortable and ergonomic access. Swivel stand. Battery level indicator. 6V 4Ah sealed lead acid battery. Supplied with AC/DC mains charger and 12V DC car plug adaptor.

Battery operation times (18 hrs full charge):

- Standard brightness mode up to 8 hours.
- High brightness mode up to 3 hours.
- SOS distress mode up to 20 hours.
- Emergency light up to 25 hours.
- Emergency blinking light up to 30 hours.



247 lm



3/30 hr



250m

247 LUMENS



LED

Product Number	Weight	Order Code
ELRS001	1.46kg	EDI-904 -1060K

Waterproof SW LED Lantern

Super bright and waterproof.

- 200 lumens
- Beam distance: 150m
- Operating time: 20 hrs
- IPx7
- Requires 6V or 4 x D batteries (not included)

Beam distance: 150m.



200 lm



20 hr



150m

Description	Order Code	
Lantern	EDI-904 -5100K	NA

Rechargeable NiMH Battery**9V**

- Reducing the single use batteries
- Nickel Metal Hydride, suffer no voltage depression
- Contain no harmful cadmium, mercury or lead



Battery Size	mAh	Pack Qty	Order Code	
9V	170	1	EDI-904 -4440K	NA

50 Years of Keeping Industry Working
© 2022

EDISON Alkaline Batteries

A range of alkaline batteries that offer significantly longer life than zinc carbon batteries in high-drain appliances. Suitable for torches, radios, answerphones, toys, calculators, pagers, remote controls, smoke alarms and many other portable electrical appliances.

Bulk Value Battery Multi Pack

Contents	Order Code	Price/Pk
5 Packs AA & 2 Packs AAA	EDI-904 -5000K	NA



Battery Size	Volt	Pack Qty	Order Code	Price/Pk
AAA	1.5V	4	EDI-904 -3040K	NA
C	1.5V	2	EDI-904 -3080K	NA
D	1.5V	2	EDI-904 -3100K	NA
6LR61	9V	1	EDI-904 -3000K	NA